

# RcppArmadillo: Sparse Matrix Support

Binxiang Ni<sup>1</sup>, Dmitry Selivanov<sup>1</sup>, Dirk Eddelbuettel<sup>c</sup>, and Qiang Kou<sup>d</sup>

<sup>a</sup><https://github.com/binxiangni>; <sup>b</sup><https://github.com/dselivanov>; <sup>c</sup><http://dirk.eddelbuettel.com>; <sup>d</sup><https://github.com/thirdwing>

This version was compiled on February 18, 2025

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Sparse Matrix</b>	<b>2</b>
2.1	dgCMatrix . . . . .	2
2.2	dtCMatrix . . . . .	2
2.3	dsCMatrix . . . . .	3
2.4	dgTMatrix . . . . .	4
2.5	dtTMatrix . . . . .	4
2.6	dsTMatrix . . . . .	5
2.7	dgRMatrix . . . . .	6
2.8	dtRMatrix . . . . .	6
2.9	dsRMatrix . . . . .	7
2.10	indMatrix . . . . .	7
2.11	pMatrix . . . . .	8
2.12	ddiMatrix . . . . .	8

## 1. Introduction

The documentation is intended for the convenience of RcppArmadillo sparse matrix users based on integration of the documentation of library [Matrix](#) (Bates *et al.*, 2024) and [Armadillo](#) (Sanderson, 2010; Sanderson and Curtin, 2016).

There are 31 types of sparse matrices in the [Matrix](#) package that can be used directly. But for now, only 12 of them are supported in RcppArmadillo: dgCMatrix, dtCMatrix, dsCMatrix, dgTMatrix, dtTMatrix, dsTMatrix, dgRMatrix, dtRMatrix, dsRMatrix, indMatrix, pMatrix, ddiMatrix.

In the [Armadillo](#) library, sparse matrix content is currently stored as [CSC](#) format. Such kind of format is quite similar to numeric column-oriented sparse matrix in the library [Matrix](#) (including dgCMatrix, dtCMatrix and dsCMatrix). When a sparse matrix from the package [Matrix](#) is passed through the [RcppArmadillo](#) package (Eddelbuettel and Sanderson, 2014; Eddelbuettel *et al.*, 2024), it will be converted or mapped to CSC format, then undertaken operations on, and finally output as a dgCMatrix in R.

In what follows, we will always assume this common header:

```
#include <RcppArmadillo.h>
// [[Rcpp::depends(RcppArmadillo)]]
```

but do not generally show it. We recommend explicitly prefixing namespaces with Rcpp:: or arma:: as appropriate.

## 2. Sparse Matrix

### 2.1. dgCMatrix.

#### Synopsis.

- Description: general column-oriented numeric sparse matrix.
- Constructor
  - `new("dgCMatrix", ...)`
  - `Matrix(*, sparse = TRUE)`
  - `sparseMatrix()`
- Coercion
  - `as(*, "CsparseMatrix")`
  - `as(*, "dgCMatrix")`

#### C++ Code.

```
// [[Rcpp::export]]
arma::sp_mat sqrt_(arma::sp_mat X) {
  return arma::sqrt(X);
}
```

#### R Code.

```
R> i <- c(1,3:8)
R> j <- c(2,9,6:10)
R> x <- 7 * (1:7)
R> A <- sparseMatrix(i, j, x = x)
R> sqrt_(A)
8 x 10 sparse Matrix of class "dgCMatrix"

[1,] . 2.645751 . . . . . . . .
[2,] . . . . . . . . . .
[3,] . . . . . . . 3.741657 .
[4,] . . . . 4.582576 . . . .
[5,] . . . . . 5.291503 . . .
[6,] . . . . . . 5.91608 . .
[7,] . . . . . . . 6.480741 .
[8,] . . . . . . . . 7
```

### 2.2. dtCMatrix.

#### Synopsis.

- Description: triangular column-oriented numeric sparse matrix.
- Constructor
  - `new("dtCMatrix", ...)`
  - `Matrix(*, sparse = TRUE)`
  - `sparseMatrix(*, triangular=TRUE)`
- Coercion
  - `as(*, "triangularMatrix")`
  - `as(*, "dtCMatrix")`

#### C++ Code.

```
// [[Rcpp::export]]
arma::sp_mat symmatl_(arma::sp_mat X) {
  return arma::symmatl(X);
}
```

#### R Code.

```
R> dtC <- new("dtCMatrix", Dim = c(5L, 5L), uplo = "L",
             x = c(10, 1, 3, 10, 1, 10, 1, 10, 10),
             i = c(0L, 2L, 4L, 1L, 3L, 2L, 4L, 3L, 4L),
             p = c(0L, 3L, 5L, 7:9))
R> symmatl_(dtC)
5 x 5 sparse Matrix of class "dtCMatrix"

[1,] 10 . 1 . 3
[2,] . 10 . 1 .
[3,] 1 . 10 . 1
[4,] . 1 . 10 .
[5,] 3 . 1 . 10
```

### 2.3. dsCMatrix.

#### Synopsis.

- Description: symmetric column-oriented numeric sparse matrix.
- Constructor
  - `new("dsCMatrix", ...)`
  - `Matrix(*, sparse = TRUE)`
  - `sparseMatrix(*, symmetric = TRUE)`
- Coercion
  - `as(*, "symmetricMatrix")`
  - `as(*, "dsCMatrix")`

#### C++ Code.

```
// [[Rcpp::export]]
arma::sp_mat trimatu_(arma::sp_mat X) {
  return arma::trimatu(X);
}
```

#### R Code.

```
R> i <- c(1,3:8)
R> j <- c(2,9,6:10)
R> x <- 7 * (1:7)
R> dsC <- sparseMatrix(i, j, x = x, symmetric = TRUE)
R> trimatu_(dsC)
10 x 10 sparse Matrix of class "dgCMatrix"

[1,] . 7 . . . . . . .
```

```
[2,] . . . . . . . . . .
[3,] . . . . . . . . 14 .
[4,] . . . . . 21 . . . .
[5,] . . . . . . 28 . . .
[6,] . . . . . . . 35 . .
[7,] . . . . . . . . 42 .
[8,] . . . . . . . . . 49
[9,] . . . . . . . . . .
[10,] . . . . . . . . . .
```

## 2.4. dgTMatrix.

### Synopsis.

- Description: general numeric sparse matrix in triplet form.
- Constructor
  - `new("dgTMatrix", ...)`
  - `sparseMatrix(*, giveCsparse=FALSE)`
  - `spMatrix()`
- Coercion
  - `as(*, "TsparseMatrix")`
  - `as(*, "dgTMatrix")`

### C++ Code.

```
// [[Rcpp::export]]
arma::sp_mat multiply(arma::sp_mat A, arma::sp_mat B) {
  return A * B;
}

// [[Rcpp::export]]
arma::sp_mat trans_(arma::sp_mat X) {
  return arma::trans(X);
}

// [[Rcpp::export]]
int trace_(arma::sp_mat X) {
  return arma::trace(X);
}
```

### R Code.

```
R> dgT <- new("dgTMatrix", i = c(1L,1L,0L,3L,3L), j = c(2L,2L,4L,0L,0L),
             x=10*1:5, Dim=4:5)
R> dgT_t <- trans_(dgT)
R> prod <- multiply(dgT, dgT_t)
R> trace_(prod)
[1] 9900
```

## 2.5. dtTMatrix.

### Synopsis.

- Description: triangular numeric sparse matrix in triplet form.
- Constructor
  - `new("dtTMatrix", ...)`
  - `sparseMatrix(*, triangular=TRUE, giveCsparse=FALSE)`
- Coercion
  - `as(*, "triangularMatrix")`
  - `as(*, "dtTMatrix")`

### C++ Code.

```
// [[Rcpp::export]]
arma::sp_mat diag_ones(arma::sp_mat X) {
  X.diag().ones();
  return X;
}
```

### R Code.

```
R> dtT <- new("dtTMatrix", x= c(3,7), i= 0:1, j=3:2, Dim= as.integer(c(4,4)))
R> diag_ones(dtT)
4 x 4 sparse Matrix of class "dgCMatrix"

[1,] 1 . . 3
[2,] . 1 7 .
[3,] . . 1 .
[4,] . . . 1
```

## 2.6. dsTMatrix.

### Synopsis.

- Description: symmetric numeric sparse matrix in triplet form.
- Constructor
  - `new("dsTMatrix", ...)`
  - `sparseMatrix(*, symmetric=TRUE, giveCsparse=FALSE)`
- Coercion
  - `as(*, "symmetricMatrix")`
  - `as(*, "dsTMatrix")`

### C++ Code.

```
// [[Rcpp::export]]
int trace_(arma::sp_mat X) {
  return arma::trace(X);
}
```

### R Code.

```
R> mm <- Matrix(toeplitz(c(10, 0, 1, 0, 3)), sparse = TRUE)
R> mT <- as(mm, "dgTMatrix")
R> dsT <- as(mT, "symmetricMatrix")
R> trace_(dsT)
[1] 50
```

## 2.7. dgRMatrix.

### Synopsis.

- Description: general row-oriented numeric sparse matrix.
- Constructor
  - `new("dgRMatrix", ...)`
- Coercion
  - `as(*, "RsparseMatrix")`
  - `as(*, "dgRMatrix")`

### C++ Code.

```
// [[Rcpp::export]]
arma::sp_mat square_(arma::sp_mat X) {
  return arma::square(X);
}
```

### R Code.

```
R> dgR <- new("dgRMatrix", j=c(0L,2L,1L,3L), p=c(0L,2L,3L,3L,4L),
              x=c(3,1,2,1), Dim=rep(4L,2))
R> square_(dgR)
4 x 4 sparse Matrix of class "dgCMatrix"

[1,] 9 . 1 .
[2,] . 4 . .
[3,] . . . .
[4,] . . . 1
```

## 2.8. dtRMatrix.

### Synopsis.

- Description: triangular row-oriented numeric sparse matrix.
- Constructor
  - `new("dtRMatrix", ...)`

### C++ Code.

```
// [[Rcpp::export]]
arma::sp_mat repmat_(arma::sp_mat X, int i, int j) {
  return arma::repmat(X, i, j);
}
```

### R Code.

```
R> dtR <- new("dtRMatrix", Dim = c(2L,2L), x = c(5, 1:2), p = c(0L,2:3), j= c(0:1,1L))
R> repmat_(dtR, 2, 2)
4 x 4 sparse Matrix of class "dgCMatrix"

[1,] 5 1 5 1
[2,] . 2 . 2
[3,] 5 1 5 1
[4,] . 2 . 2
```

## 2.9. dsRMatrix.

### Synopsis.

- Description: symmetric row-oriented numeric sparse matrix.
- Constructor
  - `new("dsRMatrix", ...)`
- Coercion
  - `as("dsCMatrix", "dsRMatrix")`

### C++ Code.

```
// [[Rcpp::export]]
arma::sp_mat sign_(arma::sp_mat X) {
  return arma::sign(X);
}
```

### R Code.

```
R> dsR <- new("dsRMatrix", Dim = c(2L,2L), x = c(-3,1), j = c(1L,1L), p = 0:2)
R> sign_(dsR)
2 x 2 sparse Matrix of class "dgCMatrix"

[1,] . -1
[2,] -1 1
```

## 2.10. indMatrix.

### Synopsis.

- Description: index matrix.
- Constructor
  - `new("indMatrix", ...)`
- Coercion
  - `as(*, "indMatrix")`

### C++ Code.

```
// [[Rcpp::export]]
arma::sp_mat multiply(arma::sp_mat A, arma::sp_mat B) {
  return A * B;
}
```

#### R Code.

```
R> ind <- as(2:4, "indMatrix")
R> dgT <- new("dgTMatrix", i = c(1L,1L,0L,3L,3L), j = c(2L,2L,4L,0L,0L),
              x=10*1:5, Dim=4:5)
R> multiply(ind, dgT)
3 x 5 sparse Matrix of class "dgCMatrix"

[1,] . . 30 . .
[2,] . . . . .
[3,] 90 . . . .
```

### 2.11. pMatrix.

#### Synopsis.

- Description: permutation matrix.
- Constructor
  - new("pMatrix", ...)
- Coercion
  - as(\*, "pMatrix")

#### C++ Code.

```
// [[Rcpp::export]]
arma::sp_mat multiply(arma::sp_mat A, arma::sp_mat B) {
  return A * B;
}
```

#### R Code.

```
R> pM <- as(c(2,3,1,4), "pMatrix")
R> dgT <- new("dgTMatrix", i = c(1L,1L,0L,3L,3L), j = c(2L,2L,4L,0L,0L),
              x=10*1:5, Dim=4:5)
R> multiply(pM, dgT)
4 x 5 sparse Matrix of class "dgCMatrix"

[1,] . . 30 . .
[2,] . . . . .
[3,] . . . . 30
[4,] 90 . . . .
```

### 2.12. ddiMatrix.



### Synopsis.

- Description: numeric diagonal Matrix.
- Constructor
  - `new("ddiMatrix", ...)`
  - `Diagonal(*)`

### C++ Code.

```
// [[Rcpp::export]]
arma::sp_mat multiply(arma::sp_mat A, arma::sp_mat B) {
  return A * B;
}
```

### R Code.

```
R> ddi <- Diagonal(4)
R> dgR <- new("dgRMatrix", j=c(0L,2L,1L,3L), p=c(0L,2L,3L,3L,4L),
             x=c(3,1,2,1), Dim=rep(4L,2))
R> multiply(ddi, dgR)
4 x 4 sparse Matrix of class "dgCMatrix"

[1,] 3 . 1 .
[2,] . 2 . .
[3,] . . . .
[4,] . . . 1
```

## References

- Bates D, Maechler M, Jagan M (2024). *Matrix: Sparse and Dense Matrix Classes and Methods*. doi:10.32614/CRAN.package.Matrix. R package version 1.7-1, URL <http://CRAN.R-Project.org/package=Matrix>.
- Eddelbuettel D, Francois R, Bates D, Ni B, Sanderson C (2024). *RcppArmadillo: 'Rcpp' Integration for the 'Armadillo' Templated Linear Algebra Library*. doi:10.32614/CRAN.package.RcppArmadillo. R package version 14.2.2-1, URL <http://CRAN.R-Project.org/package=RcppArmadillo>.
- Eddelbuettel D, Sanderson C (2014). "RcppArmadillo: Accelerating R with high-performance C++ linear algebra." *Computational Statistics and Data Analysis*, **71**, 1054–1063. doi:10.1016/j.csda.2013.02.005. URL <http://dx.doi.org/10.1016/j.csda.2013.02.005>.
- Sanderson C (2010). "Armadillo: An open source C++ Algebra Library for Fast Prototyping and Computationally Intensive Experiments." *Technical report*, NICTA. URL <http://arma.sourceforge.net>.
- Sanderson C, Curtin R (2016). "Armadillo: A Template-Based C++ Library for Linear Algebra." *JOSS*, **1**(2). doi:10.21105/joss.00026. URL <http://dx.doi.org/10.21105/joss.00026>.