

# Package ‘RAQSAPI’

January 27, 2022

**Type** Package

**Version** 2.0.3

**Title** A Simple Interface to the US EPA Air Quality System Data Mart API

**Description** Retrieve air monitoring data and associated metadata from the US Environmental Protection Agency's Air Quality System service using functions. See <[https://aqs.epa.gov/aqsweb/documents/data\\_api.html](https://aqs.epa.gov/aqsweb/documents/data_api.html)> for details about the US EPA Data Mart API.

**Encoding** UTF-8

**URL** <<https://github.com/USEPA/RAQSAPI>>,  
<[https://aqs.epa.gov/aqsweb/documents/data\\_api.html](https://aqs.epa.gov/aqsweb/documents/data_api.html)>

**BugReports** <https://github.com/USEPA/RAQSAPI/issues>

**Depends** R (>= 4.0.0)

**Imports** dplyr,

glue,  
httr,  
jsonlite,  
lubridate,  
magrittr,  
purrr,  
stringr,  
tibble,  
rlang,  
lifecycle

**Suggests** spelling,

desc,  
devtools,  
goodpractice,  
keyring,  
knitr,  
markdown,  
roxygen2,  
rmarkdown,  
testthat (>= 3.0.0),  
usethis,  
covr

**SystemRequirements** package manual requires pandoc (>= 1.14) <http://pandoc.org>

**RoxygenNote** 7.1.2

**VignetteBuilder** knitr  
**BuildVignettes** true  
**ByteCompile** true  
**License** CC0  
**License\_is\_FOSS** yes  
**NeedsCompilation** no  
**License\_restricts\_use** no  
**Language** en-US  
**Collate** 'AQSAPI\_helperfunctions.R'  
           'bysite.R'  
           'bycounty.R'  
           'bystate.R'  
           'byma.R'  
           'bypqao.R'  
           'bycbas.R'  
           'bybox.R'  
           'RAQSAPIlistfunctions.R'  
           'setupfunctions.R'  
           'zzz.R'  
           'RAQSAPI-package.R'  
**Copyright** United States Environmental Protection Agency  
**RdMacros** lifecycle  
**Roxygen** list(markdown = TRUE)  
**Config/testthat/edition** 3

## R topics documented:

aqs_annualsummary_by_box . . . . .	4
aqs_annualsummary_by_cbsa . . . . .	6
aqs_annualsummary_by_county . . . . .	8
aqs_annualsummary_by_site . . . . .	9
aqs_annualsummary_by_state . . . . .	11
aqs_cbsas . . . . .	13
aqs_classes . . . . .	14
aqs_counties_by_state . . . . .	15
aqs_credentials . . . . .	15
aqs_dailysummary_by_box . . . . .	16
aqs_dailysummary_by_cbsa . . . . .	18
aqs_dailysummary_by_county . . . . .	19
aqs_dailysummary_by_site . . . . .	21
aqs_dailysummary_by_state . . . . .	23
aqs_fields_by_service . . . . .	25
aqs_isavailable . . . . .	25
aqs_knownissues . . . . .	26
aqs_mas . . . . .	27
aqs_metadata_service . . . . .	27
aqs_monitors_by_box . . . . .	28
aqs_monitors_by_cbsa . . . . .	29

aqs_monitors_by_county . . . . .	31
aqs_monitors_by_site . . . . .	32
aqs_monitors_by_state . . . . .	34
aqs_parameters_by_class . . . . .	35
aqs_pqaos . . . . .	36
aqs_qa_annualperformanceeval_by_MA . . . . .	37
aqs_qa_annualperformanceeval_by_pqao . . . . .	38
aqs_qa_annualperformanceeval_by_site . . . . .	39
aqs_qa_annualperformanceeval_by_state . . . . .	41
aqs_qa_annualperformanceevaltransaction_by_county . . . . .	43
aqs_qa_annualperformanceevaltransaction_by_MA . . . . .	44
aqs_qa_annualperformanceevaltransaction_by_pqao . . . . .	46
aqs_qa_annualperformanceevaltransaction_by_site . . . . .	47
aqs_qa_annualperformanceevaltransaction_by_state . . . . .	49
aqs_qa_annualperformanceeval_by_county . . . . .	50
aqs_qa_blanks_by_county . . . . .	52
aqs_qa_blanks_by_MA . . . . .	54
aqs_qa_blanks_by_pqao . . . . .	55
aqs_qa_blanks_by_site . . . . .	57
aqs_qa_blanks_by_state . . . . .	59
aqs_qa_collocated_assessments_by_county . . . . .	61
aqs_qa_collocated_assessments_by_MA . . . . .	62
aqs_qa_collocated_assessments_by_pqao . . . . .	64
aqs_qa_collocated_assessments_by_site . . . . .	66
aqs_qa_collocated_assessments_by_state . . . . .	67
aqs_qa_flowrateaudit_by_county . . . . .	69
aqs_qa_flowrateaudit_by_MA . . . . .	71
aqs_qa_flowrateaudit_by_pqao . . . . .	72
aqs_qa_flowrateaudit_by_site . . . . .	74
aqs_qa_flowrateaudit_by_state . . . . .	76
aqs_qa_flowrateverification_by_county . . . . .	77
aqs_qa_flowrateverification_by_MA . . . . .	79
aqs_qa_flowrateverification_by_pqao . . . . .	81
aqs_qa_flowrateverification_by_site . . . . .	82
aqs_qa_flowrateverification_by_state . . . . .	84
aqs_qa_one_point_qc_by_county . . . . .	86
aqs_qa_one_point_qc_by_MA . . . . .	88
aqs_qa_one_point_qc_by_pqao . . . . .	89
aqs_qa_one_point_qc_by_site . . . . .	91
aqs_qa_one_point_qc_by_state . . . . .	93
aqs_qa_pep_audit_by_county . . . . .	94
aqs_qa_pep_audit_by_MA . . . . .	96
aqs_qa_pep_audit_by_pqao . . . . .	98
aqs_qa_pep_audit_by_site . . . . .	99
aqs_qa_pep_audit_by_state . . . . .	101
aqs_quarterlysummary_by_box . . . . .	103
aqs_quarterlysummary_by_cbsa . . . . .	105
aqs_quarterlysummary_by_county . . . . .	106
aqs_quarterlysummary_by_site . . . . .	108
aqs_quarterlysummary_by_state . . . . .	110
aqs_removeheader . . . . .	111
aqs_revisionhistory . . . . .	112

aqs_sampledata_by_box . . . . .	113
aqs_sampledata_by_cbsa . . . . .	115
aqs_sampledata_by_county . . . . .	117
aqs_sampledata_by_site . . . . .	119
aqs_sampledata_by_state . . . . .	121
aqs_sampledurations . . . . .	123
aqs_services_by_box . . . . .	123
aqs_services_by_cbsa . . . . .	125
aqs_services_by_county . . . . .	126
aqs_services_by_MA . . . . .	127
aqs_services_by_pqao . . . . .	128
aqs_services_by_site . . . . .	129
aqs_services_by_state . . . . .	131
aqs_sign_up . . . . .	132
aqs_sites_by_county . . . . .	133
aqs_states . . . . .	134
aqs_transactionsample_by_county . . . . .	134
aqs_transactionsample_by_MA . . . . .	136
aqs_transactionsample_by_site . . . . .	137
aqs_transactionsample_by_state . . . . .	139
RAQSAPI . . . . .	141

## Index 142

---

aqs\_annualsummary\_by\_box  
*aqs\_annualsummary\_by\_box*

---

## Description

**[Stable]** Returns multiple years of data where annual data is aggregated at the bounding box level. Returned is an annual summary within the input parameter, latitude/longitude bounding box provided for bdate - edate time frame. Variables returned include mean value, maxima, percentiles, and etc. If return\_header is FALSE (default) the object returned is a tibble, if TRUE an AQS\_API\_v2 object.

## Usage

```
aqs_annualsummary_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object which represents the minimum latitude of a geographic box. Decimal latitude with north begin positive. Only data north of this latitude will be returned.
maxlat	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north begin positive. Only data south of this latitude will be returned.
minlon	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.
maxlon	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east begin positive. Only data west of this longitude will be returned. Note that -80 is less than -70.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object that containing annual summary data for the box (area) requested. A AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (`Header`) is a tibble of header information from the AQS API and the second item (`Data`) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate \_by\_box functions: [aq<sub>s</sub>\\_monitors\\_by\\_box\(\)](#), [aq<sub>s</sub>\\_sampledata\\_by\\_box\(\)](#)

**Examples**

```
# returns a tibble containing ozone annual summaries
# in the vicinity of central Alabama for the first two days
# in May, 2015
## Not run: aqs_annualsummary_by_box(parameter = "44201",
                                     bdate = as.Date("20150501",
                                                       format = "%Y%m%d"),
                                     edate = as.Date("20170502",
                                                       format = "%Y%m%d"),
                                     minlat = "33.3",
                                     maxlat = "33.6",
                                     minlon = "-87.0",
                                     maxlon = "-86.7"
                                     )

## End(Not run)
```

---

aq<sub>s</sub>\_annualsummary\_by\_cbsa

*aq<sub>s</sub>\_annualsummary\_by\_cbsa*

---

**Description**

**[Stable]** Returns multiple years of data where annual data is aggregated at the Core Based Statistical Area (CBSA) level. Returned is an annual summary matching the input parameter, and cbsa\_code provided for bdate - edate time frame. Variables returned include mean value, maxima, percentiles, and etc. If return\_header is FALSE (default) the object returned is a tibble, if TRUE an AQS\_API\_v2 object.

**Usage**

```
aqs_annualsummary_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.

edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros)
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object that containing annual summary data for the cbsa\_code requested. A AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_cbsa functions: [aqsum\\_dailysummary\\_by\\_cbsa\(\)](#), [aqsum\\_monitors\\_by\\_cbsa\(\)](#), [aqsum\\_sampledata\\_by\\_cbsa\(\)](#)

### Examples

```
# returns a tibble of annual summary NO2
# data the for Charlotte-Concord-Gastonia, NC cbsa for
# January 01, 2017
## Not run: aqsum_by_cbsa(parameter = "42602",
                           bdate = as.Date("20170101",
                                             format = "%Y%m%d"),
                           edate = as.Date("20170101",
                                             format = "%Y%m%d"),
                           cbsa_code = "16740")
```

```
## End(Not run)
```

---

```
aqs_annualsummary_by_county
      aqs_annualsummary_by_county
```

---

## Description

**[Stable]** Returns multiple years of data where annual data is aggregated at the county level. Returned is an annual summary matching the input parameter, stateFIPS, and county\_code provided for bdate - edate time frame. Variables returned include mean value, maxima, percentiles, and etc. If return\_header is FALSE (default) the object returned is a tibble, if TRUE an AQS\_API\_v2 object.

## Usage

```
aqs_annualsummary_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

**return\_header** If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object that containing annual summary data for the countycode and stateFIPS requested. A AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_county functions: [aq\\$dailysummary\\_by\\_county\(\)](#), [aq\\$monitors\\_by\\_county\(\)](#), [aq\\$qa\\_annualperformanceeval\\_by\\_county\(\)](#), [aq\\$qa\\_blanks\\_by\\_county\(\)](#), [aq\\$qa\\_collocated\\_assessments\\_by\\_county\(\)](#), [aq\\$qa\\_flowrateaudit\\_by\\_county\(\)](#), [aq\\$qa\\_flowrateverification\\_by\\_county\(\)](#), [aq\\$qa\\_one\\_point\\_qc\\_by\\_county\(\)](#), [aq\\$qa\\_pep\\_audit\\_by\\_county\(\)](#), [aq\\$quarterlysummary\\_by\\_county\(\)](#), [aq\\$quarterlysummary\\_by\\_site\(\)](#), [aq\\$sampled\\_data\\_by\\_county\(\)](#), [aq\\$transactionsample\\_by\\_county\(\)](#)

### Examples

```
# returns an aqs S3 object with annual summary FRM/FEM
# PM2.5 data for Wake County, NC between January
# and February 2016
## Not run: aqs_annualsummary_by_county(parameter = "88101",
#                                     bdate = as.Date("20160101",
#                                     format = "%Y%m%d"),
#                                     edate = as.Date("20160228",
#                                     format = "%Y%m%d"),
#                                     stateFIPS = "37",
#                                     countycode = "183"
#                                     )

## End(Not run)
```

---

aq\$annualsummary\_by\_site

*aq\$annualsummary\_by\_site*

---

## Description

**[Stable]** Returns multiple years of data where annual data is aggregated at the site level. Returned is an annual summary matching the input parameter, stateFIPS, county\_code, and sitenum provided for bdate - edate time frame. The data returned is summarized at the annual level. Variables returned include mean value, maxima, percentiles, and etc. If return\_header is FALSE (default) the object returned is a tibble, if TRUE an AQS\_API\_v2 object.

## Usage

```
aqs_annualsummary_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested as a single tibble. If TRUE returns a list of AQSAPI_v2 objects which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing annual summary data for the sitenum, countycode and stateFIPS requested. A AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_site functions: [aq\\$\\_dailysummary\\_by\\_site\(\)](#), [aq\\$\\_monitors\\_by\\_site\(\)](#), [aq\\$\\_qa\\_annualperformanceeval\\_by\\_site\(\)](#), [aq\\$\\_qa\\_annualperformanceevaltransaction\\_by\\_county\(\)](#), [aq\\$\\_qa\\_annualperformanceevaltransaction\\_by\\_site\(\)](#), [aq\\$\\_qa\\_blanks\\_by\\_site\(\)](#), [aq\\$\\_qa\\_collocated\\_asse](#), [aq\\$\\_qa\\_flowrateaudit\\_by\\_site\(\)](#), [aq\\$\\_qa\\_flowrateverification\\_by\\_site\(\)](#), [aq\\$\\_qa\\_one\\_point\\_qc\\_by\\_site](#), [aq\\$\\_qa\\_pep\\_audit\\_by\\_site\(\)](#), [aq\\$\\_sampledata\\_by\\_site\(\)](#), [aq\\$\\_services\\_by\\_site\(\)](#), [aq\\$\\_transactionsample](#)

**Examples**

```
# Returns a tibble of annual summary ozone
# data for the Millbrook School site (\#0014) in Wake County,
# NC for 2017 (Note, for annual data, only the
# year portion of the bdate and edate are used and only whole
# years of data are returned. For example, bdate = 2017-12-31 and
# edate = 2018-01-01 will return full data for 2017 and 2018 )
## Not run:
aq$annualsummary_by_site(parameter = "44201",
                        bdate = as.Date("20170618",
                                         format="%Y%m%d"),
                        edate = as.Date("20190618",
                                         format="%Y%m%d"),
                        stateFIPS = "37",
                        countycode = "183",
                        sitenum = "0014"
                        )

## End(Not run)
```

---

aq\$annualsummary\_by\_state

*aq\$annualsummary\_by\_state*

---

## Description

**[Stable]** Returns multiple years of data where annual data is aggregated at the state level. Returned is an annual summary matching the input parameter and stateFIPS provided for bdate - edate time frame. The data returned is summarized at the annual level. Variables returned include mean value, maxima, percentiles, and etc. If return\_header is FALSE (default) the object returned is a tibble, if TRUE an AQS\_API\_v2 object.

## Usage

```
aqs_annualsummary_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aq<sub>s</sub>_states()</a> for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

## Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object that containing annual summary data for the state-FIPS requested. A AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_state functions: [aqs\\_dailysummary\\_by\\_state\(\)](#), [aqs\\_monitors\\_by\\_state\(\)](#), [aqs\\_qa\\_blanks\\_by\\_state\(\)](#), [aqs\\_qa\\_collocated\\_assessments\\_by\\_state\(\)](#), [aqs\\_qa\\_flowrateaudit\\_by\\_state\(\)](#), [aqs\\_qa\\_flowrateverification\\_by\\_state\(\)](#), [aqs\\_qa\\_one\\_point\\_qc\\_by\\_state\(\)](#), [aqs\\_qa\\_pep\\_audit\\_by\\_state\(\)](#), [aqs\\_sampledata\\_by\\_state\(\)](#)

**Examples**

```
# returns a tibble of all benzene annualy
# summaries from North Carolina collected for 1995
## Not run: aqs_annualsummary_by_state(parameter = "45201",
                                     bdate = as.Date("19950515",
                                     format="%Y%m%d"
                                     ),
                                     edate = as.Date("19950515",
                                     format = "%Y%m%d"
                                     ),
                                     stateFIPS = "37"
                                     )

## End(Not run)
```

---

aqs_cbsas	<i>aqs_cbsas</i>
-----------	------------------

---

**Description**

**[Stable]** Returns a table of all Core Based Statistical Areas (cbsa) and their associated cbsa\_codes. for constructing other requests.

**Usage**

```
aqs_cbsas(return_header = FALSE)
```

**Arguments**

return\_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of all Core Based Statistical Areas (cbsa) and their cbsa\_codes for constructing other requests.

**Examples**

```
#returns a tibble or an AQS_Data Mart_APIv2 S3 object of cbsas
# and their respective cbsa codes
## Not run: aqs_cbsas()
```

---

aq <sub>s</sub> _classes	<i>aq<sub>s</sub>_classes</i>
--------------------------	-------------------------------

---

**Description**

**[Stable]** Returns a table of Parameter classes (groups of parameters, i.e. "criteria" or "all"). The information from this function can be used as input to other API calls.

**Usage**

```
aqs_classes(return_header = FALSE)
```

**Arguments**

**return\_header** If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of Parameter classes (groups of parameters, i.e. "criteria" or "all").

**Examples**

```
#returns a tibble or an AQS_Data Mart_APIv2 S3 object of
# parameter classes (groups of parameters, i.e. "criteria" or
# all")
## Not run: aqs_classes()
```

---

aqs\_counties\_by\_state    *aqs\_counties\_by\_state*


---

**Description**

**[Stable]** Returns a table of all counties in within the stateFIPS provided.

**Usage**

```
aqs_counties_by_state(stateFIPS, return_header = FALSE)
```

**Arguments**

stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zeros) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of all counties in the requested state.

**Examples**

```
#returns a tibble all the counties
#   in North Carolina the county FIPS codes (county codes) for
#   each.
## Not run: aqs_counties_by_state(stateFIPS = "37")
```

---

aqs\_credentials    *aqs\_credentials*


---

**Description**

**[Stable]** Sets the user credentials for the AQS API. This function needs to be called once and only once every time this library is re-loaded. Users must have a valid username and key which can be obtained through the use of the aqs\_sign\_up function, @seealso [aqs\\_sign\\_up\(\)](#) to sign up for AQS data mart credentials.

**Usage**

```
aqs_credentials(username = NA_character_, key = NA_character_)
```

**Arguments**

username	a R character object which represents the email account that will be used to connect to the AQS API.
key	the key used in conjunction with the username given to connect to AQS Data Mart.

**Value**

None

**RAQSAPI setup functions**

NA

**Examples**

```
#to authenticate an existing user the email address
# "John.Doe@myemail.com" and key = "MyKey"
# after calling this function please follow the instructions that are sent
# in the verification e-mail before proceeding.
## Not run: aqs_credentials(username = "John.Doe@myemail.com",
                           key = "MyKey")

## End(Not run)
```

---

aq\_s\_dailysummary\_by\_box

*aq\_s\_dailysummary\_by\_box*


---

**Description**

**[Stable]** Returns a tibble or an AQS\_Data Mart\_APIv2 S3 object containing daily summary data bounded within a latitude/longitude bounding box

**Usage**

```
aq_s_dailysummary_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.



```

format = "%Y%m%d"
),
mqinlat = "33.3",
maxlat = "33.6",
minlon = "-87.0",
maxlon = "-86.7"
)

## End(Not run)

```

---

aqs\_dailysummary\_by\_cbsa

*aqs\_dailysummary\_by\_cbsa*


---

## Description

**[Stable]** Returns a tibble or an AQS\_Data Mart\_APIv2 S3 object containing daily summary data aggregated by cbsa (Core Based Statistical Area) code.

## Usage

```

aqs_dailysummary_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros)
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object that contains daily summary statistics for the given parameter for a single cbsa\_code. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of summary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_cbsa functions: [aqsummary\\_by\\_cbsa\(\)](#), [aqmonitors\\_by\\_cbsa\(\)](#), [aqsampledata\\_by\\_cbsa\(\)](#)

**Examples**

```
# returns a tibble of daily summary NO2
# data the for Charlotte-Concord-Gastonia, NC cbsa for
# January 01, 2017
## Not run: aqsummary_by_cbsa(parameter = "42602",
                             bdate = as.Date("20170101",
                                                format = "%Y%m%d"
                                                ),
                             edate = as.Date("20190101",
                                                format = "%Y%m%d"
                                                ),
                             cbsa_code = "16740"
                             )

## End(Not run)
```

---

aqsummary\_by\_county

*aqsummary\_by\_county*

---

**Description**

**[Stable]** Returns multiple years of data where daily data is aggregated at the site level. Returned is a daily summary matching the input parameter, stateFIPS and county\_code provided for bdate - edate time frame. Variables returned include mean value, maxima, percentiles, and etc.

**Usage**

```
aqs_dailysummary_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object that contains daily summary statistics for the given parameter for a single countycode and stateFIPS combination. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of dailysummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar

year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_county functions: [aqsanualsummary\\_by\\_county\(\)](#), [aqsmotors\\_by\\_county\(\)](#), [aqsqannualperformanceeval\\_by\\_county\(\)](#), [aqsqablanks\\_by\\_county\(\)](#), [aqsqacollocatedassessments\\_by\\_county\(\)](#), [aqsqflowrateaudit\\_by\\_county\(\)](#), [aqsqflowrateverification\\_by\\_county\(\)](#), [aqsqonepointqc\\_by\\_county\(\)](#), [aqsqpep\\_audit\\_by\\_county\(\)](#), [aqsqquarterlysummary\\_by\\_county\(\)](#), [aqsqquarterlysummary\\_by\\_site\(\)](#), [aqssampledataby\\_county\(\)](#), [aqstransactionssample\\_by\\_county\(\)](#)

### Examples

```
# returns an aqs S3 object of daily summary FRM/FEM PM2.5 data
# for Wake County, NC between January and February 2016
## Not run: aqsdailysummary_by_county(parameter = "88101",
                                     bdate = as.Date("20160101",
                                     format = "%Y%m%d"),
                                     edate = as.Date("20170228",
                                     format = "%Y%m%d"),
                                     stateFIPS = "37",
                                     countycode = "183"
                                     )

## End(Not run)
```

---

```
aqsdailysummary_by_site
      aqsdailysummary_by_site
```

---

### Description

**[Stable]** Returns multiple years of data where daily data is aggregated at the site level. Returned is a daily summary matching the input parameter stateFIPS, countycode, and sitenum provided for bdate - edate time frame. Data is aggregated at the state level. Variables returned include mean value, maxima, percentiles, and etc.

### Usage

```
aqsdailysummary_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqsummary_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqsummary_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object that contains daily summary statistics for the given parameter for a single site. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of dailysummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_site functions: [aqsummary\\_annualsummary\\_by\\_site\(\)](#), [aqsummary\\_monitors\\_by\\_site\(\)](#), [aqsummary\\_qa\\_annualperformanceeval\\_by\\_site\(\)](#), [aqsummary\\_qa\\_annualperformanceevaltransaction\\_by\\_county\(\)](#), [aqsummary\\_qa\\_annualperformanceevaltransaction\\_by\\_site\(\)](#), [aqsummary\\_qa\\_blanks\\_by\\_site\(\)](#), [aqsummary\\_qa\\_collocated\\_asse](#)

[aqs\\_qa\\_flowrateaudit\\_by\\_site\(\)](#), [aqs\\_qa\\_flowrateverification\\_by\\_site\(\)](#), [aqs\\_qa\\_one\\_point\\_qc\\_by\\_site\(\)](#), [aqs\\_qa\\_pep\\_audit\\_by\\_site\(\)](#), [aqs\\_sampledata\\_by\\_site\(\)](#), [aqs\\_services\\_by\\_site\(\)](#), [aqs\\_transactionsample](#)

## Examples

```
#Returns a tibble of daily summary ozone
# data for the Millbrook School site (\#0014) in Wake County,
# NC for June 18, 2017.
## Not run:
aqs_dailysummary_by_site(parameter = "44201",
                        bdate = as.Date("20160618",
                                         format = "%Y%m%d"),
                        edate = as.Date("20190618",
                                         format = "%Y%m%d"),
                        stateFIPS = "37",
                        countycode = "183",
                        sitenum = "0014"
                        )

## End(Not run)
```

---

aqs\_dailysummary\_by\_state

*aqs\_dailysummary\_by\_state*

---

## Description

**[Stable]** Returns multiple years of data where daily data is aggregated at the state level. Returned is a daily summary matching the input parameter and stateFIPS provided for bdate - edate time frame. Data is aggregated at the state level. Variables returned include mean value, maxima, percentiles, and etc.

## Usage

```
aqs_dailysummary_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.

stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqsummary_states()</a> for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object that contains daily summary statistics for the given parameter for a single stateFIPS. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of dailysummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_state functions: [aqsummary\\_annualsummary\\_by\\_state\(\)](#), [aqsummary\\_monitors\\_by\\_state\(\)](#), [aqsummary\\_qa\\_blanks\\_by\\_state\(\)](#), [aqsummary\\_qa\\_collocated\\_assessments\\_by\\_state\(\)](#), [aqsummary\\_qa\\_flowrateaudit\\_by\\_state\(\)](#), [aqsummary\\_qa\\_flowrateverification\\_by\\_state\(\)](#), [aqsummary\\_qa\\_one\\_point\\_qc\\_by\\_state\(\)](#), [aqsummary\\_qa\\_pep\\_audit\\_by\\_state\(\)](#), [aqsummary\\_sampledata\\_by\\_state\(\)](#)

### Examples

```
# returns a tibble of all benzene daily
# summaries from North Carolina collected on May 15th, 1995
## Not run: aqsummary_by_state(parameter = "45201",
                             bdate = as.Date("19950515",
                                                format="%Y%m%d"),
                             edate = as.Date("19970515",
                                                format = "%Y%m%d"),
                             stateFIPS = "37"
                             )
```

```
## End(Not run)
```

---

```
aqsfldsbyervice  aqsfldsbyservice
```

---

### Description

**[Stable]** Returns a tibble or an AQS\_Data Mart\_APIv2 S3 object with the list and definitions of fields in the service requested.

### Usage

```
aqsfldsbyervice(service, return_header = FALSE)
```

### Arguments

service	a string which represents the services provided by the AQS API. For a list of available services @seealso <a href="https://aqsepa.gov/aqsweb/documents/data_api.html#services">https://aqsepa.gov/aqsweb/documents/data_api.html#services</a>
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object with containing the list and definitions of fields requested service

### Examples

```
# Returns a tibble containing a list and definitions
# of fields in the Sample Data service
## Not run: aqsfldsbyservice(service = "sampleData")
```

---

```
aqsisavailable  aqsisavailable
```

---

### Description

**[Stable]** returns a tibble or an AQS\_Data Mart\_APIv2 S3 object explaining the status of the AQS API.

### Usage

```
aqsisavailable(return_header = FALSE)
```

**Arguments**

return\_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object which details the status of the AQS API (The status information is located in the header)

**list functions**

NA

**Examples**

```
#check if the AQS API is up, running and accepting requests.
## Not run: aqs_isAvailable()
```

---

aq <sub>s</sub> _knownissues	<i>aq<sub>s</sub>_knownissues</i>
------------------------------	-----------------------------------

---

**Description**

**[Stable]** Returns a table of any known issues with system functionality or the data. These are usually issues that have been identified internally and will require some time to correct in Data Mart or the API. This function implements a direct API call to Data Mart and returns data directly from the API. Issues returned via this function do not include any issues from the RAQSAPI R package.

**Usage**

```
aqs_knownissues(return_header = FALSE)
```

**Arguments**

return\_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object that contains information involving known issues with the Data Mart API.

**Examples**

```
#retrieve the list of known issues directly from the AQS data mart API
## Not run: aqs_knownissues()
```

---

aqsmas	<i>aqsmas</i>
--------	---------------

---

### Description

**[Stable]** Returns a table of monitoring agencies (MA).

### Usage

```
aqsmas(return_header = FALSE)
```

### Arguments

**return\_header** If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object of monitoring agencies and their associated agency code.

### Examples

```
#returns a tibble or an AQS_Data Mart_APIv2 S3 object
#   of monitoring agencies and their respective
#   monitoring agency codes.
## Not run: aqsmas()
```

---

aqsmetadata_service	<i>aqsmetadata_service</i>
---------------------	----------------------------

---

### Description

A helper function for functions which use the metaData service from the AQS API. This function is not intended to be called directly by the end user

### Usage

```
aqsmetadata_service(
  filter,
  service = NA_character_,
  AQS_domain = "aqs.epa.gov"
)
```

### Arguments

**filter** a character string representing the filter being applied

**service** a character string representing the service

**AQS\_domain** a R string object containing the domain that should be used in constructing the API call.

**Value**

a AQS\_DATAMART\_APIv2 S3 object that is the return value from the AQS API. A AQS\_DATAMART\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

---

aqs_monitors_by_box	<i>aqs_monitors_by_box</i>
---------------------	----------------------------

---

**Description**

**[Stable]** Returns a table of monitors and related metadata sites with the provided parameter, aggregated by latitude/longitude bounding box (\_by\_box) for bdate - edate time frame.

**Usage**

```
aqs_monitors_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object which represents the minimum latitude of a geographic box. Decimal latitude with north begin positive. Only data north of this latitude will be returned.
maxlat	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north begin positive. Only data south of this latitude will be returned.
minlon	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.
maxlon	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east begin positive. Only data west of this longitude will be returned. Note that -80 is less than -70.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of monitors from a latitude/longitude bounding box (\_by\_box).

**by\_box aggregate functions**

NA

**See Also**

Other Aggregate \_by\_box functions: [aq<sub>s</sub>\\_annualsummary\\_by\\_box\(\)](#), [aq<sub>s</sub>\\_sampledata\\_by\\_box\(\)](#)

**Examples**

```
# returns a tibble of all ozone
# monitors in the vicinity of central Alabama that operated in
# 1995
## Not run: aqs_monitors_by_box(parameter="44201",
                                bdate=as.Date("19950101",
                                                format="%Y%m%d"),
                                edate=as.Date("19951231",
                                                format="%Y%m%d"),
                                minlat="33.3",
                                maxlat="33.6",
                                minlon="-87.0",
                                maxlon="-86.7"
                                )

## End(Not run)
```

---

aq<sub>s</sub>\_monitors\_by\_cbsa    *aq<sub>s</sub>\_monitors\_by\_cbsa*

---

**Description**

**[Stable]** Returns a table of monitors at all sites with the provided parameter, aggregated by Core Based Statistical Area (CBSA) for bdate - edate time frame.

**Usage**

```
aqs_monitors_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros)
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object that is the return value from the AQS API. A AQS\_Data Mart\_APIv2 object is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

**by\_cbsa (By Core Based Statistical Area, as defined by the US Census Bureau) aggregate functions**

NA

**See Also**

Other Aggregate\_by\_cbsa functions: [aq<sub>s</sub>\\_annualsummary\\_by\\_cbsa\(\)](#), [aq<sub>s</sub>\\_dailysummary\\_by\\_cbsa\(\)](#), [aq<sub>s</sub>\\_sampledata\\_by\\_cbsa\(\)](#)

**Examples**

```
# returns a tibble of NO2 monitors
# for Charlotte-Concord-Gastonia, NC cbsa that were operating
# on January 01, 2017
## Not run: aqs_monitors_by_cbsa(parameter="42602",
                                bdate=as.Date("20170101",
                                                format="%Y%m%d"),
                                edate=as.Date("20170101",
                                                format="%Y%m%d"),
                                cbsa_code="16740"
                                )

## End(Not run)
```

---

aqs\_monitors\_by\_county

*aqs\_monitors\_by\_county*


---

## Description

**[Stable]** Returns a table of monitors and related metadata at sites with the provided parameter, stateFIPS and county\_code for bdate - edate time frame.

## Usage

```
aqs_monitors_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of monitors from a selected county

**by\_county aggregate functions**

NA

**See Also**

Other Aggregate\_by\_county functions: [aq<sub>s</sub>\\_annualsummary\\_by\\_county\(\)](#), [aq<sub>s</sub>\\_dailysummary\\_by\\_county\(\)](#), [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_county\(\)](#), [aq<sub>s</sub>\\_qa\\_blanks\\_by\\_county\(\)](#), [aq<sub>s</sub>\\_qa\\_collocated\\_assessments\\_by\\_county\(\)](#), [aq<sub>s</sub>\\_qa\\_flowrateaudit\\_by\\_county\(\)](#), [aq<sub>s</sub>\\_qa\\_flowrateverification\\_by\\_county\(\)](#), [aq<sub>s</sub>\\_qa\\_one\\_point\\_qc\\_by\\_county\(\)](#), [aq<sub>s</sub>\\_qa\\_pep\\_audit\\_by\\_county\(\)](#), [aq<sub>s</sub>\\_quarterlysummary\\_by\\_county\(\)](#), [aq<sub>s</sub>\\_quarterlysummary\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_sampledata\\_by\\_county\(\)](#), [aq<sub>s</sub>\\_transactionsample\\_by\\_county\(\)](#)

**Examples**

```
# returns an aqs_v2 S3 object containing all S02 monitors in
# Hawaii County, HI that were operating on May 01, 2015.
## Not run: aqs_monitors_by_county(parameter="42401",
                                bdate=as.Date("20150501", format="%Y%m%d"),
                                edate=as.Date("20150502", format="%Y%m%d"),
                                stateFIPS="15",
                                countycode="001"
                                )

## End(Not run)
```

---

aq<sub>s</sub>\_monitors\_by\_site    *aq<sub>s</sub>\_monitors\_by\_site*

---

**Description**

**[Stable]** Returns a table of monitors and related metadata at sites with the provided parameter, stateFIPS, county\_code, and sitenum for bdate - edate time frame.

**Usage**

```
aqs_monitors_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of monitors from a selected stateFIPS, county, and sitenum combination.

**by\_site aggregate functions**

NA

**Note**

all monitors that operated between the bdate and edate will be returned

**See Also**

Other Aggregate\_by\_site functions: [aqs\\_annualsummary\\_by\\_site\(\)](#), [aqs\\_dailysummary\\_by\\_site\(\)](#), [aqs\\_qa\\_annualperformanceeval\\_by\\_site\(\)](#), [aqs\\_qa\\_annualperformanceevaltransaction\\_by\\_county\(\)](#), [aqs\\_qa\\_annualperformanceevaltransaction\\_by\\_site\(\)](#), [aqs\\_qa\\_blanks\\_by\\_site\(\)](#), [aqs\\_qa\\_collocated\\_asse](#), [aqs\\_qa\\_flowrateaudit\\_by\\_site\(\)](#), [aqs\\_qa\\_flowrateverification\\_by\\_site\(\)](#), [aqs\\_qa\\_one\\_point\\_qc\\_by\\_site](#), [aqs\\_qa\\_pep\\_audit\\_by\\_site\(\)](#), [aqs\\_sampledata\\_by\\_site\(\)](#), [aqs\\_services\\_by\\_site\(\)](#), [aqs\\_transactionsample](#)

## Examples

```
#Returns a tibble of the SO2 monitors at Hawaii
# Volcanoes NP site (\#0007) in Hawaii County, HI that were operating on
# May 1 , 2015. (Note, all monitors that operated between the bdate and
# edate will be returned)
## Not run:
  aqs_monitors_by_site(parameter = "42401",
                        bdate = as.Date("20150501",
                                         format="%Y%m%d"),
                        edate = as.Date("20150502",
                                         format="%Y%m%d"),
                        stateFIPS = "15",
                        countycode = "001",
                        sitenum = "0007"
                        )

## End(Not run)
```

---

aqs\_monitors\_by\_state    aqs\_monitors\_by\_state

---

## Description

**[Stable]** Returns a table of monitors and related metadata at sites with the provided parameter, and stateFIPS for bdate - edate time frame.

## Usage

```
aqs_monitors_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aq<sub>s</sub>_states()</a> for the list of available FIPS codes.

cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of monitors from the selected state

**by\_state aggregate functions**

NA

**See Also**

Other Aggregate\_by\_state functions: [aqc\\_annualsummary\\_by\\_state\(\)](#), [aqc\\_dailysummary\\_by\\_state\(\)](#), [aqc\\_qa\\_blanks\\_by\\_state\(\)](#), [aqc\\_qa\\_collocated\\_assessments\\_by\\_state\(\)](#), [aqc\\_qa\\_flowrateaudit\\_by\\_state\(\)](#), [aqc\\_qa\\_flowrateverification\\_by\\_state\(\)](#), [aqc\\_qa\\_one\\_point\\_qc\\_by\\_state\(\)](#), [aqc\\_qa\\_pep\\_audit\\_by\\_state\(\)](#), [aqc\\_sampledata\\_by\\_state\(\)](#)

**Examples**

```
# returns a tibble of SO2 monitors in Hawaii
#   that were operating on May 01, 2015
## Not run: aqc_monitors_by_state(parameter="88101",
                                bdate=as.Date("20170101",
                                                format="%Y%m%d"),
                                edate=as.Date("20171231",
                                                format="%Y%m%d"),
                                stateFIPS="01"
                                )

## End(Not run)
```

---

aqc\_parameters\_by\_class

*aqc\_parameters\_by\_class*

---

**Description**

[Stable] Returns parameters associated with the input class.

**Usage**

```
aqc_parameters_by_class(class, return_header = FALSE)
```

**Arguments**

- class** a R character object that represents the class requested, @seealso [aq<sub>s</sub>\\_classes\(\)](#) for retrieving available classes. The class R character object must be a valid class as returned from [aq<sub>s</sub>\\_classes\(\)](#). The class must be an exact match to what is returned from [aq<sub>s</sub>\\_classes\(\)](#) (case sensitive).
- return\_header** If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing the parameters associated with the class requested. NULL is returned for classes not found.

**Examples**

```
# Returns a tibble of AQS parameters in the criteria class
## Not run: aqs_parameters_by_class(class = "CRITERIA")
```

---

aq<sub>s</sub>\_pqaos

*aq<sub>s</sub>\_pqaos*


---

**Description**

**[Stable]** Returns a table of primary quality assurance organizations (pqaos).

**Usage**

```
aqs_pqaos(return_header = FALSE)
```

**Arguments**

- return\_header** If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of pqaos and their associated pqao code.

**Examples**

```
#To retrieve a tibble of primary quality assurance
# organizations (pqaos)
## Not run: pqaos <- aqs_pqaos()
```

---

```
aqs_qa_annualperformanceeval_by_MA
      aqs_qa_annualperformanceeval_by_MA
```

---

## Description

**[Stable]** Returns quality assurance performance evaluation data - aggregated by Monitoring agency (MA) for a parameter code aggregated by matching input parameter and MA\_code for the time frame between bdate and edate.

## Usage

```
aqs_qa_annualperformanceeval_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

## Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object of quality assurance performance evaluation data. for all monitoring sites for with the MA\_code requested for the time frame between bdate and edate. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

## Note

The AQS API only allows for a single year of quality assurance Annual Performance Evaluation data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate \_by\_MA functions: [aq<sub>s</sub>\\_qa<sub>\\_</sub>annualperformanceevaltransaction\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa<sub>\\_</sub>blanks\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa<sub>\\_</sub>collocated\\_assessments\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa<sub>\\_</sub>flowrateaudit\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa<sub>\\_</sub>flowrateverification\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa<sub>\\_</sub>one\\_point\\_qc\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa<sub>\\_</sub>pep\\_audit\\_by\\_MA\(\)](#)

**Examples**

```
#Returns an AQS_Data Mart_APIv2 S3 object or a tibble
# containing annual performance evaluation data for ozone where
# the monitoring agency is the Alabama Department of
# Environmental Management (MA_code 0013).
## Not run: aqs_qa_annualpeferomanceeval_by_MA(parameter = "44201",
                                                bdate = as.Date("20170101",
                                                                format = "%Y%m%d"),
                                                edate = as.Date("20171231",
                                                                format = "%Y%m%d"),
                                                MA_code = "0013"
                                                )

## End(Not run)
```

---

aq<sub>s</sub>\_qa<sub>\_</sub>annualpeferomanceeval\_by\_pqao

*aq<sub>s</sub>\_qa<sub>\_</sub>annualpeferomanceeval\_by\_pqao*

---

**Description**

**[Stable]** Returns quality assurance performance evaluation data - aggregated by Primary Quality Assurance Organization (PQAO) for a parameter code aggregated by matching input parameter and pqao\_code for the time frame between bdate and edate.

**Usage**

```
aqs_qa_annualpeferomanceeval_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).

**return\_header** If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object of quality assurance performance evaluation data. for single monitoring site for the pqao\_code requested for the time frame between bdate and edate. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of qaAnnualPerformanceEvaluations to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_pqao functions: [aqsqqaannualperformanceevaltransaction\\_by\\_pqao\(\)](#), [aqsqqa\\_blanks\\_by\\_pqao\(\)](#), [aqsqqa\\_collocated\\_assessments\\_by\\_pqao\(\)](#), [aqsqqa\\_flowrateaudit\\_by\\_pqao\(\)](#), [aqsqqa\\_flowrateverification\\_by\\_pqao\(\)](#), [aqsqqa\\_one\\_point\\_qc\\_by\\_pqao\(\)](#), [aqsqqa\\_pep\\_audit\\_by\\_pqao\(\)](#)

### Examples

```
#Returns an AQS_Data Mart_APIv2 S3 object or a tibble
#   containing annual performance evaluation data for ozone where
#   the PQAO is the Alabama Department of Environmental
#   Management (pqao_code 0013).
## Not run: aqsqqaannualpeferomanceeval_by_pqao(parameter = "44201",
#                                               bdate = as.Date("20170101",
#                                                             format = "%Y%m%d"),
#                                               edate = as.Date("20171231",
#                                                             format = "%Y%m%d"),
#                                               pqao_code = "0013"
#                                               )

## End(Not run)
```

---

aqsqqaannualpeferomanceeval\_by\_site

*aqsqqaannualpeferomanceeval\_by\_site*

---

### Description

**[Stable]** Returns quality assurance performance evaluation data - aggregated by site for a parameter code aggregated by matching input parameter, sitenum, countycode and stateFIPS provided for bdate - edate time frame.

**Usage**

```
aqs_qa_annualperformanceeval_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of quality assurance performance evaluation data. for single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of quality assurance Annual Performance Evaluation data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate \_by\_site functions: [aqsqannualsummary\\_by\\_site\(\)](#), [aqsqdailysummary\\_by\\_site\(\)](#), [aqsqmonitors\\_by\\_site\(\)](#), [aqsqqaannualperformanceevaltransaction\\_by\\_county\(\)](#), [aqsqqaannualperformanceeval\\_by\\_county\(\)](#), [aqsqqa\\_blanks\\_by\\_site\(\)](#), [aqsqqa\\_collocated\\_assessments\\_by\\_site\(\)](#), [aqsqqa\\_flowrateaudit\\_by\\_site\(\)](#), [aqsqqa\\_flowrateverification\\_by\\_site\(\)](#), [aqsqqa\\_one\\_point\\_qc\\_by\\_site\(\)](#), [aqsqqa\\_pep\\_audit\\_by\\_site\(\)](#), [aqsqsampledata\\_by\\_site\(\)](#), [aqsqservices\\_by\\_site\(\)](#), [aqsqtransactionsample\\_by\\_site\(\)](#)

**Examples**

```
#Returns an AQS_Data Mart_APIv2 S3 object or a tibble
#   containing annual performance evaluation data for ozone at the
#   Fairhope site in Baldwin County, AL for 2017
## Not run:  aqsqaannualpeferomanceeval_by_site(parameter = "44201",
                                                bdate = as.Date("20170101",
                                                                format = "%Y%m%d"),
                                                edate = as.Date("20171231",
                                                                format = "%Y%m%d"),
                                                stateFIPS = "01",
                                                countycode = "003",
                                                sitenum = "0010"
                                                )

## End(Not run)
```

---

```
aqsqqaannualpeferomanceeval_by_state
      aqsqaannualpeferomanceeval_by_state
```

---

**Description**

**[Stable]** Returns quality assurance performance evaluation data - aggregated by state for a parameter code aggregated by matching input parameter, countycode and stateFIPS provided for bdate - edate time frame.

**Usage**

```
aqsqqaannualpeferomanceeval_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
```



```

stateFIPS = "01"
)

## End(Not run)

```

---

```

aqs_qa_annualperformanceevaltransaction_by_county
aqs_qa_annualperformanceevaltransaction_by_site

```

---

## Description

**[Stable]** Returns AQS submissions transaction format (RD) of the annual performance evaluation data (raw). Includes data pairs for QA - aggregated by site for a parameter code aggregated by matching input parameter, countycode and stateFIPS provided for bdate - edate time frame.

## Usage

```

aqs_qa_annualperformanceevaltransaction_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  return_header = FALSE
)

```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

## Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object of quality assurance performance evaluation data in the RD format for a single monitoring site for the countycode and stateFIPS requested for the time frame between bdate and edate in the AQS. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of quality assurance Annual Performance Evaluations data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_site functions: [aqs\\_annualsummary\\_by\\_site\(\)](#), [aqs\\_dailysummary\\_by\\_site\(\)](#), [aqs\\_monitors\\_by\\_site\(\)](#), [aqs\\_qa\\_annualperformanceeval\\_by\\_site\(\)](#), [aqs\\_qa\\_annualperformanceevaltransaction\\_by\\_site\(\)](#), [aqs\\_qa\\_blanks\\_by\\_site\(\)](#), [aqs\\_qa\\_collocated\\_assessments\\_by\\_site\(\)](#), [aqs\\_qa\\_flowrateaudit\\_by\\_site\(\)](#), [aqs\\_qa\\_flowrateverification\\_by\\_site\(\)](#), [aqs\\_qa\\_one\\_point\\_qc\\_by\\_site\(\)](#), [aqs\\_qa\\_pep\\_audit\\_by\\_site\(\)](#), [aqs\\_sampledata\\_by\\_site\(\)](#), [aqs\\_services\\_by\\_site\(\)](#), [aqs\\_transactionsample\\_by\\_site\(\)](#)

**Examples**

```
#Returns an AQS_Data Mart_APIv2 S3 object or a tibble
#   containing annual performance evaluation data (raw) for ozone
#   in Baldwin County, AL for 2017 in RD format.
## Not run: aqs_qa_annualperformanceevaltransaction_by_county(parameter = "44201",
#                                                             bdate = as.Date("20170101",
#                                                             format = "%Y%m%d"),
#                                                             edate = as.Date("20171231",
#                                                             format = "%Y%m%d"),
#                                                             stateFIPS = "01",
#                                                             countycode = "003"
#                                                             )

## End(Not run)
```

---

aqs\_qa\_annualperformanceevaltransaction\_by\_MA

*aqs\_qa\_annualperformanceevaltransaction\_by\_site*

---

**Description**

**[Stable]** Returns AQS submissions transaction format (RD) of the annual performance evaluation data (raw). Includes data pairs for QA - aggregated by Monitoring agency (MA) for a parameter code aggregated by matching input parameter and MA\_code provided for bdate - edate time frame.

**Usage**

```
aqs_qa_annualperformanceevaltransaction_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of quality assurance performance evaluation data in the AQS submissions transaction format (RD) for all sites matching the MA\_code requested for the time frame between bdate and edate. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of quality assurance Annual Performance Evaluation transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_MA functions: [aqsqqaannualperformanceeval\\_by\\_MA\(\)](#), [aqsqqa\\_blanks\\_by\\_MA\(\)](#), [aqsqqa\\_collocated\\_assessments\\_by\\_MA\(\)](#), [aqsqqa\\_flowrateaudit\\_by\\_MA\(\)](#), [aqsqqa\\_flowrateverification\\_by\\_MA\(\)](#), [aqsqqa\\_one\\_point\\_qc\\_by\\_MA\(\)](#), [aqsqqa\\_pep\\_audit\\_by\\_MA\(\)](#)

**Examples**

```
#Returns an AQS_Data Mart_APIv2 S3 object or a tibble
#   containing annual performance evaluation data for ozone in
#   where the MA is the Alabama Department of Environmental
#   Management (MA_code 0013) for 2017 in RD format.
## Not run: aqsqaannualperformanceevaltransaction_by_MA(parameter = "44201",
#   bdate = as.Date("20170101",
#   format = "%Y%m%d"),
#   edate = as.Date("20171231",
#   format = "%Y%m%d"),
#   MA_code = "0013"
# )

## End(Not run)
```

---

```
aqsqqaannualperformanceevaltransaction_by_pqao
      aqsqqaannualperformanceevaltransaction_by_pqao
```

---

## Description

**[Stable]** Returns AQS submissions transaction format (RD) of the annual performance evaluation data (raw). Includes data pairs for QA - aggregated by Primary Quality Assurance Organization (PQAO) for a parameter code aggregated by matching input parameter and pqao\_code provided for bdate - edate time frame.

## Usage

```
aqsqqaannualperformanceevaltransaction_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

## Value

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object of quality assurance performance evaluation data. for single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

## Note

The AQS API only allows for a single year of qaAnnualPerformanceEvaluations to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length

of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

## See Also

Other Aggregate\_by\_pqao functions: [aqsqqaannualperformanceeval\\_by\\_pqao\(\)](#), [aqsqqa\\_blanks\\_by\\_pqao\(\)](#), [aqsqqa\\_collocated\\_assessments\\_by\\_pqao\(\)](#), [aqsqqa\\_flowrateaudit\\_by\\_pqao\(\)](#), [aqsqqa\\_flowrateverification\\_by\\_pqao\(\)](#), [aqsqqa\\_onepointqc\\_by\\_pqao\(\)](#), [aqsqqa\\_pep\\_audit\\_by\\_pqao\(\)](#)

## Examples

```
#Returns an AQS_Data Mart_APIv2 S3 object or a tibble
#   containing annual performance evaluation data for ozone in
#   where the PQAO is the Alabama Department of Environmental
#   Management (pqao_code 0013) for 2017 in RD format.
## Not run: aqsqaannualperformanceevaltransaction_by_pqao(parameter = "44201",
#                                                         bdate = as.Date("20170101",
#                                                         format = "%Y%m%d"),
#                                                         edate = as.Date("20171231",
#                                                         format = "%Y%m%d"),
#                                                         pqao_code = "0013"
#                                                         )

## End(Not run)
```

---

aqsqqaannualperformanceevaltransaction\_by\_site

*aqsqqaannualperformanceevaltransaction\_by\_site*

---

## Description

**[Stable]** Returns AQS submissions transaction format (RD) of the annual performance evaluation data (raw). Includes data pairs for QA - aggregated by site for a parameter code aggregated by matching input parameter, sitenum, countycode and stateFIPS provided for bdate - edate time frame.

## Usage

```
aqsqqaannualperformanceevaltransaction_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqsqstates()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqsqcounties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of quality assurance annual performance evaluation data in the RD format for a single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate in the AQS. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of quality assurance Annual Performance Evaluations data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_site functions: [aqsqannualsummary\\_by\\_site\(\)](#), [aqsqdailysummary\\_by\\_site\(\)](#), [aqsqmonitors\\_by\\_site\(\)](#), [aqsqqa\\_annualperformanceeval\\_by\\_site\(\)](#), [aqsqqa\\_annualperformanceevaltransaction\\_by\\_site\(\)](#)

```

aqsqqa_blanks_by_site(), aqsqqa_collocated_assessments_by_site(), aqsqqa_flowrateaudit_by_site(),
aqsqqa_flowrateverification_by_site(), aqsqqa_one_point_qc_by_site(), aqsqqa_pep_audit_by_site(),
aqsqqa_sampledata_by_site(), aqsqqa_services_by_site(), aqsqqa_transactionsample_by_site()

```

## Examples

```

#Returns an AQS_Data Mart_APIv2 S3 object or a tibble
#   containing annual performance evaluation data (raw) for ozone
#   at the Fairhope site in Baldwin County, AL for 2017 in RD format.
## Not run: aqsqqaannualperformanceevaltransaction_by_site(parameter = "44201",
#   bdate = as.Date("20170101",
#   format = "%Y%m%d"),
#   edate = as.Date("20171231",
#   format = "%Y%m%d"),
#   stateFIPS = "01",
#   countycode = "003",
#   sitenum = "0010"
#   )

## End(Not run)

```

---

```
aqsqqaannualperformanceevaltransaction_by_state
```

```
aqsqqaannualperformanceevaltransaction_by_state
```

---

## Description

**[Stable]** Returns AQS submissions transaction format (RD) of the annual performance evaluation data (raw). Includes data pairs for QA - aggregated by state for a parameter code aggregated by matching input parameter and stateFIPS provided for bdate - edate time frame.

## Usage

```

aqsqqaannualperformanceevaltransaction_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  return_header = FALSE
)

```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqsqqa_states()</a> for the list of available FIPS codes.

**return\_header** If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object of quality assurance performance evaluation data. for single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of quality assurance Annual Performance Evaluation data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_state functions: [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_state\(\)](#), [aq<sub>s</sub>\\_quarterlysummary\\_by\\_bo](#), [aq<sub>s</sub>\\_quarterlysummary\\_by\\_cbsa\(\)](#), [aq<sub>s</sub>\\_quarterlysummary\\_by\\_state\(\)](#), [aq<sub>s</sub>\\_transactionsample\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_transactionsample\\_by\\_state\(\)](#)

### Examples

```
#Returns an AQS_Data Mart_APIv2 S3 object or a tibble
#   containing annual performance evaluation data for ozone in
#   Alabmba for 2017 in RD format.
## Not run:
aqs_qa_annualperformanceevaltransaction_by_state(parameter = "44201",
                                                bdate = as.Date("20170101",
                                                                format = "%Y%m%d"),
                                                edate = as.Date("20171231",
                                                                format = "%Y%m%d"),
                                                stateFIPS = "01"
                                                )

## End(Not run)
```

---

aq<sub>s</sub>\_qa\_annualperformanceeval\_by\_county

*aq<sub>s</sub>\_qa\_annualpeferomanceeval\_by\_county*

---

### Description

**[Stable]** Returns AQS submissions transaction format (RD) of the annual performance evaluation data (raw). Includes data pairs for QA - aggregated by county for a parameter code aggregated by matching input parameter, countycode and stateFIPS provided for bdate - edate time frame.

**Usage**

```
aqs_qa_annualperformanceeval_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of quality assurance performance evaluation data. for single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of quality assurance Annual Performance Evaluation data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_county functions: [aqs\\_annualsummary\\_by\\_county\(\)](#), [aqs\\_dailysummary\\_by\\_county\(\)](#), [aqs\\_monitors\\_by\\_county\(\)](#), [aqs\\_qa\\_blanks\\_by\\_county\(\)](#), [aqs\\_qa\\_collocated\\_assessments\\_by\\_county\(\)](#),

```
aqs_qa_flowrateaudit_by_county(), aqs_qa_flowrateverification_by_county(), aqs_qa_one_point_qc_by_
aqs_qa_pep_audit_by_county(), aqs_quarterlysummary_by_county(), aqs_quarterlysummary_by_site(),
aqs_sampledata_by_county(), aqs_transactionsample_by_county()
```

## Examples

```
#Returns an AQS_Data Mart_APIv2 S3 object or a tibble
#   containing annual performance evaluation data (raw) for ozone
#   in Baldwin County, AL for 2017 in RD format.
## Not run: aqs_qa_annualperformanceeval_by_county(parameter = "44201",
                                                    bdate = as.Date("20170101",
                                                                    format = "%Y%m%d"),
                                                    edate = as.Date("20171231",
                                                                    format = "%Y%m%d"),
                                                    stateFIPS = "01",
                                                    countycode = "003"
                                                    )

## End(Not run)
```

---

```
aqs_qa_blanks_by_county
```

```
    aqs_qa_blanks_by_county
```

---

## Description

**[Stable]** Returns a table of blank quality assurance data. Blanks are unexposed sample collection devices (e.g., filters) that are transported with the exposed sample devices to assess if contamination is occurring during the transport or handling of the samples. Data is aggregated at the county level.

## Usage

```
aqs_qa_blanks_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.



```

stateFIPS = "01",
countycode = "033"
)

## End(Not run)

```

---

```

aqs_qa_blanks_by_MA    aqs_qa_blanks_by_MA

```

---

## Description

**[Stable]** Returns a table of blank quality assurance data. Blanks are unexposed sample collection devices (e.g., filters) that are transported with the exposed sample devices to assess if contamination is occurring during the transport or handling of the samples. Data is aggregated by monitoring agency code (MA\_code).

## Usage

```

aqs_qa_blanks_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object that contains quality assurance blank sample data for all monitors within the input MA\_code. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**by\_ma aggregate functions**

NA

**Note**

The AQS API only allows for a single year of qa\_blank data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_MA functions: [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_collocated\\_assessments\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_flowrateaudit\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_flowrateverification\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_one\\_point\\_qc\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_pep\\_audit\\_by\\_MA\(\)](#)

**Examples**

```
# returns a tibble containing PM2.5 blank data for
# January 2018 where the Monitoring Agency is the Alabama
# Department of Environmental Management (agency 0013)
## Not run: aqs_qa_blanks_by_MA(parameter = "88101",
                                bdate = as.Date("20170101",
                                                  format = "%Y%m%d"),
                                edate = as.Date("20190131",
                                                  format = "%Y%m%d"),
                                MA_code = "0013"
                                )

## End(Not run)
```

---

aq<sub>s</sub>\_qa\_blanks\_by\_pqao    aq<sub>s</sub>\_qa\_blanks\_by\_pqao

---

**Description**

**[Stable]** Returns a table of blank quality assurance data. Blanks are unexposed sample collection devices (e.g., filters) that are transported with the exposed sample devices to assess if contamination is occurring during the transport or handling of the samples. Data is aggregated by Primary Quality Assurance Organization (PQAO).

**Usage**

```
aqs_qa_blanks_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing quality assurance blank data for monitors within a pqao. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**by\_pqao aggregate functions**

NA

**Note**

The AQS API only allows for a single year of qa\_blank data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will

take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

## See Also

Other Aggregate\_by\_pqao functions: [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_pqao\(\)](#), [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_pqao\(\)](#), [aq<sub>s</sub>\\_qa\\_collocated\\_assessments\\_by\\_pqao\(\)](#), [aq<sub>s</sub>\\_qa\\_flowrateaudit\\_by\\_pqao\(\)](#), [aq<sub>s</sub>\\_qa\\_flowrateverification\\_by\\_pqao\(\)](#), [aq<sub>s</sub>\\_qa\\_one\\_point\\_qc\\_by\\_pqao\(\)](#), [aq<sub>s</sub>\\_qa\\_pep\\_audit\\_by\\_pqao\(\)](#)

## Examples

```
# returns tibble of PM2.5 blank data for
# January 2018 where the PQA0 is the Alabama Department of
# Environmental Management (agency 0013)
## Not run: aqs_qa_blanks_by_pqao(parameter = "88101",
#                               bdate = as.Date("20180101",
#                                                format = "%Y%m%d"),
#                               edate = as.Date("20180131",
#                                                format = "%Y%m%d"),
#                               pqao_code = "0013"
#                               )

## End(Not run)
```

---

aq<sub>s</sub>\_qa\_blanks\_by\_site    *aq<sub>s</sub>\_qa\_blanks\_by\_site*

---

## Description

**[Stable]** Returns a table of blank quality assurance data. Blanks are unexposed sample collection devices (e.g., filters) that are transported with the exposed sample devices to assess if contamination is occurring during the transport or handling of the samples. Data is aggregated at the site level.

## Usage

```
aqs_qa_blanks_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object that contains quality assurance blank sample data for single monitoring site for the sitenum, countycode and stateFIPS requested for the time frame between bdate and edate. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of qa\_blank data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_site functions: [aqs\\_annualsummary\\_by\\_site\(\)](#), [aqs\\_dailysummary\\_by\\_site\(\)](#), [aqs\\_monitors\\_by\\_site\(\)](#), [aqs\\_qa\\_annualperformanceeval\\_by\\_site\(\)](#), [aqs\\_qa\\_annualperformanceevaltransa](#)

[aqs\\_qa\\_annualperformanceevaltransaction\\_by\\_site\(\)](#),
 [aqs\\_qa\\_collocated\\_assessments\\_by\\_site\(\)](#),
 [aqs\\_qa\\_flowrateaudit\\_by\\_site\(\)](#),
 [aqs\\_qa\\_flowrateverification\\_by\\_site\(\)](#),
 [aqs\\_qa\\_one\\_point\\_qc\\_by\\_site\(\)](#),
 [aqs\\_qa\\_pep\\_audit\\_by\\_site\(\)](#),
 [aqs\\_sampledata\\_by\\_site\(\)](#),
 [aqs\\_services\\_by\\_site\(\)](#),
 [aqs\\_transactionsample](#)

## Examples

```

#Returns a tibble of PM2.5 blank
# data for the Muscle Shoals site (#0014) in Colbert County, AL
# for January 2018
## Not run:
    aqs_qa_blanks_by_site(parameter = "88101",
                          bdate = as.Date("20170101",
                                          format="%Y%m%d"),
                          edate = as.Date("20190131",
                                          format="%Y%m%d"),
                          stateFIPS = "01",
                          countycode = "033",
                          sitenum = "1002"
                          )

## End(Not run)

```

---

aqs\_qa\_blanks\_by\_state

*aqs\_qa\_blanks\_by\_state*

---

## Description

**[Stable]** Returns a table of blank quality assurance data . Blanks are unexposed sample collection devices (e.g., filters) that are transported with the exposed sample devices to assess if contamination is occurring during the transport or handling of the samples. Data is aggregated at the state level.

## Usage

```

aqs_qa_blanks_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.

stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqsa_states()</a> for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object that contains quality assurance blank sample data for all monitors within the input stateFIPS. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of qa\_blank data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_state functions: [aqsa\\_annualsummary\\_by\\_state\(\)](#), [aqsa\\_dailysummary\\_by\\_state\(\)](#), [aqsa\\_monitors\\_by\\_state\(\)](#), [aqsa\\_qa\\_collocated\\_assessments\\_by\\_state\(\)](#), [aqsa\\_qa\\_flowrateaudit\\_by\\_state\(\)](#), [aqsa\\_qa\\_flowrateverification\\_by\\_state\(\)](#), [aqsa\\_qa\\_one\\_point\\_qc\\_by\\_state\(\)](#), [aqsa\\_qa\\_pep\\_audit\\_by\\_state\(\)](#), [aqsa\\_sampledata\\_by\\_state\(\)](#)

### Examples

```
# returns a aqs_v2 object which contains PM2.5 blank data
# for Alabama for January 2018
## Not run: aqsa_qa_blanks_by_state(parameter = "88101",
                                   bdate = as.Date("20180101",
                                                    format = "%Y%m%d"),
                                   ),
                                   edate = as.Date("20180131",
                                                    format = "%Y%m%d"),
                                   stateFIPS = "01"
                                   )

## End(Not run)
```

---

```
aqs_qa_collocated_assessments_by_county
      aqs_qa_collocated_assessments_by_county
```

---

## Description

**[Stable]** Returns a table of collocated assessment data aggregated by matching input parameter, stateFIPS and county\_code provided for bdate - edate time frame.

## Usage

```
aqs_qa_collocated_assessments_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing quality assurance collocated assessment data for monitors within a county. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of collocated assessments to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_county functions: [aqsqannualsummarybycounty\(\)](#), [aqsqdailysummarybycounty\(\)](#), [aqsqmonitorsbycounty\(\)](#), [aqsqqaannualperformanceevalbycounty\(\)](#), [aqsqqablanksbycounty\(\)](#), [aqsqqaflowrateauditbycounty\(\)](#), [aqsqqaflowrateverificationbycounty\(\)](#), [aqsqqaonepointqcbycounty\(\)](#), [aqsqqaqepauditbycounty\(\)](#), [aqsqquarterlysummarybycounty\(\)](#), [aqsqquarterlysummarybycountybycountycode\(\)](#), [aqsqsampledatabycounty\(\)](#), [aqsqtransactionssamplebycounty\(\)](#)

**Examples**

```
# returns a tibble with collocated assessment data
# for FRM PM2.5 in Madison County, AL for January 2013
## Not run: aqsqaacollocatedassessmentsbycounty(parameter = "88101",
#                                     bdate = as.Date("20130101",
#                                     format = "%Y%m%d"),
#                                     edate = as.Date("20150131",
#                                     format = "%Y%m%d"),
#                                     stateFIPS = "01",
#                                     countycode = "089")
## End(Not run)
```

---

aqsqacollocatedassessmentsbyMA

*aqsqacollocatedassessmentsbyMA*

---

**Description**

**[Stable]** Returns a table of collocated assessment data aggregated by matching input parameter, and monitoring agency (MA) code provided for bdate - edate time frame.

**Usage**

```
aqsa_qa_collocated_assessments_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing quality assurance collocated assessment data for monitors within a monitoring agency. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of collocated assessments to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_MA functions: [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_blanks\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_flowrateaudit\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_flowrateverification\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_one\\_point\\_qc\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_pep\\_audit\\_by\\_MA\(\)](#)

**Examples**

```
# returns a tibble containing collocated assessment
#   data for FRM PM2.5 January 2013 where the Monitoring Agency is
#   the Alabama Department of Environmental Management (agency 0013)
## Not run: aqs_qa_collocated_assessments_by_MA(parameter="88101",
#                                               bdate = as.Date("20130101",
#                                               format = "%Y%m%d"),
#                                               edate = as.Date("20150131",
#                                               format="%Y%m%d"),
#                                               MA_code = "0013"
#                                               )

## End(Not run)
```

---

```
aqs_qa_collocated_assessments_by_pqao
      aqs_qa_collocated_assessments_by_pqao
```

---

**Description**

**[Stable]** Returns a table of collocated assessment data aggregated by matching input parameter, and Primary Quality Assurance Organisation (PQAO) code provided for bdate - edate time frame.

**Usage**

```
aqs_qa_collocated_assessments_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).



---

```
aqs_qa_collocated_assessments_by_site
      aqs_qa_collocated_assessments_by_site
```

---

### Description

**[Stable]** Returns a table of collocated assessment data aggregated by matching input parameter, stateFIPS, county\_code, and sitenum provided for bdate - edate time frame.

### Usage

```
aqs_qa_collocated_assessments_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

### Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing quality assurance collocated assessment data for monitors within a site. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of collocated assessments to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_site functions: [aqsq\\_annualsummary\\_by\\_site\(\)](#), [aqsq\\_dailysummary\\_by\\_site\(\)](#), [aqsq\\_monitors\\_by\\_site\(\)](#), [aqsq\\_qa\\_annualperformanceeval\\_by\\_site\(\)](#), [aqsq\\_qa\\_annualperformanceevaltransaction\\_by\\_site\(\)](#), [aqsq\\_qa\\_blanks\\_by\\_site\(\)](#), [aqsq\\_qa\\_flowrateaudit\\_by\\_site\(\)](#), [aqsq\\_qa\\_flowrateverification\\_by\\_site\(\)](#), [aqsq\\_qa\\_one\\_point\\_qc\\_by\\_site\(\)](#), [aqsq\\_qa\\_pep\\_audit\\_by\\_site\(\)](#), [aqsq\\_sampledata\\_by\\_site\(\)](#), [aqsq\\_services\\_by\\_site\(\)](#), [aqsq\\_transactionsample\\_by\\_site\(\)](#)

**Examples**

```
#returns a tibble of collocated assessment data
# for FRM PM2.5 at the Huntsville Old Airport site (\#0014)
# in Madison County, AL for January 2013:
## Not run: aqsqa_collocated_assessments_by_site(parameter = "88101",
                                                bdate = as.Date("20130101",
                                                                format = "%Y%m%d"),
                                                edate = as.Date("20150131",
                                                                format = "%Y%m%d"),
                                                stateFIPS = "01",
                                                countycode = "089",
                                                sitenum = "0014")

## End(Not run)
```

---

aqsq\_collocated\_assessments\_by\_state

*aqsq\_collocated\_assessments\_by\_state*

---

**Description**

**[Stable]** Returns a table of collocated assessment data aggregated by matching input parameter and stateFIPS provided for bdate - edate time frame.

**Usage**

```
aqs_qa_collocated_assessments_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing quality assurance collocated assessment data for monitors within a state. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of collocated assessments to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

## See Also

Other Aggregate\_by\_state functions: [aqs\\_annualsummary\\_by\\_state\(\)](#), [aqs\\_dailysummary\\_by\\_state\(\)](#), [aqs\\_monitors\\_by\\_state\(\)](#), [aqs\\_qa\\_blanks\\_by\\_state\(\)](#), [aqs\\_qa\\_flowrateaudit\\_by\\_state\(\)](#), [aqs\\_qa\\_flowrateverification\\_by\\_state\(\)](#), [aqs\\_qa\\_one\\_point\\_qc\\_by\\_state\(\)](#), [aqs\\_qa\\_pep\\_audit\\_by\\_state\(\)](#), [aqs\\_sampledata\\_by\\_state\(\)](#)

## Examples

```
# returns a tibble of collocated
# assessment data fofr FRM2.5 for January 2013
## Not run: aqs_qa_collocated_assessments_by_state(parameter="88101",
                                                    bdate = as.Date("20130101",
                                                    format = "%Y%m%d"
                                                    ),
                                                    edate = as.Date("20150131",
                                                    format = "%Y%m%d"
                                                    ),
                                                    stateFIPS = "01"
                                                    )

## End(Not run)
```

---

```
aqs_qa_flowrateaudit_by_county
```

```
    aqs_qa_flowrateaudit_by_county
```

---

## Description

**[Stable]** Returns a table containing flow rate audit data aggregated by parameter code, stateFIPS and countycode for bdate - edate time frame.

## Usage

```
aqs_qa_flowrateaudit_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.



```

tateFIPS = "01",
countycode = "073"
)

## End(Not run)

```

---

```

aqs_qa_flowrateaudit_by_MA
  aqs_qa_flowrateaudit_by_MA

```

---

## Description

**[Stable]** Returns a table containing flow rate audit data aggregated by parameter code and monitoring agency code (`_by_MA`) for `bdate` - `edate` time frame.

## Usage

```

aqs_qa_flowrateaudit_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

## Arguments

<code>parameter</code>	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
<code>bdate</code>	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
<code>edate</code>	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
<code>MA_code</code>	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
<code>cbdate</code>	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. <code>cbdate</code> is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to <code>NA_Date_</code> .
<code>cedate</code>	a R date object which represents an "end date of last change" that indicates when the data was last updated. <code>cedate</code> is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to <code>NA_Date_</code> .
<code>return_header</code>	If <code>FALSE</code> (default) only returns data requested. If <code>TRUE</code> returns a <code>AQSAPI_v2</code> object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object containing flow rate audit data for the requested MA\_code. An AQS\_Data\_Mart\_APIv2 object is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of flow rate audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_MA functions: [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_blanks\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_collocated\\_assessments\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_flowrateverification\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_one\\_point\\_qc\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_pep\\_audit\\_by\\_MA\(\)](#)

**Examples**

```
# returns a tibble of flow rate audit data
# for FRM PM2.5 January 2016 - January 2018 where the Monitoring Agency is
# the Jefferson County, AL Department of Health (agency 0550)
## Not run: aqs_qa_flowrateaudit_by_MA(parameter = "88101",
                                     bdate = as.Date("20160101",
                                     format = "%Y%m%d"),
                                     edate = as.Date("20180131",
                                     format = "%Y%m%d"),
                                     MA_code = "0550"
                                     )

## End(Not run)
```

---

aq<sub>s</sub>\_qa\_flowrateaudit\_by\_pqao

*aq<sub>s</sub>\_qa\_flowrateaudit\_by\_pqao*

---

**Description**

**[Stable]** Returns a table containing flow rate audit data aggregated by parameter code and Primary Quality Assurance Organization (PQAO) code for bdate - edate time frame.

**Usage**

```
aqs_qa_flowrateaudit_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object containing flow rate audit data for the requested pqao\_code. An AQS\_Data\_Mart\_APIv2 object is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of flow rate audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

## See Also

Other Aggregate\_by\_pqao functions: [aqs\\_qa\\_annualperformanceeval\\_by\\_pqao\(\)](#), [aqs\\_qa\\_annualperformanceeval\\_by\\_pqao\(\)](#), [aqs\\_qa\\_blanks\\_by\\_pqao\(\)](#), [aqs\\_qa\\_collocated\\_assessments\\_by\\_pqao\(\)](#), [aqs\\_qa\\_flowrateverification\\_by\\_pqao\(\)](#), [aqs\\_qa\\_one\\_point\\_qc\\_by\\_pqao\(\)](#), [aqs\\_qa\\_pep\\_audit\\_by\\_pqao\(\)](#)

## Examples

```
# returns a tibble of flow rate audit data for January
# 2018 where the PQAO is the Jefferson County, AL Department Of
# Health (agency 0550).
## Not run: aqs_qa_flowrateaudit_by_pqao(parameter = "88101",
                                         bdate = as.Date("20170101",
                                                         format = "%Y%m%d"),
                                         edate = as.Date("20180131",
                                                         format = "%Y%m%d"),
                                         pqao_code = "0550"
                                         )

## End(Not run)
```

---

aqs\_qa\_flowrateaudit\_by\_site

*aqs\_qa\_flowrate audit\_by\_site*

---

## Description

**[Stable]** Returns a table containing flow rate audit data aggregated by parameter code, stateFIPS, countycode and site number for bdate - edate time frame.

## Usage

```
aqs_qa_flowrateaudit_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.

stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqsa_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqsa_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing flow rate audit data for the requested sitenum, countycode and stateFIPS. An AQS\_Data\_Mart\_APIv2 object is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of flow rate audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_site functions: [aqsa\\_annualsummary\\_by\\_site\(\)](#), [aqsa\\_dailysummary\\_by\\_site\(\)](#), [aqsa\\_monitors\\_by\\_site\(\)](#), [aqsa\\_qa\\_annualperformanceeval\\_by\\_site\(\)](#), [aqsa\\_qa\\_annualperformanceevaltransaction\\_by\\_site\(\)](#), [aqsa\\_qa\\_blanks\\_by\\_site\(\)](#), [aqsa\\_qa\\_collocated\\_asset\\_by\\_site\(\)](#), [aqsa\\_qa\\_flowrateverification\\_by\\_site\(\)](#), [aqsa\\_qa\\_one\\_point\\_qc\\_by\\_site\(\)](#), [aqsa\\_qa\\_pep\\_audit\\_by\\_site\(\)](#), [aqsa\\_sampledata\\_by\\_site\(\)](#), [aqsa\\_services\\_by\\_site\(\)](#), [aqsa\\_transactionsample\\_by\\_site\(\)](#)

### Examples

```
# returns a tibble of flow rate audit data
# for the Wylam site (#2003) in Jefferson County, AL
# for January 2018:
## Not run: aqsa_qa_flowrateaudit_by_site(parameter = "88101",
```

```

        bdate = as.Date("20150101",
                        format="%Y%m%d"),
        edate = as.Date("20180131",
                        format="%Y%m%d"),
        stateFIPS = "01",
        countycode = "073",
        sitenum = "2003"
    )

## End(Not run)

```

---

```

aqs_qa_flowrateaudit_by_state
      aqs_qa_flowrateaudit_by_state

```

---

## Description

**[Stable]** Returns a table containing flow rate audit data aggregated by parameter code and stateFIPS for bdate - edate time frame.

## Usage

```

aqs_qa_flowrateaudit_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

**return\_header** If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object containing flow rate audit data for the requested stateFIPS. An AQS\_Data\_Mart\_APIv2 object is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of flow rate audit data to be retrieved at a time. This function conveniently extracts date information from the `bdate` and `edate` parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_state functions: [aqsq\\_annualsummary\\_by\\_state\(\)](#), [aqsq\\_dailysummary\\_by\\_state\(\)](#), [aqsq\\_monitors\\_by\\_state\(\)](#), [aqsq\\_qa\\_blanks\\_by\\_state\(\)](#), [aqsq\\_qa\\_collocated\\_assessments\\_by\\_state\(\)](#), [aqsq\\_qa\\_flowrateverification\\_by\\_state\(\)](#), [aqsq\\_qa\\_one\\_point\\_qc\\_by\\_state\(\)](#), [aqsq\\_qa\\_pep\\_audit\\_by\\_state\(\)](#), [aqsq\\_sampledata\\_by\\_state\(\)](#)

### Examples

```
# returns a tibble of flow rate audit
# data for Alabama in January 2018
## Not run: aqsqa_flowrateaudit_by_state(parameter = "88101",
                                         b date = as.Date("20170101",
                                         format = "%Y%m%d"
                                         ),
                                         edate = as.Date("20180131",
                                         format = "%Y%m%d"
                                         ),
                                         stateFIPS = "01"
                                         )

## End(Not run)
```

---

`aqsq_flowrateverification_by_county`

*aqsq\_flowrateverification\_by\_county*

---

### Description

**[Stable]** Returns a table containing flow rate Verification data for a parameter code aggregated matching input parameter, stateFIPS, and county\_code, provided for `bdate` - `edate` time frame.

**Usage**

```
aqs_qa_flowrateverification_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing quality assurance flow rate verification data for monitors within a county. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of flow rate verifications to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each

calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_county functions: [aqs\\_annualsummary\\_by\\_county\(\)](#), [aqs\\_dailysummary\\_by\\_county\(\)](#), [aqs\\_monitors\\_by\\_county\(\)](#), [aqs\\_qa\\_annualperformanceeval\\_by\\_county\(\)](#), [aqs\\_qa\\_blanks\\_by\\_county\(\)](#), [aqs\\_qa\\_collocated\\_assessments\\_by\\_county\(\)](#), [aqs\\_qa\\_flowrateaudit\\_by\\_county\(\)](#), [aqs\\_qa\\_one\\_point\\_qc\\_b](#), [aqs\\_qa\\_pep\\_audit\\_by\\_county\(\)](#), [aqs\\_quarterlysummary\\_by\\_county\(\)](#), [aqs\\_quarterlysummary\\_by\\_site\(\)](#), [aqs\\_sampledata\\_by\\_county\(\)](#), [aqs\\_transactionsample\\_by\\_county\(\)](#)

### Examples

```
# returns a tibble of flow rate verification data for
#   Colbert County, AL for January 2018
## Not run: aqs_qa_flowrateverification_by_county(parameter = "88101",
                                                    bdate = as.Date("20180101",
                                                    format = "%Y%m%d"
                                                    ),
                                                    edate = as.Date("20190131",
                                                    format = "%Y%m%d"
                                                    ),
                                                    stateFIPS = "01",
                                                    countycode = "033"
                                                    )

## End(Not run)
```

---

aqs\_qa\_flowrateverification\_by\_MA

*aqs\_qa\_flowrateverification\_by\_MA*

---

### Description

**[Stable]** Returns a table containing flow rate Verification data for a parameter code aggregated by matching input parameter, and monitoring agency (MA) code provided for bdate - edate time frame.

### Usage

```
aqs_qa_flowrateverification_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing quality assurance flow rate verification data for monitors within a Monitoring agency. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of flow rate verifications to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_MA functions: [aq\\_s\\_qa\\_annualperformanceeval\\_by\\_MA\(\)](#), [aq\\_s\\_qa\\_annualperformanceeval\\_by\\_MA\(\)](#), [aq\\_s\\_qa\\_blanks\\_by\\_MA\(\)](#), [aq\\_s\\_qa\\_collocated\\_assessments\\_by\\_MA\(\)](#), [aq\\_s\\_qa\\_flowrateaudit\\_by\\_MA\(\)](#), [aq\\_s\\_qa\\_one\\_point\\_qc\\_by\\_MA\(\)](#), [aq\\_s\\_qa\\_pep\\_audit\\_by\\_MA\(\)](#)

**Examples**

```
# returns a tibble containing collocated assessment
# data for FRM PM2.5 January 2013 where the Monitoring Agency is
# the Alabama Department of Environmental Management (agency 0013)
## Not run: aq_s_qa_flowrateverification_by_MA(parameter = "88101",
```

```

        bdate = as.Date("20130101",
                        format = "%Y%m%d"
                        ),
        edate = as.Date("20150131",
                        format = "%Y%m%d"
                        ),
        MA_code = "0013"
    )

## End(Not run)

```

---

```
aqsa_qa_flowrateverification_by_pqao
```

```
aqsa_qa_flowrateverification_by_pqao
```

---

## Description

**[Stable]** Returns a table containing flow rate Verification data for a parameter code aggregated by matching input parameter, and Primary Quality Assurance Organization (PQAO) code provided for bdate - edate time.

## Usage

```

aqsa_qa_flowrateverification_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

**return\_header** If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing quality assurance flow rate verification data for monitors within a pqao. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of flow rate verifications to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_pqao functions: [aq\\_s\\_qa\\_annualperformanceeval\\_by\\_pqao\(\)](#), [aq\\_s\\_qa\\_annualperformanceeval\\_by\\_pqao\(\)](#), [aq\\_s\\_qa\\_blanks\\_by\\_pqao\(\)](#), [aq\\_s\\_qa\\_collocated\\_assessments\\_by\\_pqao\(\)](#), [aq\\_s\\_qa\\_flowrateaudit\\_by\\_pqao\(\)](#), [aq\\_s\\_qa\\_one\\_point\\_qc\\_by\\_pqao\(\)](#), [aq\\_s\\_qa\\_pep\\_audit\\_by\\_pqao\(\)](#)

### Examples

```
# returns a tibble of flow rate verification
# data for January 2018 where the PQAO is the Alabama Department
# of Environmental Management (agency 0013)
## Not run: aq_s_qa_flowrateverification_by_pqao(parameter = "88101",
                                                bdate = as.Date("20170101",
                                                                format = "%Y%m%d"),
                                                edate = as.Date("20190131",
                                                                format = "%Y%m%d"),
                                                pqao_code = "0013")

## End(Not run)
```

---

aq\_s\_qa\_flowrateverification\_by\_site

*aq\_s\_qa\_flowrateverification\_by\_site*

---

### Description

**[Stable]** Returns a table containing flow rate Verification data for a parameter code aggregated matching input parameter, stateFIPS, county\_code, and sitenum provided for bdate - edate time frame.

**Usage**

```
aqs_qa_flowrateverification_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing quality assurance flow rate verification data for monitors at a site. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of flow rate verifications to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_site functions: [aq<sub>s</sub>\\_annualsummary\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_dailysummary\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_monitors\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_qa\\_annualperformanceevaltransaction\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_qa\\_blanks\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_qa\\_collocated\\_asset\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_qa\\_flowrateaudit\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_qa\\_one\\_point\\_qc\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_qa\\_pep\\_audit\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_sampledata\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_services\\_by\\_site\(\)](#), [aq<sub>s</sub>\\_transactionsample\\_by\\_site\(\)](#)

**Examples**

```
# returns a tibble of flow rate verification
# data for the Muscle Shoals site (#0014) in Colbert County, AL
# for January 2018:
## Not run: aqs_qa_flowrateverification_by_site(parameter = "88101",
#                                             bdate = as.Date("20170101",
#                                                         format = "%Y%m%d"),
#                                             edate = as.Date("20180131",
#                                                         format = "%Y%m%d"),
#                                             stateFIPS = "01",
#                                             countycode = "033",
#                                             sitenum = "1002"
#                                             )

## End(Not run)
```

---

aq<sub>s</sub>\_qa\_flowrateverification\_by\_state

*aq<sub>s</sub>\_qa\_flowrateverification\_by\_state*

---

**Description**

**[Stable]** Returns a table containing flow rate Verification data for a parameter code aggregated matching input parameter, and stateFIPS, provided for bdate - edate time frame.

**Usage**

```
aqs_qa_flowrateverification_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
```

```

cedate = NA_Date_,
return_header = FALSE
)

```

### Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqsqstates()</a> for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing quality assurance flow rate verification data for monitors within a state. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of flow rate verifications to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_state functions: [aqsqannualsummary\\_by\\_state\(\)](#), [aqsqdailysummary\\_by\\_state\(\)](#), [aqsqmonitors\\_by\\_state\(\)](#), [aqsqqa\\_blanks\\_by\\_state\(\)](#), [aqsqqa\\_collocated\\_assessments\\_by\\_state\(\)](#), [aqsqqa\\_flowrateaudit\\_by\\_state\(\)](#), [aqsqqa\\_one\\_point\\_qc\\_by\\_state\(\)](#), [aqsqqa\\_pep\\_audit\\_by\\_state\(\)](#), [aqsqsampledata\\_by\\_state\(\)](#)

## Examples

```
# returns a tibble of flow rate verification
# data for Alabama 2018
## Not run: aqs_qa_flowrateverification_by_state(parameter = "88101",
                                                bdate = as.Date("20170101",
                                                                format = "%Y%m%d"),
                                                edate = as.Date("20190131",
                                                                format = "%Y%m%d"),
                                                stateFIPS = "01"
                                                )

## End(Not run)
```

---

```
aqs_qa_one_point_qc_by_county
      aqs_qa_one_point_qc_by_county_
```

---

## Description

**[Stable]** Returns a tibble or an AQS\_Data Mart\_APIv2 S3 object containing one point QC check data aggregated by county\_code.

## Usage

```
aqs_qa_one_point_qc_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.



---

```
aqs_qa_one_point_qc_by_MA
      aqs_qa_one_point_qc_by_MA
```

---

### Description

**[Stable]** Returns a tibble or an AQS\_Data Mart\_APIv2 S3 object containing one point QC check data aggregated by monitoring agency code (\_by\_MA).

### Usage

```
aqs_qa_one_point_qc_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

### Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing one point qc data for a single monitoring agency. A AQS\_Data\_Mart\_APIv2 object is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of one point qc data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_MA functions: [aqsa\\_qa\\_annualperformanceeval\\_by\\_MA\(\)](#), [aqsa\\_qa\\_annualperformanceeval\\_by\\_MA\(\)](#), [aqsa\\_qa\\_blanks\\_by\\_MA\(\)](#), [aqsa\\_qa\\_collocated\\_assessments\\_by\\_MA\(\)](#), [aqsa\\_qa\\_flowrateaudit\\_by\\_MA\(\)](#), [aqsa\\_qa\\_flowrateverification\\_by\\_MA\(\)](#), [aqsa\\_qa\\_pep\\_audit\\_by\\_MA\(\)](#)

**Examples**

```
# returns a tibble of ozone One Point QC data
# for January 2018 where the Monitoring Agency is the
# Massachusetts Department of Environmental Protection
# (agency 0660)
## Not run: aqsa_qa_one_point_qc_by_MA(parameter = "44201",
#                                     bdate = as.Date("20170101",
#                                     format = "%Y%m%d"),
#                                     edate = as.Date("20180131",
#                                     format = "%Y%m%d"),
#                                     MA_code = "0660"
#                                     )

## End(Not run)
```

---

```
aqsa_qa_one_point_qc_by_pqao
aqsa_qa_one_point_qc_by_pqao
```

---

**Description**

**[Stable]** Returns a tibble or an AQS\_Data Mart\_APIv2 S3 object containing Quality assurance data - collocated assessment raw data aggregated by Primary Quality Assurance Organization (PQAO) code.

**Usage**

```
aqsa_qa_one_point_qc_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```



```

                                format = "%Y%m%d"),
    edate = as.Date("20180131",
                    format = "%Y%m%d"),
    pqao_code = "0660"
)

## End(Not run)

```

---

```

aqs_qa_one_point_qc_by_site
      aqs_qa_one_point_qc_by_site

```

---

## Description

**[Stable]** Returns a table of one point QC raw data aggregated by parameter code, stateFIPS, countycode and site number.

## Usage

```

aqs_qa_one_point_qc_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.



---

```
aqs_qa_one_point_qc_by_state
      aqs_qa_one_point_qc_by_state
```

---

## Description

**[Stable]** Returns a tibble or an AQS\_Data Mart\_APIv2 S3 object containing Quality assurance data - flow rate audit raw data aggregated by state FIPS.

## Usage

```
aqs_qa_one_point_qc_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

## Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing one point qc data within a state. A AQS\_Data\_Mart\_APIv2 object is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of one point qc data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_state functions: [aq\\_s\\_annualsummary\\_by\\_state\(\)](#), [aq\\_s\\_dailysummary\\_by\\_state\(\)](#), [aq\\_s\\_monitors\\_by\\_state\(\)](#), [aq\\_s\\_qa\\_blanks\\_by\\_state\(\)](#), [aq\\_s\\_qa\\_collocated\\_assessments\\_by\\_state\(\)](#), [aq\\_s\\_qa\\_flowrateaudit\\_by\\_state\(\)](#), [aq\\_s\\_qa\\_flowrateverification\\_by\\_state\(\)](#), [aq\\_s\\_qa\\_pep\\_audit\\_by\\_state\(\)](#), [aq\\_s\\_sampledata\\_by\\_state\(\)](#)

**Examples**

```
# returns a tibble of one point QC check
# data for ozone in Massachusetts in January 2018
## Not run: aq_s_qa_one_point_qc_by_state(parameter = "44201",
                                         bdate = as.Date("20170101",
                                                           format = "%Y%m%d"),
                                         edate = as.Date("20190131",
                                                           format = "%Y%m%d"),
                                         stateFIPS = "25"
                                         )

## End(Not run)
```

---

```
aq_s_qa_pep_audit_by_county
```

```
aq_s_qa_pep_audit_by_county
```

---

**Description**

**[Stable]** Returns a table of Performance Evaluation Program (PEP) audit data aggregated by parameter code, stateFIPS and countycode for the time frame between bdate and edate.

**Usage**

```
aq_s_qa_pep_audit_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
```

```

    return_header = FALSE
  )

```

### Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqsa_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqsa_counties_by_state()</a> for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object containing quality assurance PEP audit data within a county. A AQS\_Data\_Mart\_APIv2 object is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of one point pest audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_county functions: [aqsa\\_annualsummary\\_by\\_county\(\)](#), [aqsa\\_dailysummary\\_by\\_county\(\)](#), [aqsa\\_monitors\\_by\\_county\(\)](#), [aqsa\\_qa\\_annualperformanceeval\\_by\\_county\(\)](#), [aqsa\\_qa\\_blanks\\_by\\_county\(\)](#),

```

aq_s_qa_collocated_assessments_by_county(), aq_s_qa_flowrateaudit_by_county(), aq_s_qa_flowrateverifi
aq_s_qa_one_point_qc_by_county(), aq_s_quarterlysummary_by_county(), aq_s_quarterlysummary_by_site(),
aq_s_sampledata_by_county(), aq_s_transactionsample_by_county()

```

## Examples

```

# returns a tibble with PEP Audit data for FRM
#   PM2.5 in Madison County, AL for 2017
## Not run: aq_s_qa_pep_audit_by_county_multiyear(parameter = "88101",
                                                    bdate = as.Date("20150101",
                                                    format = "%Y%m%d"
                                                    ),
                                                    edate = as.Date("20171231",
                                                    format = "%Y%m%d"
                                                    ),
                                                    stateFIPS = "01",
                                                    countycode = "089"
                                                    )

## End(Not run)

```

---

```
aq_s_qa_pep_audit_by_MA
```

```
aq_s_qa_pep_audit_by_MA
```

---

## Description

**[Stable]** Returns a table of Performance Evaluation Program (PEP) audit data aggregated by monitoring agency code (`_by_MA`) for the time frame between `bdate` and `edate`.

## Usage

```

aq_s_qa_pep_audit_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

## Arguments

<code>parameter</code>	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
<code>bdate</code>	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
<code>edate</code>	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
<code>MA_code</code>	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).

cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object containing quality assurance PEP audit data for a monitoring agency. A AQS\_Data\_Mart\_APIv2 object is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of one point pep audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_MA functions: [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_blanks\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_collocated\\_assessments\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_flowrateaudit\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_flowrateverification\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_qa\\_one\\_point\\_qc\\_by\\_MA\(\)](#)

### Examples

```
# returns a tibble of PEP audit data for
# June 2017 where the Monitoring Agency is the Alabama Department
# of Environmental Management (agency 0013)
## Not run: aqs_qa_pep_audit_by_MA(parameter = "88101",
                                bdate = as.Date("20170601",
                                                  format = "%Y%m%d"),
                                edate = as.Date("20170630",
                                                  format = "%Y%m%d"),
                                MA_code = "0013"
                                )

## End(Not run)
```

---

```
aqs_qa_pep_audit_by_pqao
      aqs_qa_pep_audit_by_pqao
```

---

## Description

**[Stable]** Returns a table of Performance Evaluation Program (PEP) audit data aggregated by Primary Quality Assurance Organization (PQAO) code for the time frame between bdate and edate.

## Usage

```
aqs_qa_pep_audit_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

## Value

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object containing quality assurance PEP audit data for a Primary Quality Assurance Organization. A AQS\_Data\_Mart\_APIv2 object is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of one point pep audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate \_by\_pqao functions: [aqs\\_qa\\_annualperformanceeval\\_by\\_pqao\(\)](#), [aqs\\_qa\\_annualperformanceeval\\_by\\_pqao\(\)](#), [aqs\\_qa\\_blanks\\_by\\_pqao\(\)](#), [aqs\\_qa\\_collocated\\_assessments\\_by\\_pqao\(\)](#), [aqs\\_qa\\_flowrateaudit\\_by\\_pqao\(\)](#), [aqs\\_qa\\_flowrateverification\\_by\\_pqao\(\)](#), [aqs\\_qa\\_one\\_point\\_qc\\_by\\_pqao\(\)](#)

**Examples**

```
# returns a tibble of PEP audit data for
# June 2017 where the pqao is the Alabama Department of
# Environmental Management (agency 0013)
## Not run: aqs_qa_pep_audit_by_pqao(parameter = "88101",
                                   bdate = as.Date("20170601",
                                                  format = "%Y%m%d"),
                                   ),
                                   edate = as.Date("20190630",
                                                  format = "%Y%m%d"),
                                   pqao_code = "0013"
                                   )

## End(Not run)
```

---

```
aqs_qa_pep_audit_by_site
      aqs_qa_pep_audit_by_site
```

---

**Description**

**[Stable]** Returns a table of Performance Evaluation Program (PEP) audit data aggregated by parameter code, stateFIPS, countycode and site number for the time frame between bdate and edate.

**Usage**

```
aqs_qa_pep_audit_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
```

```

    return_header = FALSE
  )

```

### Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object containing quality assurance PEP audit data within a site. A AQS\_Data\_Mart\_APIv2 object is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of one point pep audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_site functions: [aqsa\\_annualsummary\\_by\\_site\(\)](#), [aqsa\\_dailysummary\\_by\\_site\(\)](#), [aqsa\\_monitors\\_by\\_site\(\)](#), [aqsa\\_qa\\_annualperformanceeval\\_by\\_site\(\)](#), [aqsa\\_qa\\_annualperformanceevaltransaction\\_by\\_site\(\)](#), [aqsa\\_qa\\_blanks\\_by\\_site\(\)](#), [aqsa\\_qa\\_collocated\\_asse](#), [aqsa\\_qa\\_flowrateaudit\\_by\\_site\(\)](#), [aqsa\\_qa\\_flowrateverification\\_by\\_site\(\)](#), [aqsa\\_qa\\_one\\_point\\_qc\\_by\\_site](#), [aqsa\\_sampledata\\_by\\_site\(\)](#), [aqsa\\_services\\_by\\_site\(\)](#), [aqsa\\_transactionsample\\_by\\_site\(\)](#)

**Examples**

```
# returns a aqsa_v2 S3 object of pep Audit data for FRM PM2.5
#   at the Huntsville Old Airport site (\#0014) in Madison County,
#   AL for 2017 - 2019.
## Not run: aqsa_qa_pep_audit_by_site(parameter = "88101",
#                                     bdate = as.Date("20170101",
#                                                       format = "%Y%m%d"),
#                                     edate = as.Date("20191231",
#                                                       format = "%Y%m%d"),
#                                     stateFIPS = "01",
#                                     countycode = "089",
#                                     sitenum = "0014"
#                                     )

## End(Not run)
```

---

aqsa\_qa\_pep\_audit\_by\_state

*aqsa\_qa\_pep\_audit\_by\_state*

---

**Description**

**[Stable]** Returns a table of Performance Evaluation Program (PEP) audit data aggregated by parameter code, and stateFIPS for the time frame between bdate and edate.

**Usage**

```
aqsa_qa_pep_audit_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.

edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqstates()</a> for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object containing quality assurance PEP audit data within a state. A AQS\_Data\_Mart\_APIv2 object is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

### Note

The AQS API only allows for a single year of one point pep audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate\_by\_state functions: [aqsanualsummary\\_by\\_state\(\)](#), [aqsdailysummary\\_by\\_state\(\)](#), [aqsmotors\\_by\\_state\(\)](#), [aqsqablanks\\_by\\_state\(\)](#), [aqsqacollocated\\_assessments\\_by\\_state\(\)](#), [aqsqaflowrateaudit\\_by\\_state\(\)](#), [aqsqaflowrateverification\\_by\\_state\(\)](#), [aqsqaone\\_point\\_qc\\_by\\_state\(\)](#), [aqsqasampled\\_data\\_by\\_state\(\)](#)

### Examples

```
# returns a tibble of PEP audit data for PM2.5 in Alabama 2017
## Not run: aqsqaapep_audit_by_state_multiyear(parameter="88101",
                                              bdate=as.Date("20160101",
                                                            format="%Y%m%d"),
                                              edate=as.Date("20171231",
                                                            format="%Y%m%d"),
                                              stateFIPS="01"
                                              )
```

```
## End(Not run)
```

---

```
aqs_quarterlysummary_by_box
      aqs_quarterlysummary_by_box
```

---

## Description

**[Stable]** Returns a tibble or an AQS\_Data Mart\_APIv2 S3 object of quarterly summary data aggregated by and area within a latitude/longitude bounding box.

## Usage

```
aqs_quarterlysummary_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object which represents the minimum latitude of a geographic box. Decimal latitude with north begin positive. Only data north of this latitude will be returned.
maxlat	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north begin positive. Only data south of this latitude will be returned.
minlon	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.
maxlon	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east begin positive. Only data west of this longitude will be returned. Note that -80 is less than -70.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.



---

```
aqqs_quarterlysummary_by_cbsa
  aqs_quarterlysummary_by_cbsa
```

---

## Description

**[Stable]** Returns a tibble or an AQS\_Data Mart\_APIv2 S3 object of quarterly summary data aggregated by stateFIPS.

## Usage

```
aqqs_quarterlysummary_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros)
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

## Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object that contains quarterly summary statistics for the given parameter for a stateFIPS. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of quarterly summary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_state functions: [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_state\(\)](#), [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_state\(\)](#), [aq<sub>s</sub>\\_quarterlysummary\\_by\\_box\(\)](#), [aq<sub>s</sub>\\_quarterlysummary\\_by\\_state\(\)](#), [aq<sub>s</sub>\\_transactionssample\\_by\\_MA\(\)](#), [aq<sub>s</sub>\\_transactionssample\\_by\\_state\(\)](#)

**Examples**

```
# returns a tibble of quarterly summary N02
# data the for Charlotte-Concord-Gastonia, NC cbsa for
# January 01, 2017
## Not run: aqs_quarterlysummary_by_cbsa(parameter = "42602",
#                                     bdate = as.Date("20170101",
#                                     format = "%Y%m%d"),
#                                     edate = as.Date("20190101",
#                                     format = "%Y%m%d"),
#                                     cbsa_code = "16740"
#                                     )

## End(Not run)
```

---

```
aqs_quarterlysummary_by_county
      aqs_quarterlysummary_by_county
```

---

**Description**

**[Stable]** Returns a tibble or an AQS\_Data Mart\_APIv2 S3 object of quarterly summary data aggregated by cbsa (Core Based Statistical Area) code.

**Usage**

```
aqs_quarterlysummary_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqsq_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqsq_counties_by_state()</a> for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object that contains quarterly summary statistics for the given parameter for a single countycode and stateFIPS combination. An AQS\_Data Mart\_APIv2 is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of quarterly summary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_county functions: [aqsq\\_annualsummary\\_by\\_county\(\)](#), [aqsq\\_dailysummary\\_by\\_county\(\)](#), [aqsq\\_monitors\\_by\\_county\(\)](#), [aqsq\\_qa\\_annualperformanceeval\\_by\\_county\(\)](#), [aqsq\\_qa\\_blanks\\_by\\_county\(\)](#), [aqsq\\_qa\\_collocated\\_assessments\\_by\\_county\(\)](#), [aqsq\\_qa\\_flowrateaudit\\_by\\_county\(\)](#), [aqsq\\_qa\\_flowrateverification\\_by\\_county\(\)](#), [aqsq\\_qa\\_one\\_point\\_qc\\_by\\_county\(\)](#), [aqsq\\_qa\\_pep\\_audit\\_by\\_county\(\)](#), [aqsq\\_quarterlysummary\\_by\\_site\(\)](#), [aqsq\\_sampledata\\_by\\_county\(\)](#), [aqsq\\_transactionsample\\_by\\_county\(\)](#)

## Examples

```
# returns a tibble containing quarterly summaries for
#   FRM/FEM PM2.5 data for Wake County, NC between January
#   and February 2016
## Not run: aqs_quarterlysummary_by_county(parameter = "88101",
#                                           bdate = as.Date("20160101",
#                                                         format = "%Y%m%d"),
#                                           edate = as.Date("20170228",
#                                                         format = "%Y%m%d"),
#                                           stateFIPS = "37",
#                                           countycode = "183"
#                                           )

## End(Not run)
```

---

```
aqs_quarterlysummary_by_site
```

```
  aqs_quarterlysummary_by_site
```

---

## Description

**[Stable]** Returns a tibble or an AQS\_Data Mart\_APIv2 S3 object of quarterly summary data aggregated by site with the provided parameternum, stateFIPS, county\_code, and sitenum for bdate - edate time frame.

## Usage

```
aqs_quarterlysummary_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aq<sub>s</sub>_states()</a> for the list of available FIPS codes.



```

stateFIPS = "37",
countycode = "183",
sitenum = "0014"
)

## End(Not run)

```

---

aqs\_quarterlysummary\_by\_state

*aqs\_quarterlysummary\_by\_state*


---

## Description

**[Stable]** Returns a tibble or an AQS\_Data Mart\_APIv2 S3 object of quarterly summary data aggregated by stateFIPS.

## Usage

```

aqs_quarterlysummary_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object that contains quarterly summary statistics for the given parameter for a stateFIPS. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

**Note**

The AQS API only allows for a single year of quarterly summary to be retrieved at a time. This function conveniently extracts date information from the `bdate` and `edate` parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_state functions: [aq\\_qa\\_annualperformanceeval\\_by\\_state\(\)](#), [aq\\_qa\\_annualperformanceeval\\_by\\_state\(\)](#), [aq\\_quarterlysummary\\_by\\_box\(\)](#), [aq\\_quarterlysummary\\_by\\_cbsa\(\)](#), [aq\\_transactionsample\\_by\\_MA\(\)](#), [aq\\_transactionsample\\_by\\_state\(\)](#)

**Examples**

```
# returns an aqs S3 object containing quarterly summaries for
#   FRM/FEM PM2.5 data for North Carolina between January
#   and February 2016
## Not run: aqs_quarterlysummary_by_state(parameter = "88101",
#                                         bdate = as.Date("20160101",
#                                                         format = "%Y%m%d"),
#                                         edate = as.Date("20170228",
#                                                         format = "%Y%m%d"),
#                                         stateFIPS = "37"
#                                         )

## End(Not run)
```

aq\_removeheader

*aq\_removeheader***Description**

**[Stable]** Coerces a single AQS\_Data\_Mart\_APIv2 S3 object or a list of AQS\_Data\_Mart\_APIv2 S3 objects into a single tibble object. This function decouples the `$Data` from the AQSAPI\_v2 object and returns only the `$Data` portion as a tibble. If the input is a list of AQSAPI\_v2 objects combines the `$Data` portion of each AQS\_Data\_Mart\_APIv2 S3 object into a single tibble with `$Header` information discarded. Else returns the input with no changes.

**Usage**

```
aq_removeheader(AQSobject)
```

**Arguments**

AQSubject      An object of AQSAPI\_v2 or a list of AQSAPI\_v2 objects.

**Value**

a tibble of the combined \$data portions of the input AQS\_Data\_Mart\_APIv2 S3 object with the \$Header portion discarded.

**Note**

Since this function returns only the \$Data portion of RAQSAPI\_v2 objects this means that the \$Header information will not be present in the object being returned.

**Examples**

```
## Not run: AQSubject <- aqs_removeheader(AQSubject)
```

---

aq <sub>s</sub> _revisionhistory	<i>aq<sub>s</sub>_revisionhistory</i>
----------------------------------	---------------------------------------

---

**Description**

**[Stable]** Returns the change history to the AQS Data Mart API.

**Usage**

```
aqs_revisionhistory(return_header = FALSE)
```

**Arguments**

return\_header    If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object that is the return value from the AQS API. A AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

**Examples**

```
# read the Data Mart API revision history
# \dontrun{aqs_revisionHistory()}
```

---

aqs\_sampledata\_by\_box aqs\_sampledata\_by\_box

---

## Description

**[Stable]** Returns sample data where the data is aggregated by latitude/longitude bounding box (`_by_box`). If `return_header` is `FALSE` (default) this function returns a single dataframe with the requested data. If `return_header` is `TRUE` returns a list of `AQSAPI_v2` objects where each index of the list is an individual `RAQSAPI_v2` object returned from each successive call to the AQS API. `RAQSAPI_v2` objects are two item list where the `$Data` portion contains data that contains sample air monitoring data at a site with the input parameter and `cbsa_code` provided for `bdate` - `edate` time frame. The `$Header` is a tibble of header information from the API call `/(useful for debugging/)`. This function returns `NULL` is `bdate > edate`.

## Usage

```
aqs_sampledata_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  duration = NA_character_,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

<code>parameter</code>	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
<code>bdate</code>	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
<code>edate</code>	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
<code>minlat</code>	a R character object which represents the minimum latitude of a geographic box. Decimal latitude with north begin positive. Only data north of this latitude will be returned.
<code>maxlat</code>	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north begin positive. Only data south of this latitude will be returned.
<code>minlon</code>	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.
<code>maxlon</code>	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east begin positive. Only data west of this longitude will be returned. Note that -80 is less than -70.

duration	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of NA_character_ results in no filtering based on duration code. Valid durations include actual sample durations and not calculated durations such as 8 hour CO or SO <sub>3</sub> rolling averages, 3/6 day PM averages or Pb 3 month rolling averages. @seealso <a href="#">aq_sampl durations()</a> for a list of all available duration codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object containing sample data for all monitors within the input latitude/longitude bounding box for a single parameter. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item */((\$Header)/)* is a tibble of header information from the AQS API and the second item */((\$Data)/)* is a tibble of the data returned.

### Note

The AQS API only allows for a single year of sampled data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. Fortunately this operation has a linear run time */(Big O notation: O/(n + 5 seconds)/)*.

### See Also

Other Aggregate\_by\_box functions: [aq\\_sannualsummary\\_by\\_box\(\)](#), [aq\\_monitors\\_by\\_box\(\)](#)

### Examples

```
# returns a aqs_v2 S3 object containing all ozone samples
# in the vicinity of central Alabama for
# May 1, 2015 - May 2, 2017
## Not run: aq_sampladata_by_box(parameter = "44201",
                                bdate = as.Date("20150501",
                                                  format = "%Y%m%d"),
                                edate = as.Date("20170502",
                                                  format = "%Y%m%d"),
                                minlat = "33.3",
                                maxlat = "33.6",
                                minlon = "-87.0",
```

```

maxlon = "-86.7"
)

## End(Not run)

```

---

aqs\_sampledata\_by\_cbsa

*aqs\_sampledata\_by\_cbsa*


---

## Description

**[Stable]** Returns sample data where the data is aggregated at the Core Based Statistical Area (cbsa) level. If return\_header is FALSE (default) this function returns a single dataframe with the requested data. If return\_header is TRUE returns a list of AQSAPI\_v2 objects where each index of the list is an individual RAQSAPI\_v2 object returned from each successive call to the AQS API. RAQSAPI\_v2 objects are two item list where the \$Data portion contains data that contains sample air monitoring data at a site with the input parameter and cbsa\_code provided for bdate - edate time frame. The \$Header is a tibble of header information from the API call /(useful for debugging/). This function returns NULL is bdate > edate.

## Usage

```

aqs_sampledata_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  duration = NA_character_,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros)
duration	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of NA_character_ results in no filtering based on duration code. Valid durations include actual sample durations and not calculated durations such as 8 hour CO or \$O_3\$ rolling averages, 3/6 day PM averages or Pb 3 month rolling averages. @seealso <a href="#">aqs_sampledurations()</a> for a list of all available duration codes.

<code>cbdate</code>	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. <code>cbdate</code> is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to <code>NA_Date_</code> .
<code>cedate</code>	a R date object which represents an "end date of last change" that indicates when the data was last updated. <code>cedate</code> is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to <code>NA_Date_</code> .
<code>return_header</code>	If <code>FALSE</code> (default) only returns data requested. If <code>TRUE</code> returns a <code>AQSAPI_v2</code> object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an `AQS_Data_Mart_APIv2` S3 object containing sample data for all monitors matching `cbsa_code` for the given parameter. An `AQS_Data_Mart_APIv2` is a 2 item named list in which the first item `/(($Header/)` is a tibble of header information from the AQS API and the second item `/(($Data/)` is a tibble of the data returned.

### Note

The AQS API only allows for a single year of `sampladata` to be retrieved at a time. This function conveniently extracts date information from the `bdate` and `edate` parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. Fortunately this operation has a linear run time `/(Big O notation: O/(n + 5 seconds)/)`

### See Also

Other Aggregate `_by_cbsa` functions: `aq_annualsummary_by_cbsa()`, `aq_dailysummary_by_cbsa()`, `aq_monitors_by_cbsa()`

### Examples

```
# returns an aqs_v2 s3 object which contains NO2 data
# for Charlotte-Concord-Gastonia, NC cbsa for
# January 1, 2015 - January 01, 2017
## Not run: aq_sampladata_by_cbsa(parameter = "42602",
                                bdate = as.Date("20150101",
                                                  format = "%Y%m%d"),
                                edate = as.Date("20170101",
                                                  format = "%Y%m%d"),
                                cbsa_code = "16740"
                                )

## End(Not run)
```

---

```
aq_sampladata_by_county
      aq_sampladata_by_county
```

---

## Description

**[Stable]** Returns a single tibble with the requested data. If return\_header is TRUE returns a list of AQSAPI\_v2 objects where each index of the list is an individual RAQSAPI\_v2 object returned from each successive call to the AQS API. RAQSAPI\_v2 objects are two item list where the \$Data portion contains data that contains sample air monitoring data at a site with the input parameter, stateFIPS and county\_code provided for bdate - edate time frame. The \$Header is a tibble of header information from the API call /(useful for debugging/). This function returns NULL is bdate > edate.

## Usage

```
aq_sampladata_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  duration = NA_character_,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aq_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aq_counties_by_state()</a> for the list of available county codes for each state.
duration	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of NA_character_ results in no filtering based on duration code. Valid durations include actual sample durations and not calculated durations such as 8 hour CO or \$O_3\$ rolling averages, 3/6 day PM averages or Pb 3 month rolling averages. @seealso <a href="#">aq_sampl durations()</a> for a list of all available duration codes.

cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data\_Mart\_APIv2 S3 object containing sample data for all monitors matching stateFIPS and county\_code for the given parameter. An AQS\_Data\_Mart\_APIv2 is a 2 item named list in which the first item `/(($Header)/)` is a tibble of header information from the AQS API and the second item `/(($Data)/)` is a tibble of the data returned.

### Note

The AQS API only allows for a single year of sampledata to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. Fortunately this operation has a linear run time `/(Big O notation:  $O(n + 5 \text{ seconds})$ /)`.

### See Also

Other Aggregate\_by\_county functions: [aq\\_sannualsummary\\_by\\_county\(\)](#), [aq\\_sdailysummary\\_by\\_county\(\)](#), [aq\\_smonitors\\_by\\_county\(\)](#), [aq\\_sqa\\_annualperformanceeval\\_by\\_county\(\)](#), [aq\\_sqa\\_blanks\\_by\\_county\(\)](#), [aq\\_sqa\\_collocated\\_assessments\\_by\\_county\(\)](#), [aq\\_sqa\\_flowrateaudit\\_by\\_county\(\)](#), [aq\\_sqa\\_flowrateverify\\_by\\_county\(\)](#), [aq\\_sqa\\_one\\_point\\_qc\\_by\\_county\(\)](#), [aq\\_sqa\\_pep\\_audit\\_by\\_county\(\)](#), [aq\\_squarterlysummary\\_by\\_county\(\)](#), [aq\\_squarterlysummary\\_by\\_site\(\)](#), [aq\\_stransactionsample\\_by\\_county\(\)](#)

### Examples

```
# returns all FRM/FEM PM2.5 data for Wake County, NC between
#   January 1, 2015 - February 28, 2016
## Not run: aq_ssampledata_by_county(parameter = "88101",
                                   bdate = as.Date("20150101",
                                                    format = "%Y%m%d"),
                                   edate=as.Date("20160228",
                                                  format = "%Y%m%d"),
                                   stateFIPS = "37",
                                   countycode = "183"
                                   )

## End(Not run)
```

---

aqs\_sampledata\_by\_site

*aqs\_sampledata\_by\_site*


---

## Description

**[Stable]** Returns multiple years of data where sample data is aggregated at the site level. If `return_header` is `FALSE` (default) returns a single data frame with the requested data. If `return_header` is `TRUE` returns a list of `AQSAPI_v2` objects where each index of the list is an individual `RAQS-API_v2` object returned from each successive calls to the AQS API. `RAQSAPI_v2` objects are two item list where the `$Data` portion contains data that contains sample air monitoring data at a site with the input parameter, `stateFIPS` and `county_code` provided for `bdate` - `edate` time frame. The `$Header` is a tibble of header information from the API call */(useful for debugging/)*. Returns `NULL` is `bdate > edate`.

## Usage

```
aqs_sampledata_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  duration = NA_character_,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
duration	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of <code>NA_character_</code>



```

                                edate = as.Date("20190618",
                                                format = "%Y%m%d"),
                                stateFIPS = "37",
                                countycode = "183",
                                sitenum = "0014"
                                )

## End(Not run)

```

---

```
aq_sampladata_by_state
```

```
aq_sampladata_by_state
```

---

## Description

**[Stable]** Returns sample data where the data is aggregated at the state level. If `return_header` is `FALSE` (default) this function returns a single dataframe with the requested data. If `return_header` is `TRUE` returns a list of `AQSAPI_v2` objects where each index of the list is an individual `RAQS-API_v2` object returned from each successive call to the AQS API. `RAQS-API_v2` objects are two item list where the `$Data` portion contains data that contains sample air monitoring data at a site with the input parameter and stateFIPS provided for `bdate` - `edate` time frame. The `$Header` is a tibble of header information from the API call (useful for debugging). This function returns `NULL` is `bdate > edate`.

## Usage

```

aq_sampladata_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  duration = NA_character_,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aq_states()</a> for the list of available FIPS codes.



```

                                stateFIPS = "37"
                                )

## End(Not run)

```

---

aq<sub>s</sub>\_sampledurations      *aq<sub>s</sub>\_sampledurations*

---

### Description

**[Stable]** Returns a table of sample durations and their associated duration codes. Returned values are not calculated durations such as 8 hour CO or O<sub>3</sub> rolling averages, 3/6 day PM averages or Pb 3 month rolling averages.

### Usage

```
aqs_sampledurations(return_header = FALSE)
```

### Arguments

**return\_header**      If FALSE (default) only returns data requested. If TRUE returns a AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object of sample durations and their associated duration codes (groups of parameters, i.e. "criteria" or "all").

### Examples

```

#returns a tibble or an AQS_Data Mart_APIv2 S3 object of
#
## Not run:  aqs_sampledurations()

```

---

aq<sub>s</sub>\_services\_by\_box      *aq<sub>s</sub>\_services\_by\_box*

---

### Description

a helper function that abstracts the formatting of the inputs for a call to aq<sub>s</sub> away from the calling function for aggregations by a box formed by minimum/maximum latitude/longitude coordinates then calls the aq<sub>s</sub> and returns the result. This helper function is not meant to be called directly from external functions.

**Usage**

```

aqserv_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  duration = NA_character_,
  service,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  AQS_domain = "aqserv.epa.gov"
)

```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object which represents the minimum latitude of a geographic box. Decimal latitude with north begin positive. Only data north of this latitude will be returned.
maxlat	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north begin positive. Only data south of this latitude will be returned.
minlon	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.
maxlon	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east begin positive. Only data west of this longitude will be returned. Note that -80 is less than -70.
duration	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of NA_character_ results in no filtering based on duration code. Valid durations include actual sample durations and not calculated durations such as 8 hour CO or SO <sub>2</sub> rolling averages, 3/6 day PM averages or Pb 3 month rolling averages. @seealso <a href="#">aqserv_durations()</a> for a list of all available duration codes.
service	a string which represents the services provided by the AQS API. For a list of available services @seealso <a href="https://aqserv.epa.gov/aqservweb/documents/data_api.html#services">https://aqserv.epa.gov/aqservweb/documents/data_api.html#services</a>
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.

cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
AQS_domain	a R string object containing the domain that should be used in constructing the API call.

### Value

a AQS\_DATAMART\_APIv2 S3 object that is the return value from the AQS API. A AQS\_DATAMART\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

---

aqserv\_by\_cbsa    *aqserv\_by\_cbsa*

---

### Description

a helper function that abstracts the formatting of the inputs for a call to aqs away from the calling function for aggregations by cbsa then calls the aqs and returns the result. This helper function is not meant to be called directly from external functions.

### Usage

```
aqserv_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  duration = NA_character_,
  service,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  AQS_domain = "aqs.epa.gov"
)
```

### Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros)
duration	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of NA_character_ results in no filtering based on duration code. Valid durations include actual sample durations and not calculated durations such as 8 hour CO or \$O_3\$ rolling

	averages, 3/6 day PM averages or Pb 3 month rolling averages. @seealso <a href="#">aqservicedurations()</a> for a list of all available duration codes.
service	a string which represents the services provided by the AQS API For a list of available services @seealso <a href="https://aqservices.epa.gov/aqservices/documents/data_api.html#services">https://aqservices.epa.gov/aqservices/documents/data_api.html#services</a>
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
AQS_domain	a R string object containing the domain that should be used in constructing the API call.

### Value

a AQS\_DATAMART\_APIv2 S3 object that is the return value from the AQS API. A AQS\_DATAMART\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

---

```
aqservices_by_county
      aqservices_by_county
```

---

### Description

a helper function that abstracts the formatting of the inputs for a call to aqs away from the calling function for aggregations by county then calls the aqs and returns the result. This helper function is not meant to be called directly from external functions.

### Usage

```
aqservices_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  service,
  duration = NA_character_,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  AQS_domain = "aqservices.epa.gov"
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqstates()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqcounties_by_state()</a> for the list of available county codes for each state.
service	a string which represents the services provided by the AQS API For a list of available services @seealso <a href="https://aq.epa.gov/aqweb/documents/data_api.html#services">https://aq.epa.gov/aqweb/documents/data_api.html#services</a>
duration	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of NA_character_ results in no filtering based on duration code. Valid durations include actual sample durations and not calculated durations such as 8 hour CO or \$O_3\$ rolling averages, 3/6 day PM averages or Pb 3 month rolling averages. @seealso <a href="#">aqsampledurations()</a> for a list of all available duration codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
AQS_domain	a R string object containing the domain that should be used in constructing the API call.

**Value**

a AQS\_DATAMART\_APIv2 S3 object that is the return value from the AQS API. A AQS\_DATAMART\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

---

aqservices_by_MA	<i>aqservices_by_MA</i>
------------------	-------------------------

---

**Description**

a helper function that abstracts the formatting of the inputs for a call to aqs away from the calling function for aggregations by Monitoring Agency (MA) then calls the aqs and returns the result. This helper function is not meant to be called directly from external functions.

**Usage**

```
aqs_services_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  service,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  AQS_domain = "aqs.epa.gov"
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
service	a string which represents the services provided by the AQS API For a list of available services @seealso <a href="https://aqs.epa.gov/aqsweb/documents/data_api.html#services">https://aqs.epa.gov/aqsweb/documents/data_api.html#services</a>
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
AQS_domain	a R string object containing the domain that should be used in constructing the API call.

**Value**

a AQS\_DATAMART\_APIv2 S3 object that is the return value from the AQS API. A AQS\_DATAMART\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

---

```
aqs_services_by_pqao    aqs_services_by_pqao
```

---

**Description**

a helper function that abstracts the formatting of the inputs for a call to aqs away from the calling function for aggregations by Primary Quality Assurance Organization (pqao) then calls the aqs and returns the result. This helper function is not meant to be called directly from external functions.

**Usage**

```
aqservices_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  service,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  AQS_domain = "aqs.epa.gov"
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).
service	a string which represents the services provided by the AQS API. For a list of available services @seealso <a href="https://aqs.epa.gov/aqsweb/documents/data_api.html#services">https://aqs.epa.gov/aqsweb/documents/data_api.html#services</a>
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
AQS_domain	a R string object containing the domain that should be used in constructing the API call.

**Value**

a AQS\_DATAMART\_APIv2 S3 object that is the return value from the AQS API. A AQS\_DATAMART\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

---

aqservices\_by\_site    *aqservices\_by\_site*

---

**Description**

a helper function that abstracts the formatting of the inputs for a call to aqs away from the calling function for aggregations by site then calls the aqs and returns the result. This helper function is not meant to be called directly from external functions.

**Usage**

```

aqs_services_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  duration = NA_character_,
  service,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  AQS_domain = "aqs.epa.gov"
)

```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aqs_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
duration	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of NA_character_ results in no filtering based on duration code. Valid durations include actual sample durations and not calculated durations such as 8 hour CO or \$O_3\$ rolling averages, 3/6 day PM averages or Pb 3 month rolling averages. @seealso <a href="#">aqs_sampledurations()</a> for a list of all available duration codes.
service	a string which represents the services provided by the AQS API. For a list of available services @seealso <a href="https://aqs.epa.gov/aqsweb/documents/data_api.html#services">https://aqs.epa.gov/aqsweb/documents/data_api.html#services</a>
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
AQS_domain	a R string object containing the domain that should be used in constructing the API call.

Value

a AQS\_DATAMART\_APIv2 S3 object that is the return value from the AQS API. A AQS\_DATAMART\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

See Also

Other Aggregate\_by\_site functions: [aqs\\_annualsummary\\_by\\_site\(\)](#), [aqs\\_dailysummary\\_by\\_site\(\)](#), [aqs\\_monitors\\_by\\_site\(\)](#), [aqs\\_qa\\_annualpeferomanceeval\\_by\\_site\(\)](#), [aqs\\_qa\\_annualperformanceevaltransa](#), [aqs\\_qa\\_annualperformanceevaltransaction\\_by\\_site\(\)](#), [aqs\\_qa\\_blanks\\_by\\_site\(\)](#), [aqs\\_qa\\_collocated\\_asse](#), [aqs\\_qa\\_flowrateaudit\\_by\\_site\(\)](#), [aqs\\_qa\\_flowrateverification\\_by\\_site\(\)](#), [aqs\\_qa\\_one\\_point\\_qc\\_by\\_site](#), [aqs\\_qa\\_pep\\_audit\\_by\\_site\(\)](#), [aqs\\_sampledata\\_by\\_site\(\)](#), [aqs\\_transactionsample\\_by\\_site\(\)](#)

---

aqs_services_by_state	<i>aqs_services_by_state</i>
-----------------------	------------------------------

---

Description

a helper function that abstracts the formatting of the inputs for a call to aqs away from the calling function for aggregations by State then calls the aqs and returns the result. This helper function is not meant to be called directly from external functions.

Usage

```
aqs_services_by_state(  
  parameter,  
  bdate,  
  edate,  
  stateFIPS,  
  duration = NA_character_,  
  service,  
  cbdate = NA_Date_,  
  cedate = NA_Date_,  
  AQS_domain = "aqs.epa.gov"  
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aqs_states()</a> for the list of available FIPS codes.

duration	an optional R character string that represents the parameter duration code that limits returned data to a specific sample duration. The default value of NA_character_ results in no filtering based on duration code. Valid durations include actual sample durations and not calculated durations such as 8 hour CO or SO <sub>3</sub> rolling averages, 3/6 day PM averages or Pb 3 month rolling averages. @seealso <a href="#">aqsampledurations()</a> for a list of all available duration codes.
service	a string which represents the services provided by the AQS API. For a list of available services @seealso <a href="https://aq.epa.gov/aqweb/documents/data_api.html#services">https://aq.epa.gov/aqweb/documents/data_api.html#services</a>
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
AQS_domain	a R string object containing the domain that should be used in constructing the API call.

### Value

a AQS\_DATAMART\_APIv2 S3 object that is the return value from the AQS API. A AQS\_DATAMART\_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

---

aqsign_up	<i>aqsign_up</i>
-----------	------------------

---

### Description

**[Stable]** Use this service to register as a new user or to reset an existing user's key. A verification email will be sent to the email account specified. To reset a password: If the request is made with an email that is already registered, a new key will be issued for that account and emailed to the listed address. Usage is the same in either case. Refer to the email message for further instructions before continuing.

### Usage

```
aqsign_up(email)
```

### Arguments

email	a R character object which represents the email account that will be used to register with the AQS API or change an existing user's key. A verification email will be sent to the account specified. Follow the instructions in the verification e-mail before proceeding to use any other functionality of the AQS API. Register your credential with the @3 <a href="#">aqcredentials()</a> before using the other functions in this library.
-------	---



---

aq<sub>s</sub>\_states

aq<sub>s</sub>\_states

---

### Description

**[Stable]** Returns a table of US states, US territories, and the district of Columbia with their respective FIPS codes.

### Usage

```
aqs_states(return_header = FALSE)
```

### Arguments

**return\_header** If FALSE (default) only returns data requested. If TRUE returns an AQSAPI\_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

### Value

a tibble or an AQS\_Data Mart\_APIv2 S3 object of states and their associated FIPS codes.

### Examples

```
#returns a tibble of states and their FIPS codes
## Not run: aqs_states()
```

---

aq<sub>s</sub>\_transactionssample\_by\_county

aq<sub>s</sub>\_transactionssample\_by\_county

---

### Description

**[Stable]** Returns transactionssample data - aggregated by county in the AQS Submission Transaction Format (RD) sample (raw) data for a parameter code aggregated by matching input parameter, stateFIPS and countycode provided for bdate - edate time frame. Includes data both in submitted and standard units

### Usage

```
aqs_transactionssample_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aq_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aq_counties_by_state()</a> for the list of available county codes for each state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of transaction sample (raw) data in the AQS submission transaction format (RD) corresponding to the inputs provided.

**Note**

The AQS API only allows for a single year of transactiondata to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_county functions: [aq\\_annualsummary\\_by\\_county\(\)](#), [aq\\_dailysummary\\_by\\_county\(\)](#), [aq\\_monitors\\_by\\_county\(\)](#), [aq\\_qa\\_annualperformanceeval\\_by\\_county\(\)](#), [aq\\_qa\\_blanks\\_by\\_county\(\)](#), [aq\\_qa\\_collocated\\_assessments\\_by\\_county\(\)](#), [aq\\_qa\\_flowrateaudit\\_by\\_county\(\)](#), [aq\\_qa\\_flowrateverification\\_by\\_county\(\)](#), [aq\\_qa\\_one\\_point\\_qc\\_by\\_county\(\)](#), [aq\\_qa\\_pep\\_audit\\_by\\_county\(\)](#), [aq\\_quarterlysummary\\_by\\_county\(\)](#), [aq\\_quarterlysummary\\_by\\_site\(\)](#), [aq\\_sampledata\\_by\\_county\(\)](#)

**Examples**

```
#Returns a AQS_Data Mart_APIv2 S3 object of the returns
## Not run: # returns all FRM/FEM transaction data for
# Wake County, NC between January and February 2016
aq_transactionsample_by_county(parameter = "88101",
                                bdate = as.Date("20160228",
                                                  format = "%Y%m%d"),
                                edate = as.Date("20160228",
                                                  format = "%Y%m%d"),
                                stateFIPS = "37",
```

```

countycode = "183"
)

## End(Not run)

```

---

```

aq_transactionsample_by_MA
      aq_transactionsample_MA

```

---

## Description

**[Stable]** Returns transactionsample data - aggregated by Monitoring agency (MA) in the AQS Submission Transaction Format (RD) sample (raw) data for a parameter code aggregated by matching input parameter, and monitoring agency (MA) code provided for bdate - edate time frame. Includes data both in submitted and standard units

## Usage

```

aq_transactionsample_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

## Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of transaction sample (raw) data in the AQS submission transaction format (RD) corresponding to the inputs provided.

**Note**

The AQS API only allows for a single year of transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate \_by\_state functions: [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_state\(\)](#), [aq<sub>s</sub>\\_qa\\_annualperformanceeval\\_by\\_state\(\)](#), [aq<sub>s</sub>\\_quarterlysummary\\_by\\_box\(\)](#), [aq<sub>s</sub>\\_quarterlysummary\\_by\\_cbsa\(\)](#), [aq<sub>s</sub>\\_quarterlysummary\\_by\\_state\(\)](#), [aq<sub>s</sub>\\_transactionsample\\_by\\_state\(\)](#)

**Examples**

```
#Returns a AQS_Data Mart_APIv2 S3 object of
## Not run: # all ozone transaction sample data for all monitors
# operated by South Coast Air Quality Management
# District collected on May 15, 2015
# North Carolina on May 15, 1995
aqs_transactionsample_by_MA(parameter = "44201",
                             bdate = as.Date("20150515",
                                                format = "%Y%m%d"),
                             edate = as.Date("20150515",
                                                format = "%Y%m%d"),
                             MA_code = "0972"
                             )

## End(Not run)
```

---

aq<sub>s</sub>\_transactionsample\_by\_site

*aq<sub>s</sub>\_transactionsample\_by\_site*


---

**Description**

**[Stable]** Returns transactionsample data aggregated by site in the AQS Submission Transaction Format (RD) sample (raw) data for a parameter code aggregated by matching input parameter, sitenum, countycode and stateFIPS provided for bdate - edate time frame. Includes data both in submitted and standard units

**Usage**

```

aqs_transactionsample_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aq<sub>s</sub>_states()</a> for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso <a href="#">aq<sub>s</sub>_counties_by_state()</a> for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of transaction sample (raw) data in the AQS submission transaction format (RD) corresponding to the inputs provided.

**Note**

The AQS API only allows for a single year of transactiondata to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated

calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

### See Also

Other Aggregate \_by\_site functions: [aq\\_annualsummary\\_by\\_site\(\)](#), [aq\\_dailysummary\\_by\\_site\(\)](#), [aq\\_monitors\\_by\\_site\(\)](#), [aq\\_qa\\_annualperformanceeval\\_by\\_site\(\)](#), [aq\\_qa\\_annualperformanceevaltransaction\\_by\\_site\(\)](#), [aq\\_qa\\_blanks\\_by\\_site\(\)](#), [aq\\_qa\\_collocated\\_asset\\_by\\_site\(\)](#), [aq\\_qa\\_flowrateaudit\\_by\\_site\(\)](#), [aq\\_qa\\_flowrateverification\\_by\\_site\(\)](#), [aq\\_qa\\_one\\_point\\_qc\\_by\\_site\(\)](#), [aq\\_qa\\_pep\\_audit\\_by\\_site\(\)](#), [aq\\_sampledata\\_by\\_site\(\)](#), [aq\\_services\\_by\\_site\(\)](#)

### Examples

```
#Returns a AQS_Data Mart_APIv2 S3 object of the returns
## Not run: # returns all ozone transaction data for the
# Millbrook School site (#0014) in Wake County, NC for
# June 18, 2017
aq_transactionsample_by_site(parameter = "44201",
                             bdate = as.Date("20170618",
                                                format = "%Y%m%d"),
                             edate = as.Date("20170618",
                                                format = "%Y%m%d"),
                             stateFIPS = "37",
                             countycode = "183",
                             sitenum = "0014"
                             )

## End(Not run)
```

---

aq\_transactionsample\_by\_state

*aq\_transactionsample\_by\_state*

---

### Description

**[Stable]** Returns transactionsample data - aggregated by state in the AQS Submission Transaction Format (RD) sample (raw) data for a parameter code aggregated by matching input parameter, and stateFIPS provided for bdate - edate time frame. Includes data both in submitted and standard units

### Usage

```
aq_transactionsample_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  return_header = FALSE
)
```

**Arguments**

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso <a href="#">aq_states()</a> for the list of available FIPS codes.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

**Value**

a tibble or an AQS\_Data Mart\_APIv2 S3 object of transaction sample (raw) data in the AQS submission transaction format (RD) corresponding to the inputs provided.

**Note**

The AQS API only allows for a single year of transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of  $O(n + 5 \text{ seconds})$ .

**See Also**

Other Aggregate\_by\_state functions: [aq\\_qa\\_annualperformanceeval\\_by\\_state\(\)](#), [aq\\_qa\\_annualperformanceeval\\_by\\_box\(\)](#), [aq\\_quarterlysummary\\_by\\_box\(\)](#), [aq\\_quarterlysummary\\_by\\_cbsa\(\)](#), [aq\\_quarterlysummary\\_by\\_state\(\)](#), [aq\\_transactionsample\\_by\\_MA\(\)](#)

**Examples**

```
#Returns a AQS_Data Mart_APIv2 S3 object of
## Not run: # all benzene transaction sample data for
# North Carolina on May 15, 1995
aq_transactionsample_by_state(parameter = "45201",
                              bdate = as.Date("19950515",
                                                format = "%Y%m%d"),
                              edate = as.Date("19950515",
                                                format = "%Y%m%d"),
                              stateFIPS = "37"
                              )

## End(Not run)
```

---

RAQSAPI*RAQSAPI: A R Interface to The United States Environmental Protection Agency's Air Quality System Data Mart RESTful API server.*

---

**Description**

RAQSAPI is a package for R that connects the R programming environment to the United State's Environmental protection agency's Air Quality System (AQS) Data Mart API for retrieval of air monitoring data.

There are two things that you must do before using this package.

1. If you have not done so yet register your username with Data Mart
2. Every time this library is reloaded `AQS_API_credentials()` function must be called before continuing.

please use `vignette(RAQSAPI)` for more details about this package.

EPA Disclaimer: This software/application was developed by the U.S. Environmental Protection Agency (USEPA). No warranty expressed or implied is made regarding the accuracy or utility of the system, nor shall the act of distribution constitute any such warranty. The USEPA has relinquished control of the information and no longer has responsibility to protect the integrity, confidentiality or availability of the information. Any reference to specific commercial products, processes, or services by service mark, trademark, manufacturer, or otherwise, does not constitute or imply their endorsement, recommendation or favoring by the USEPA. The USEPA seal and logo shall not be used in any manner to imply endorsement of any commercial product or activity by the USEPA or the United States Government.

# Index

## \* **Aggregate \_by\_MA functions**

aqs\_qa\_annualpeferomanceeval\_by\_MA, [37](#)  
aqs\_qa\_annualperformanceevaltransaction\_by\_MA, [44](#)  
aqs\_qa\_blanks\_by\_MA, [54](#)  
aqs\_qa\_collocated\_assessments\_by\_MA, [62](#)  
aqs\_qa\_flowrateaudit\_by\_MA, [71](#)  
aqs\_qa\_flowrateverification\_by\_MA, [79](#)  
aqs\_qa\_one\_point\_qc\_by\_MA, [88](#)  
aqs\_qa\_pep\_audit\_by\_MA, [96](#)

## \* **Aggregate \_by\_box functions**

aqs\_annualsummary\_by\_box, [4](#)  
aqs\_monitors\_by\_box, [28](#)  
aqs\_sampledata\_by\_box, [113](#)

## \* **Aggregate \_by\_cbsa functions**

aqs\_annualsummary\_by\_cbsa, [6](#)  
aqs\_dailysummary\_by\_cbsa, [18](#)  
aqs\_monitors\_by\_cbsa, [29](#)  
aqs\_sampledata\_by\_cbsa, [115](#)

## \* **Aggregate \_by\_county functions**

aqs\_annualsummary\_by\_county, [8](#)  
aqs\_dailysummary\_by\_county, [19](#)  
aqs\_monitors\_by\_county, [31](#)  
aqs\_qa\_annualperformanceeval\_by\_county, [50](#)  
aqs\_qa\_blanks\_by\_county, [52](#)  
aqs\_qa\_collocated\_assessments\_by\_county, [61](#)  
aqs\_qa\_flowrateaudit\_by\_county, [69](#)  
aqs\_qa\_flowrateverification\_by\_county, [77](#)  
aqs\_qa\_one\_point\_qc\_by\_county, [86](#)  
aqs\_qa\_pep\_audit\_by\_county, [94](#)  
aqs\_quarterlysummary\_by\_county, [106](#)  
aqs\_quarterlysummary\_by\_site, [108](#)  
aqs\_sampledata\_by\_county, [117](#)  
aqs\_transactionsample\_by\_county, [134](#)

## \* **Aggregate \_by\_pqao functions**

aqs\_qa\_annualpeferomanceeval\_by\_pqao, [38](#)  
aqs\_qa\_annualperformanceevaltransaction\_by\_pqao, [46](#)  
aqs\_qa\_blanks\_by\_pqao, [55](#)  
aqs\_qa\_collocated\_assessments\_by\_pqao, [64](#)  
aqs\_qa\_flowrateaudit\_by\_pqao, [72](#)  
aqs\_qa\_flowrateverification\_by\_pqao, [81](#)  
aqs\_qa\_one\_point\_qc\_by\_pqao, [89](#)  
aqs\_qa\_pep\_audit\_by\_pqao, [98](#)

## \* **Aggregate \_by\_site functions**

aqs\_annualsummary\_by\_site, [9](#)  
aqs\_dailysummary\_by\_site, [21](#)  
aqs\_monitors\_by\_site, [32](#)  
aqs\_qa\_annualpeferomanceeval\_by\_site, [39](#)  
aqs\_qa\_annualperformanceevaltransaction\_by\_county, [43](#)  
aqs\_qa\_annualperformanceevaltransaction\_by\_site, [47](#)  
aqs\_qa\_blanks\_by\_site, [57](#)  
aqs\_qa\_collocated\_assessments\_by\_site, [66](#)  
aqs\_qa\_flowrateaudit\_by\_site, [74](#)  
aqs\_qa\_flowrateverification\_by\_site, [82](#)  
aqs\_qa\_one\_point\_qc\_by\_site, [91](#)  
aqs\_qa\_pep\_audit\_by\_site, [99](#)  
aqs\_sampledata\_by\_site, [119](#)  
aqs\_services\_by\_site, [129](#)  
aqs\_transactionsample\_by\_site, [137](#)

## \* **Aggregate \_by\_state functions**

aqs\_qa\_annualpeferomanceeval\_by\_state, [41](#)  
aqs\_qa\_annualperformanceevaltransaction\_by\_state, [49](#)  
aqs\_quarterlysummary\_by\_box, [103](#)  
aqs\_quarterlysummary\_by\_cbsa, [105](#)  
aqs\_quarterlysummary\_by\_state, [110](#)  
aqs\_transactionsample\_by\_MA, [136](#)  
aqs\_transactionsample\_by\_state,

- 139
- \* **Aggregate\_by\_box functions**
  - aqs\_dailysummary\_by\_box, 16
- \* **Aggregate\_by\_state functions**
  - aqs\_annualsummary\_by\_state, 11
  - aqs\_dailysummary\_by\_state, 23
  - aqs\_monitors\_by\_state, 34
  - aqs\_qa\_blanks\_by\_state, 59
  - aqs\_qa\_collocated\_assessments\_by\_state, 67
  - aqs\_qa\_flowrateaudit\_by\_state, 76
  - aqs\_qa\_flowrateverification\_by\_state, 84
  - aqs\_qa\_one\_point\_qc\_by\_state, 93
  - aqs\_qa\_pep\_audit\_by\_state, 101
  - aqs\_sampledata\_by\_state, 121
- aqs\_annualsummary\_by\_box, 4, 29, 114
- aqs\_annualsummary\_by\_cbsa, 6, 19, 30, 116
- aqs\_annualsummary\_by\_county, 8, 21, 32, 51, 53, 62, 70, 79, 87, 95, 107, 109, 118, 135
- aqs\_annualsummary\_by\_site, 9, 22, 33, 41, 44, 48, 58, 67, 75, 84, 92, 101, 120, 131, 139
- aqs\_annualsummary\_by\_state, 11, 24, 35, 60, 69, 77, 85, 94, 102, 122
- aqs\_cbsas, 13
- aqs\_classes, 14
- aqs\_classes(), 36
- aqs\_counties\_by\_state, 15
- aqs\_counties\_by\_state(), 8, 10, 20, 22, 31, 33, 40, 43, 48, 51, 53, 58, 61, 66, 70, 75, 78, 83, 86, 91, 95, 100, 107, 109, 117, 119, 127, 130, 133, 135, 138
- aqs\_credentials, 15
- aqs\_credentials(), 132
- aqs\_dailysummary\_by\_box, 16
- aqs\_dailysummary\_by\_cbsa, 7, 18, 30, 116
- aqs\_dailysummary\_by\_county, 9, 19, 32, 51, 53, 62, 70, 79, 87, 95, 107, 109, 118, 135
- aqs\_dailysummary\_by\_site, 11, 21, 33, 41, 44, 48, 58, 67, 75, 84, 92, 101, 120, 131, 139
- aqs\_dailysummary\_by\_state, 13, 23, 35, 60, 69, 77, 85, 94, 102, 122
- aqs\_fields\_by\_service, 25
- aqs\_isavailable, 25
- aqs\_knownissues, 26
- aqs\_mas, 27
- aqs\_metadata\_service, 27
- aqs\_monitors\_by\_box, 6, 28, 114
- aqs\_monitors\_by\_cbsa, 7, 19, 29, 116
- aqs\_monitors\_by\_county, 9, 21, 31, 51, 53, 62, 70, 79, 87, 95, 107, 109, 118, 135
- aqs\_monitors\_by\_site, 11, 22, 32, 41, 44, 48, 58, 67, 75, 84, 92, 101, 120, 131, 139
- aqs\_monitors\_by\_state, 13, 24, 34, 60, 69, 77, 85, 94, 102, 122
- aqs\_parameters\_by\_class, 35
- aqs\_pqaos, 36
- aqs\_qa\_annualpeferomanceeval\_by\_MA, 37, 45, 55, 64, 72, 80, 89, 97
- aqs\_qa\_annualpeferomanceeval\_by\_pqao, 38, 47, 57, 65, 74, 82, 90, 99
- aqs\_qa\_annualpeferomanceeval\_by\_site, 11, 22, 33, 39, 44, 48, 58, 67, 75, 84, 92, 101, 120, 131, 139
- aqs\_qa\_annualpeferomanceeval\_by\_state, 41, 50, 104, 106, 111, 137, 140
- aqs\_qa\_annualperformanceeval\_by\_county, 9, 21, 32, 50, 53, 62, 70, 79, 87, 95, 107, 109, 118, 135
- aqs\_qa\_annualperformanceevaltransaction\_by\_county, 11, 22, 33, 41, 43, 48, 58, 67, 75, 84, 92, 101, 120, 131, 139
- aqs\_qa\_annualperformanceevaltransaction\_by\_MA, 38, 44, 55, 64, 72, 80, 89, 97
- aqs\_qa\_annualperformanceevaltransaction\_by\_pqao, 39, 46, 57, 65, 74, 82, 90, 99
- aqs\_qa\_annualperformanceevaltransaction\_by\_site, 11, 22, 33, 41, 44, 47, 59, 67, 75, 84, 92, 101, 120, 131, 139
- aqs\_qa\_annualperformanceevaltransaction\_by\_state, 42, 49, 104, 106, 111, 137, 140
- aqs\_qa\_blanks\_by\_county, 9, 21, 32, 51, 52, 62, 70, 79, 87, 95, 107, 109, 118, 135
- aqs\_qa\_blanks\_by\_MA, 38, 45, 54, 64, 72, 80, 89, 97
- aqs\_qa\_blanks\_by\_pqao, 39, 47, 55, 65, 74, 82, 90, 99
- aqs\_qa\_blanks\_by\_site, 11, 22, 33, 41, 44, 49, 57, 67, 75, 84, 92, 101, 120, 131, 139
- aqs\_qa\_blanks\_by\_state, 13, 24, 35, 59, 69, 77, 85, 94, 102, 122
- aqs\_qa\_collocated\_assessments\_by\_county, 9, 21, 32, 51, 53, 61, 70, 79, 87, 96, 107, 109, 118, 135
- aqs\_qa\_collocated\_assessments\_by\_MA, 38, 45, 55, 62, 72, 80, 89, 97
- aqs\_qa\_collocated\_assessments\_by\_pqao, 39, 47, 57, 64, 74, 82, 90, 99

- aqs\_qa\_collocated\_assessments\_by\_site, [11, 22, 33, 41, 44, 49, 59, 66, 75, 84, 92, 101, 120, 131, 139](#)
- aqs\_qa\_collocated\_assessments\_by\_state, [13, 24, 35, 60, 67, 77, 85, 94, 102, 122](#)
- aqs\_qa\_flowrateaudit\_by\_county, [9, 21, 32, 52, 53, 62, 69, 79, 87, 96, 107, 109, 118, 135](#)
- aqs\_qa\_flowrateaudit\_by\_MA, [38, 45, 55, 64, 71, 80, 89, 97](#)
- aqs\_qa\_flowrateaudit\_by\_pqao, [39, 47, 57, 65, 72, 82, 90, 99](#)
- aqs\_qa\_flowrateaudit\_by\_site, [11, 23, 33, 41, 44, 49, 59, 67, 74, 84, 92, 101, 120, 131, 139](#)
- aqs\_qa\_flowrateaudit\_by\_state, [13, 24, 35, 60, 69, 76, 85, 94, 102, 122](#)
- aqs\_qa\_flowrateverification\_by\_county, [9, 21, 32, 52, 53, 62, 70, 77, 87, 96, 107, 109, 118, 135](#)
- aqs\_qa\_flowrateverification\_by\_MA, [38, 45, 55, 64, 72, 79, 89, 97](#)
- aqs\_qa\_flowrateverification\_by\_pqao, [39, 47, 57, 65, 74, 81, 90, 99](#)
- aqs\_qa\_flowrateverification\_by\_site, [11, 23, 33, 41, 44, 49, 59, 67, 75, 82, 92, 101, 120, 131, 139](#)
- aqs\_qa\_flowrateverification\_by\_state, [13, 24, 35, 60, 69, 77, 84, 94, 102, 122](#)
- aqs\_qa\_one\_point\_qc\_by\_county, [9, 21, 32, 52, 53, 62, 70, 79, 86, 96, 107, 109, 118, 135](#)
- aqs\_qa\_one\_point\_qc\_by\_MA, [38, 45, 55, 64, 72, 80, 88, 97](#)
- aqs\_qa\_one\_point\_qc\_by\_pqao, [39, 47, 57, 65, 74, 82, 89, 99](#)
- aqs\_qa\_one\_point\_qc\_by\_site, [11, 23, 33, 41, 44, 49, 59, 67, 75, 84, 91, 101, 120, 131, 139](#)
- aqs\_qa\_one\_point\_qc\_by\_state, [13, 24, 35, 60, 69, 77, 85, 93, 102, 122](#)
- aqs\_qa\_pep\_audit\_by\_county, [9, 21, 32, 52, 53, 62, 70, 79, 87, 94, 107, 109, 118, 135](#)
- aqs\_qa\_pep\_audit\_by\_MA, [38, 45, 55, 64, 72, 80, 89, 96](#)
- aqs\_qa\_pep\_audit\_by\_pqao, [39, 47, 57, 65, 74, 82, 90, 98](#)
- aqs\_qa\_pep\_audit\_by\_site, [11, 23, 33, 41, 44, 49, 59, 67, 75, 84, 92, 99, 120, 131, 139](#)
- aqs\_qa\_pep\_audit\_by\_state, [13, 24, 35, 60, 69, 77, 85, 94, 101, 122](#)
- aqs\_quarterlysummary\_by\_box, [42, 50, 103, 106, 111, 137, 140](#)
- aqs\_quarterlysummary\_by\_cbsa, [42, 50, 104, 105, 111, 137, 140](#)
- aqs\_quarterlysummary\_by\_county, [9, 21, 32, 52, 53, 62, 70, 79, 87, 96, 106, 109, 118, 135](#)
- aqs\_quarterlysummary\_by\_site, [9, 21, 32, 52, 53, 62, 70, 79, 87, 96, 107, 108, 118, 135](#)
- aqs\_quarterlysummary\_by\_state, [42, 50, 104, 106, 110, 137, 140](#)
- aqs\_removeheader, [111](#)
- aqs\_revisionhistory, [112](#)
- aqs\_sampledata\_by\_box, [6, 29, 113](#)
- aqs\_sampledata\_by\_cbsa, [7, 19, 30, 115](#)
- aqs\_sampledata\_by\_county, [9, 21, 32, 52, 53, 62, 70, 79, 87, 96, 107, 109, 117, 135](#)
- aqs\_sampledata\_by\_site, [11, 23, 33, 41, 44, 49, 59, 67, 75, 84, 92, 101, 119, 131, 139](#)
- aqs\_sampledata\_by\_state, [13, 24, 35, 60, 69, 77, 85, 94, 102, 121](#)
- aqs\_sampledurations, [123](#)
- aqs\_sampledurations(), [114, 115, 117, 120, 122, 124, 126, 127, 130, 132](#)
- aqs\_services\_by\_box, [123](#)
- aqs\_services\_by\_cbsa, [125](#)
- aqs\_services\_by\_county, [126](#)
- aqs\_services\_by\_MA, [127](#)
- aqs\_services\_by\_pqao, [128](#)
- aqs\_services\_by\_site, [11, 23, 33, 41, 44, 49, 59, 67, 75, 84, 92, 101, 120, 129, 139](#)
- aqs\_services\_by\_state, [131](#)
- aqs\_sign\_up, [132](#)
- aqs\_sign\_up(), [15](#)
- aqs\_sites\_by\_county, [133](#)
- aqs\_states, [134](#)
- aqs\_states(), [8, 10, 12, 15, 20, 22, 24, 31, 33, 34, 40, 42, 43, 48, 49, 51, 53, 58, 60, 61, 66, 68, 70, 75, 76, 78, 83, 85, 86, 91, 93, 95, 100, 102, 107, 108, 110, 117, 119, 121, 127, 130, 131, 133, 135, 138, 140](#)
- aqs\_transactionsample\_by\_county, [9, 21, 32, 52, 53, 62, 70, 79, 87, 96, 107, 109, 118, 134](#)

aq\_transactionsample\_by\_MA, [42](#), [50](#), [104](#),  
[106](#), [111](#), [136](#), [140](#)  
aq\_transactionsample\_by\_site, [11](#), [23](#),  
[33](#), [41](#), [44](#), [49](#), [59](#), [67](#), [75](#), [84](#), [92](#),  
[101](#), [120](#), [131](#), [137](#)  
aq\_transactionsample\_by\_state, [42](#), [50](#),  
[104](#), [106](#), [111](#), [137](#), [139](#)  
  
RAQSAPI, [141](#)