

Package ‘dm’

May 25, 2020

Title Relational Data Models

Version 0.1.3

Date 2020-05-24

Description Provides tools for working with multiple related tables, stored as data frames or in a relational database. Multiple tables (data and metadata) are stored in a compound object, which can then be manipulated with a pipe-friendly syntax.

License MIT + file LICENSE

URL <https://kr1mlr.github.io/dm>, <https://github.com/kr1mlr/dm>

BugReports <https://github.com/kr1mlr/dm/issues>

Depends R (>= 3.3)

Imports backports,
cli (>= 2.0.0),
DBI,
dplyr,
ellipsis,
glue,
igraph,
lifecycle,
magrittr,
memoise,
methods,
pillar,
purrr,
rlang (>= 0.4.0),
tibble,
tidyr (>= 1.0.0),
tidyselect (>= 1.0.0),
vctrs (>= 0.2.0)

Suggests brio,
crayon,
dbplyr,
DiagrammeR,

DiagrammeRsvg,
 digest,
 fansi,
 keyring,
 knitr,
 nycflights13,
 odbc,
 RMariaDB,
 rmarkdown,
 rprojroot,
 RSQLite,
 testthat ($\geq 2.1.0$),
 tidyverse,
 withr

Enhances RPostgres

VignetteBuilder knitr

RdMacros lifecycle

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE, roclets = c("`collate",
 ``namespace", ``rd"))

RoxygenNote 7.1.0

R topics documented:

check_key	3
check_set_equality	4
check_subset	5
copy_dm_to	6
decompose_table	7
dm	8
dm_add_fk	10
dm_add_pk	12
dm_add_tbl	14
dm_disambiguate_cols	15
dm_draw	16
dm_enum_fk_candidates	18
dm_examine_constraints	19
dm_filter	20
dm_financial	22
dm_flatten_to_tbl	23
dm_from_src	24
dm_get_all_fks	25
dm_get_all_pks	26
dm_get_filters	27
dm_get_fk	28

dm_get_pk	29
dm_get_referencing_tables	30
dm_has_fk	30
dm_has_pk	31
dm_is_referenced	32
dm_join_to_tbl	32
dm_nrow	33
dm_nycflights13	34
dm_paste	34
dm_ptype	36
dm_rename	36
dm_rm_tbl	37
dm_select	38
dm_select_tbl	39
dm_zoom_to	40
dplyr_join	42
dplyr_table_manipulation	43
enum_pk_candidates	44
examine_cardinality	45
head.zoomed_dm	47
pull_tbl	48
reunite_parent_child	49
tbl.dm	50
tidyr_table_manipulation	51

Index 53

check_key	<i>Check if column(s) can be used as keys</i>
-----------	---

Description

check_key() accepts a data frame and, optionally, columns. It throws an error if the specified columns are NOT a unique key of the data frame. If the columns given in the ellipsis ARE a key, the data frame itself is returned silently, so that it can be used for piping.

Usage

```
check_key(.data, ...)
```

Arguments

.data	The data frame whose columns should be tested for key properties.
...	The names of the columns to be checked. One or more unquoted expressions separated by commas. Variable names can be treated as if they were positions, so you can use expressions like x:y to select ranges of variables.

The arguments in ... are automatically quoted and evaluated in a context where column names represent column positions. They also support unquoting and splicing. See `vignette("programming")` for an introduction to these concepts. See select helpers for more details and examples about tidyselect helpers such as `starts_with()`, `everything()`, ...

Value

Returns `.data`, invisibly, if the check is passed. Otherwise an error is thrown and the reason for it is explained.

Examples

```
data <- tibble::tibble(a = c(1, 2, 1), b = c(1, 4, 1), c = c(5, 6, 7))
# this is failing:
try(check_key(data, a, b))

# this is passing:
check_key(data, a, c)
```

check_set_equality	<i>Check column values for set equality</i>
--------------------	---

Description

`check_set_equality()` is a wrapper of `check_subset()`. It tests if one value set is a subset of another and vice versa, i.e., if both sets are the same. If not, it throws an error.

Usage

```
check_set_equality(t1, c1, t2, c2)
```

Arguments

<code>t1</code>	The data frame that contains column <code>c1</code> .
<code>c1</code>	The column of <code>t1</code> that should only contain values that are also present in column <code>c2</code> of data frame <code>t2</code> .
<code>t2</code>	The data frame that contains column <code>c2</code> .
<code>c2</code>	The column of <code>t2</code> that should only contain values that are also present in column <code>c1</code> of data frame <code>t1</code> .

Value

Returns `t1`, invisibly, if the check is passed. Otherwise an error is thrown and the reason for it is explained.

Examples

```
data_1 <- tibble::tibble(a = c(1, 2, 1), b = c(1, 4, 1), c = c(5, 6, 7))
data_2 <- tibble::tibble(a = c(1, 2, 3), b = c(4, 5, 6), c = c(7, 8, 9))
# this is failing:
try(check_set_equality(data_1, a, data_2, a))

data_3 <- tibble::tibble(a = c(2, 1, 2), b = c(4, 5, 6), c = c(7, 8, 9))
# this is passing:
check_set_equality(data_1, a, data_3, a)
```

check_subset	<i>Check column values for subset</i>
--------------	---------------------------------------

Description

check_subset() tests if the values of the chosen column c1 of data frame t1 are a subset of the values of column c2 of data frame t2.

Usage

```
check_subset(t1, c1, t2, c2)
```

Arguments

t1	The data frame that contains column c1.
c1	The column of t1 that should only contain the values that are also present in column c2 of data frame t2.
t2	The data frame that contains column c2.
c2	The column of the second data frame that has to contain all values of c1 to avoid an error.

Value

Returns t1, invisibly, if the check is passed. Otherwise an error is thrown and the reason for it is explained.

Examples

```
data_1 <- tibble::tibble(a = c(1, 2, 1), b = c(1, 4, 1), c = c(5, 6, 7))
data_2 <- tibble::tibble(a = c(1, 2, 3), b = c(4, 5, 6), c = c(7, 8, 9))
# this is passing:
check_subset(data_1, a, data_2, a)

# this is failing:
try(check_subset(data_2, a, data_1, a))
```

copy_dm_to

Copy data model to data source

Description

copy_dm_to() takes a `dplyr::src_dbi` object or a `DBI::DBIConnection` object as its first argument and a `dm` object as its second argument. The latter is copied to the former. By default, temporary tables will be created and the key constraints will be set (currently only on MSSQL and Postgres databases).

Usage

```
copy_dm_to(
  dest,
  dm,
  ...,
  types = NULL,
  overwrite = NULL,
  indexes = NULL,
  unique_indexes = NULL,
  set_key_constraints = TRUE,
  unique_table_names = FALSE,
  table_names = NULL,
  temporary = TRUE
)
```

Arguments

dest	An object of class "src" or "DBIConnection".
dm	A dm object.
...	Possible further arguments passed to <code>dplyr::copy_to()</code> , which is used on each table.
overwrite, types, indexes, unique_indexes	Must remain NULL.
set_key_constraints	Boolean variable, if TRUE will mirror dm key constraints on a database.
unique_table_names	Boolean, if FALSE (default), the original table names will be used, if TRUE, unique table names will be created based on the original table names.
table_names	A named character vector, containing the names that you want the tables in the dm to have after copying them to the database. The table names within the dm will remain unchanged. The name of each element of the vector needs to be one of the table names of the dm. Those tables of the dm that are not addressed will be called by their original name on the database.
temporary	Boolean variable, if TRUE, only temporary tables will be created. These tables will vanish when disconnecting from the database.

Details

No tables will be overwritten; passing `overwrite = TRUE` to the function will give an error. Types are determined separately for each table, setting the `types` argument will also throw an error. The arguments are included in the signature to avoid passing them via the `...` ellipsis.

Value

A dm object on the given `src`.

Examples

```
src_sqlite <- dplyr::src_sqlite(":memory:", create = TRUE)
iris_dm <- copy_dm_to(
  src_sqlite,
  as_dm(list(iris = iris)),
  set_key_constraints = FALSE
)
```

decompose_table	<i>Decompose a table into two linked tables</i>
-----------------	---

Description

Questioning

Perform table surgery by extracting a 'parent table' from a table, linking the original table and the new table by a key, and returning both tables.

`decompose_table()` accepts a data frame, a name for the 'ID column' that will be newly created, and the names of the columns that will be extracted into the new data frame.

It creates a 'parent table', which consists of the columns specified in the ellipsis, and a new 'ID column'. Then it removes those columns from the original table, which is now called the 'child table', and adds the 'ID column'.

Usage

```
decompose_table(.data, new_id_column, ...)
```

Arguments

<code>.data</code>	Data frame from which columns <code>...</code> are to be extracted.
<code>new_id_column</code>	Name of the identifier column (primary key column) for the parent table. A column of this name is also added in 'child table'.
<code>...</code>	The columns to be extracted from the <code>.data</code> . One or more unquoted expressions separated by commas. You can treat variable names as if they were positions, so you can use expressions like <code>x:y</code> to select ranges of variables.

The arguments in ... are automatically quoted and evaluated in a context where column names represent column positions. They also support unquoting and splicing. See `vignette("programming")` for an introduction to those concepts.

See `select` helpers for more details, and the examples about `tidyselect` helpers, such as `starts_with()`, `everything()`, ...

Value

A named list of length two:

- entry "child_table": the child table with column `new_id_column` referring to the same column in `parent_table`,
- entry "parent_table": the "lookup table" for `child_table`.

Life cycle

This function is marked "questioning" because it feels more useful when applied to a table in a `dm` object.

See Also

Other table surgery functions: `reunite_parent_child()`

Examples

```
decomposed_table <- decompose_table(mtcars, new_id, am, gear, carb)
decomposed_table$child_table
decomposed_table$parent_table
```

dm

Data model class

Description

The `dm` class holds a list of tables and their relationships. It is inspired by `datamodelr`, and extends the idea by offering operations to access the data in the tables.

`dm()` creates a `dm` object from one or multiple `tbl` objects (tibbles or lazy data objects).

`new_dm()` is a low-level constructor that creates a new `dm` object.

- If called without arguments, it will create an empty `dm`.
- If called with arguments, no validation checks will be made to ascertain that the inputs are of the expected class and internally consistent; use `validate_dm()` to double-check the returned object.

`validate_dm()` checks the internal consistency of a dm object.

`dm_get_src()` returns the **dplyr** source for a dm object. All tables in a dm object must be from the same source, i.e. either they are all data frames, or they all are stored on the same database.

`dm_get_con()` returns the [DBI::DBIConnection](#) for dm objects. This works only if the tables are stored on a database, otherwise an error is thrown.

`dm_get_tables()` returns a named list of **dplyr** [tbl](#) objects of a dm object. Filtering expressions are NOT evaluated at this stage. To get a filtered table, use `dm_apply_filters_to_tbl()`, to apply filters to all tables use `dm_apply_filters()`

`is_dm()` returns TRUE if the input is of class dm.

`as_dm()` coerces objects to the dm class

Usage

```
dm(..., .name_repair = c("check_unique", "unique", "universal", "minimal"))
```

```
new_dm(tables = list())
```

```
validate_dm(x)
```

```
dm_get_src(x)
```

```
dm_get_con(x)
```

```
dm_get_tables(x)
```

```
is_dm(x)
```

```
as_dm(x)
```

Arguments

<code>...</code>	Tables to add to the dm object. If no names are provided, the tables are auto-named.
<code>.name_repair</code>	Options for name repair. Forwarded as <code>repair</code> to vctrs::vec_as_names() .
<code>tables</code>	A named list of the tables (tibble-objects, not names), to be included in the dm object.
<code>x</code>	An object.

Value

For `dm()`, `new_dm()`, `as_dm()`: A dm object.

For `validate_dm()`: Returns the dm, invisibly, after finishing all checks.

For `dm_get_src()`: the **dplyr** source for a dm object.

For `dm_get_con()`: The [DBI::DBIConnection](#) for dm objects.

For `dm_get_tables()`: A named list with the tables constituting the dm.

For `is_dm()`: Boolean, is this object a dm.

See Also

- `dm_from_src()` for connecting to all tables in a database and importing the primary and foreign keys
- `dm_add_pk()` and `dm_add_fk()` for adding primary and foreign keys
- `copy_dm_to()` for DB interaction
- `dm_draw()` for visualization
- `dm_join_to_tbl()` for flattening
- `dm_filter()` for filtering
- `dm_select_tbl()` for creating a dm with only a subset of the tables
- `dm_nycflights13()` for creating an example dm object
- `decompose_table()` for table surgery
- `check_key()` and `check_subset()` for checking for key properties
- `examine_cardinality()` for checking the cardinality of the relation between two tables

Examples

```
dm(iris, mtcars)
new_dm(list(iris = iris, mtcars = mtcars))
as_dm(list(iris = iris, mtcars = mtcars))

dm_nycflights13() %>% tbl("airports")
dm_nycflights13() %>% src_tbls()
dm_nycflights13() %>% dm_get_src()

copy_dm_to(
  dbplyr::src_memdb(),
  dm_nycflights13(),
  unique_table_names = TRUE
) %>%
  dm_get_con()

dm_nycflights13() %>% dm_get_tables()
dm_nycflights13() %>% dm_get_filters()
dm_nycflights13() %>% validate_dm()
is_dm(dm_nycflights13())
dm_nycflights13()["airports"]
dm_nycflights13()[["airports"]]
dm_nycflights13()$airports
```

Description

dm_add_fk() marks the specified columns as the foreign key of table `table` with respect to the primary key of table `ref_table`. If `check == TRUE`, then it will first check if the values in `columns` are a subset of the values of the primary key in table `ref_table`.

dm_rm_fk() can remove either one reference between two tables, or all references at once, if argument `columns = NULL`. All arguments may be provided quoted or unquoted.

Usage

```
dm_add_fk(dm, table, columns, ref_table, check = FALSE)
```

```
dm_rm_fk(dm, table, columns, ref_table)
```

Arguments

<code>dm</code>	A dm object.
<code>table</code>	A table in the dm.
<code>columns</code>	For dm_add_fk(): The columns of table which are to become the foreign key columns that reference the primary key of <code>ref_table</code> . For dm_rm_fk(): The columns of table that should no longer be referencing the primary key of <code>ref_table</code> . If <code>NULL</code> , all columns will be evaluated.
<code>ref_table</code>	For dm_add_fk(): The table which table will be referencing. This table needs to have a primary key set. For dm_rm_fk(): The table that table is referencing.
<code>check</code>	Boolean, if <code>TRUE</code> , a check will be performed to determine if the values of column are a subset of the values of the primary key column of <code>ref_table</code> .

Value

For dm_add_fk(): An updated dm with an additional foreign key relation.

For dm_rm_fk(): An updated dm without the given foreign key relation.

Compound keys

Currently, keys consisting of more than one column are not supported. **This feature** is planned for dm 0.2.0. The syntax of these functions will be extended but will remain compatible with current semantics.

See Also

Other foreign key functions: [dm_enum_fk_candidates\(\)](#), [dm_get_all_fks\(\)](#), [dm_get_fk\(\)](#), [dm_has_fk\(\)](#)

Other foreign key functions: [dm_enum_fk_candidates\(\)](#), [dm_get_all_fks\(\)](#), [dm_get_fk\(\)](#), [dm_has_fk\(\)](#)

Examples

```

if (rlang::is_installed("nycflights13")) {
  nycflights_dm <- dm(
    planes = nycflights13::planes,
    flights = nycflights13::flights
  )
} else {
  message("Using mock-up data, install the nycflights13 package to fix.")
  nycflights_dm <- dm(
    planes = tibble(tailnum = character()),
    flights = tibble(tailnum = character())
  )
}

nycflights_dm %>%
  dm_draw()

nycflights_dm %>%
  dm_add_pk(planes, tailnum) %>%
  dm_add_fk(flights, tailnum, planes) %>%
  dm_draw()

dm_nycflights13(cycle = TRUE) %>%
  dm_rm_fk(flights, dest, airports) %>%
  dm_draw()

```

dm_add_pk

Add/remove a primary key

Description

dm_add_pk() marks the specified columns as the primary key of the specified table. If check == TRUE, then it will first check if the given combination of columns is a unique key of the table. If force == TRUE, the function will replace an already set key.

dm_rm_pk() removes a primary key from a table and leaves the [dm](#) object otherwise unaltered. Foreign keys that point to the table from other tables, can be optionally removed as well.

Usage

```
dm_add_pk(dm, table, columns, check = FALSE, force = FALSE)
```

```
dm_rm_pk(dm, table, rm_referencing_fks = FALSE)
```

Arguments

dm	A dm object.
table	A table in the dm.
columns	Table columns, unquoted.

check	Boolean, if TRUE, a check is made if the combination of columns is a unique key of the table.
force	Boolean, if FALSE (default), an error will be thrown if there is already a primary key set for this table. If TRUE, a potential old pk is deleted before setting a new one.
rm_referencing_fks	Boolean: if FALSE (default), will throw an error if there are foreign keys addressing the primary key that is to be removed. If TRUE, the function will remove, in addition to the primary key of the table argument, also all foreign key constraints that are pointing to it.

Value

For `dm_add_pk()`: An updated `dm` with an additional primary key.

For `dm_rm_pk()`: An updated `dm` without the indicated primary key.

Compound keys

Currently, keys consisting of more than one column are not supported. **This feature** is planned for `dm 0.2.0`. The syntax of these functions will be extended but will remain compatible with current semantics.

See Also

Other primary key functions: `dm_get_all_pks()`, `dm_get_pk()`, `dm_has_pk()`, `enum_pk_candidates()`

Examples

```
if (rlang::is_installed("nycflights13")) {
  nycflights_dm <- dm(
    planes = nycflights13::planes,
    airports = nycflights13::airports
  )
} else {
  message("Using mock-up data, install the nycflights13 package to fix.")
  nycflights_dm <- dm(
    planes = tibble(tailnum = letters[1:2], manufacturer = "Acme"),
    airports = tibble(faa = character())
  )
}

nycflights_dm %>%
  dm_draw()

# the following works
nycflights_dm %>%
  dm_add_pk(planes, tailnum) %>%
  dm_add_pk(airports, faa, check = TRUE) %>%
  dm_draw()

# the following does not work (throws an error)
```

```
try(
  nycflights_dm %>%
    dm_add_pk(planes, manufacturer, check = TRUE)
)

dm_nycflights13() %>%
  dm_rm_pk(airports, rm_referencing_fks = TRUE) %>%
  dm_draw()
```

dm_add_tbl

*Add tables to a dm***Description**

dm_add_tbl() adds one or more tables to a [dm](#). It uses [mutate\(\)](#) semantics.

Usage

```
dm_add_tbl(dm, ..., repair = "unique", quiet = FALSE)
```

Arguments

dm	A dm object.
...	One or more tables to add to the dm. If no explicit name is given, the name of the expression is used.
repair	<p>Either a string or a function. If a string, it must be one of "check_unique", "minimal", "unique", or "universal". If a function, it is invoked with a vector of minimal names and must return minimal names, otherwise an error is thrown.</p> <ul style="list-style-type: none"> Minimal names are never NULL or NA. When an element doesn't have a name, its minimal name is an empty string. Unique names are unique. A suffix is appended to duplicate names to make them unique. Universal names are unique and syntactic, meaning that you can safely use the names as variables without causing a syntax error. <p>The "check_unique" option doesn't perform any name repair. Instead, an error is raised if the names don't suit the "unique" criteria.</p>
quiet	By default, the user is informed of any renaming caused by repairing the names. This only concerns unique and universal repairing. Set quiet to TRUE to silence the messages.

Value

The initial dm with the additional table(s).

See Also

[dm_rm_tbl\(\)](#)

Examples

```
dm() %>%
  dm_add_tbl(mtcars, flowers = iris)

# renaming table names if necessary (depending on the `repair` argument)
dm() %>%
  dm_add_tbl(new_tbl = mtcars, new_tbl = iris)
```

dm_disambiguate_cols *Resolve column name ambiguities*

Description

This function ensures that all columns in a dm have unique names.

Usage

```
dm_disambiguate_cols(dm, sep = ".", quiet = FALSE)
```

Arguments

dm	A dm object.
sep	The character variable that separates the names of the table and the names of the ambiguous columns.
quiet	Boolean. By default, this function lists the renamed columns in a message, pass TRUE to suppress this message.

Details

The function first checks if there are any column names that are not unique. If there are, those columns will be assigned new, unique, names by prefixing their existing name with the name of their table and a separator. Columns that act as primary or foreign keys will not be renamed because only the foreign key column will remain when two tables are joined, making that column name "unique" as well.

Value

A dm whose column names are unambiguous.

Examples

```
dm_disambiguate_cols(dm_nycflights13())
```

dm_draw

*Draw a diagram of the data model***Description**

dm_draw() uses **DiagrammeR** to draw diagrams.

dm_set_colors() allows to define the colors that will be used to display the tables of the data model. The colors can either be either specified with hex color codes or using the names of the built-in R colors. An overview of the colors corresponding to the standard color names can be found at the bottom of <http://rpubs.com/krlmlr/colors>.

dm_get_colors() returns the colors defined for a data model.

dm_get_available_colors() returns an overview of the names of the available colors. These are the standard colors also returned by grDevices::colors() plus a default table color with the name "default".

Usage

```
dm_draw(
  dm,
  rankdir = "LR",
  col_attr = "column",
  view_type = "keys_only",
  columnArrows = TRUE,
  graph_attrs = "",
  node_attrs = "",
  edge_attrs = "",
  focus = NULL,
  graph_name = "Data Model"
)

dm_set_colors(dm, ...)

dm_get_colors(dm)

dm_get_available_colors()
```

Arguments

dm	A dm object.
rankdir	Graph attribute for direction (e.g., 'BT' = bottom -> top).
col_attr	Column attributes to display. By default only the column name ("column") is displayed.
view_type	Can be "keys_only" (default), "all" or "title_only". It defines the level of details for rendering tables (only primary and foreign keys, all columns, or no columns).
columnArrows	Edges from columns to columns (default: TRUE).

graph_attrs	Additional graph attributes.
node_attrs	Additional node attributes.
edge_attrs	Additional edge attributes.
focus	A list of parameters for rendering (table filter).
graph_name	The name of the graph.
...	Colors to set in the form color = table. Allowed colors are all hex coded colors (quoted) and the color names from dm_get_available_colors(). tidyselect is supported, see dplyr::select() for details on the semantics.

Value

For dm_draw(): returns an object of class grViz (see also [DiagrammeR::grViz\(\)](#)), which, when printed, produces the output seen in the viewer as a side effect.

For dm_set_colors(): the updated data model.

For dm_get_colors(), a two-column tibble with one row per table.

For dm_get_available_colors(), a vector with the available colors.

Examples

```
dm_nycflights13() %>%
  dm_draw()

dm_nycflights13(cycle = TRUE) %>%
  dm_draw(view_type = "title_only")

head(dm_get_available_colors())
length(dm_get_available_colors())

dm_nycflights13() %>%
  dm_get_colors()

dm_nycflights13(color = FALSE) %>%
  dm_set_colors(
    darkblue = starts_with("air"),
    "#5986C4" = flights
  ) %>%
  dm_draw()

# Splicing is supported:
nyc_cols <-
  dm_nycflights13() %>%
  dm_get_colors()
nyc_cols

dm_nycflights13(color = FALSE) %>%
  dm_set_colors(!!!nyc_cols) %>%
  dm_draw()
```

dm_enum_fk_candidates *Foreign key candidates*

Description

Questioning

Determine which columns would be good candidates to be used as foreign keys of a table, to reference the primary key column of another table of the `dm` object.

Usage

```
dm_enum_fk_candidates(dm, table, ref_table)
```

```
enum_fk_candidates(zoomed_dm, ref_table)
```

Arguments

<code>dm</code>	A dm object.
<code>table</code>	The table whose columns should be tested for suitability as foreign keys.
<code>ref_table</code>	A table with a primary key.
<code>zoomed_dm</code>	A dm with a zoomed table.

Details

`dm_enum_fk_candidates()` first checks if `ref_table` has a primary key set, if not, an error is thrown.

If `ref_table` does have a primary key, then a join operation will be tried using that key as the by argument of `join()` to match it to each column of `table`. Attempting to join incompatible columns triggers an error.

The outcome of the join operation determines the value of the `why` column in the result:

- an empty value for a column of `table` that is a suitable foreign key candidate
- the count and percentage of missing matches for a column that is not suitable
- the error message triggered for unsuitable candidates that may include the types of mismatched columns

`enum_fk_candidates()` works like `dm_enum_fk_candidates()` with the zoomed table as `table`.

Value

A tibble with the following columns:

`columns` columns of `table`,

`candidate` boolean: are these columns a candidate for a foreign key,

`why` if not a candidate for a foreign key, explanation for for this.

Life cycle

These functions are marked "questioning" because we are not yet sure about the interface, in particular if we need both `dm_enum...()` and `enum...()` variants. Changing the interface later seems harmless because these functions are most likely used interactively.

See Also

Other foreign key functions: [dm_add_fk\(\)](#), [dm_get_all_fks\(\)](#), [dm_get_fk\(\)](#), [dm_has_fk\(\)](#)

Examples

```
dm_nycflights13() %>%  
  dm_enum_fk_candidates(flights, airports)  
  
dm_nycflights13() %>%  
  dm_zoom_to(flights) %>%  
  enum_fk_candidates(airports)
```

`dm_examine_constraints`*Validate your data model*

Description

This function returns a tibble with information about which key constraints are met (`is_key = TRUE`) or violated (`FALSE`). The printing for this object is special, use [as_tibble\(\)](#) to print as a regular tibble.

Usage

```
dm_examine_constraints(dm)
```

Arguments

<code>dm</code>	A dm object.
-----------------	--------------

Details

For the primary key constraints, it is tested if the values in the respective columns are all unique. For the foreign key constraints, the tests check if for each foreign key constraint, the values of the foreign key column form a subset of the values of the referenced column.

Value

A tibble with the following columns:

table the table in the dm,
 kind "PK" or "FK",
 columns the table columns that define the key,
 ref_table for foreign keys, the referenced table,
 is_key logical,
 problem if is_key = FALSE, the reason for that.

Examples

```
dm_nycflights13() %>%
  dm_examine_constraints()
```

dm_filter

Filtering

Description**Questioning**

Filtering a table of a `dm` object may affect other tables that are connected to it directly or indirectly via foreign key relations.

`dm_filter()` can be used to define filter conditions for tables using syntax that is similar to `dplyr::filter()`. These conditions will be stored in the `dm`, and executed immediately for the tables that they are referring to.

With `dm_apply_filters()`, all tables will be updated according to the filter conditions and the foreign key relations.

`dm_apply_filters_to_tbl()` retrieves one specific table of the `dm` that is updated according to the filter conditions and the foreign key relations.

Usage

```
dm_filter(dm, table, ...)
```

```
dm_apply_filters(dm)
```

```
dm_apply_filters_to_tbl(dm, table)
```

Arguments

<code>dm</code>	A dm object.
<code>table</code>	A table in the dm.
<code>...</code>	Logical predicates defined in terms of the variables in <code>.data</code> , passed on to <code>dplyr::filter()</code> . Multiple conditions are combined with <code>&</code> or <code>,</code> . Only the rows where the condition evaluates to <code>TRUE</code> are kept. The arguments in <code>...</code> are automatically quoted and evaluated in the context of the data frame. They support unquoting and splicing. See <code>vignette("programming", package = "dplyr")</code> for an introduction to these concepts.

Details

The effect of the stored filter conditions on the tables related to the filtered ones is only evaluated in one of the following scenarios:

1. Calling `dm_apply_filters()` or `compute()` (method for dm objects) on a dm: each filtered table potentially reduces the rows of all other tables connected to it by foreign key relations (cascading effect), leaving only the rows with corresponding key values. Tables that are not connected to any table with an active filter are left unchanged. This results in a new dm class object without any filter conditions.
2. Calling `dm_apply_filters_to_tbl()`: the remaining rows of the requested table are calculated by performing a sequence of semi-joins (`dplyr::semi_join()`) starting from each table that has been filtered to the requested table (similar to 1. but only for one table).

Several functions of the dm package will throw an error if filter conditions exist when they are called.

Value

For `dm_filter()`: an updated dm object (filter executed for given table, and condition stored).

For `dm_apply_filters()`: an updated dm object (filter effects evaluated for all tables).

For `dm_apply_filters_to_tbl()`, a table.

Life cycle

These functions are marked "questioning" because it feels wrong to tightly couple filtering with the data model. On the one hand, an overview of active filters is useful when specifying the base data set for an analysis in terms of column selections and row filters. However, these filter condition should be only of informative nature and never affect the results of other operations. We are working on formalizing the semantics of the underlying operations in order to present them in a cleaner interface.

Use `dm_zoom_to()` and `dplyr::filter()` to filter rows without registering the filter.

Examples

```
dm_nyc <- dm_nycflights13()
dm_nyc_filtered <-
  dm_nycflights13() %>%
```

```

dm_filter(airports, name == "John F Kennedy Intl")

dm_apply_filters_to_tbl(dm_nyc_filtered, flights)

dm_nyc_filtered %>%
  dm_apply_filters()

# If you want to keep only those rows in the parent tables
# whose primary key values appear as foreign key values in
# `flights`, you can set a `TRUE` filter in `flights`:
dm_nyc %>%
  dm_filter(flights, 1 == 1) %>%
  dm_apply_filters() %>%
  dm_nrow()
# note that in this example, the only affected table is
# `airports` because the departure airports in `flights` are
# only the three New York airports.

dm_nyc %>%
  dm_filter(planes, engine %in% c("Reciprocating", "4 Cycle")) %>%
  compute()

```

dm_financial

Creates a dm object for the Financial data

Description

Experimental

dm_financial() creates an example `dm` object from the tables at <https://relational.fit.cvut.cz/dataset/Financial>. The connection is established once per session, subsequent calls return the same connection.

dm_financial_sqlite() copies the data to a temporary SQLite database. The data is downloaded once per session, subsequent calls return the same database. The trans table is excluded due to its size.

Usage

```
dm_financial()
```

```
dm_financial_sqlite()
```

Value

A `dm` object.

Examples

```
## Not run:
if (rlang::is_installed("RMariaDB")) {
  dm_financial() %>%
    dm_draw()
}

## End(Not run)
```

dm_flatten_to_tbl	<i>Flatten a part of a dm into a wide table</i>
-------------------	---

Description

dm_flatten_to_tbl() and dm_squash_to_tbl() gather all information of interest in one place in a wide table. Both functions perform a disambiguation of column names and a cascade of joins.

Usage

```
dm_flatten_to_tbl(dm, start, ..., join = left_join)
```

```
dm_squash_to_tbl(dm, start, ..., join = left_join)
```

Arguments

dm	A dm object.
start	The table from which all outgoing foreign key relations are considered when establishing a processing order for the joins. An interesting choice could be for example a fact table in a star schema.
...	Unquoted names of the tables to be included in addition to the start table. The order of the tables here determines the order of the joins. If the argument is empty, all tables that can be reached will be included. If this includes tables that are not direct neighbors of start, it will only work with dm_squash_to_tbl() (given one of the allowed join-methods). tidyselect is supported, see dplyr::select() for details on the semantics.
join	The type of join to be performed, see dplyr::join() .

Details

With ... left empty, this function will join together all the tables of your [dm](#) object that can be reached from the start table, in the direction of the foreign key relations (pointing from the child tables to the parent tables), using the foreign key relations to determine the argument by for the necessary joins. The result is one table with unique column names. Use the ... argument if you would like to control which tables should be joined to the start table.

How does filtering affect the result?

Case 1, either no filter conditions are set in the dm, or set only in the part that is unconnected to the start table: The necessary disambiguations of the column names are performed first. Then all involved foreign tables are joined to the start table successively, with the join function given in the join argument.

Case 2, filter conditions are set for at least one table that is connected to start: First, disambiguation will be performed if necessary. The start table is then calculated using `tbl(dm, "start")`. This implies that the effect of the filters on this table is taken into account. For `right_join`, `full_join` and `nest_join`, an error is thrown if any filters are set because filters will not affect the right hand side tables and the result will therefore be incorrect in general (calculating the effects on all RHS-tables would also be time-consuming, and is not supported; if desired, call `dm_apply_filters()` first to achieve that effect). For all other join types, filtering only the start table is enough because the effect is passed on by successive joins.

Mind that calling `dm_flatten_to_tbl()` with `join = right_join` and no table order determined in the `...` argument will not lead to a well-defined result if two or more foreign tables are to be joined to start. The resulting table would depend on the order the tables that are listed in the dm. Therefore, trying this will result in a warning.

Since `join = nest_join()` does not make sense in this direction (LHS = child table, RHS = parent table: for valid key constraints each nested column entry would be a tibble of one row), an error will be thrown if this method is chosen.

Value

A single table that results from consecutively joining all affected tables to the start table.

See Also

Other flattening functions: `dm_join_to_tbl()`

Examples

```
dm_nycflights13() %>%
  dm_select_tbl(~weather) %>%
  dm_flatten_to_tbl(flights)
```

dm_from_src

Load a dm from a remote data source

Description

`dm_from_src()` creates a [dm](#) from some or all tables in a [src](#) (a database or an environment) or which are accessible via a DBI-Connection. For Postgres and SQL Server databases, primary and foreign keys are imported from the database.

Usage

```
dm_from_src(src = NULL, table_names = NULL, learn_keys = NULL, ...)
```


Arguments

src	A dplyr table source object or a <code>DBI::DBIConnection</code> object is accepted.
table_names	A character vector of the names of the tables to include.
learn_keys	Experimental Set to TRUE to query the definition of primary and foreign keys from the database. Currently works only for Postgres and SQL Server databases. The default attempts to query and issues an informative message.
...	Experimental Additional parameters for the schema learning query. Currently supports schema (default: "public") and table_type (default: "BASE TABLE") for Postgres databases.

Value

A dm object.

Examples

```
dm_from_src_demo <- function() {
  if (!rlang::is_installed("DBI")) {
    message("Install the DBI package to run this example.")
  }

  con <- DBI::dbConnect(
    RMariaDB::MariaDB(),
    username = "guest",
    password = "relational",
    dbname = "Financial_ijs",
    host = "relational.fit.cvut.cz"
  )
  on.exit(DBI::dbDisconnect(con))

  dm_from_src(con)
}
## Not run:
dm_from_src_demo()

## End(Not run)
```

dm_get_all_fks	<i>Get foreign key constraints</i>
----------------	------------------------------------

Description

Get a summary of all foreign key relations in a `dm`.

Usage

```
dm_get_all_fks(dm)
```

Arguments

dm A dm object.

Value

A tibble with the following columns:

child_table child table,
 child_fk_cols foreign key column in child table,
 parent_table parent table.

Compound keys

Currently, keys consisting of more than one column are not supported. **This feature** is planned for dm 0.2.0. Therefore the child_fk_cols column may contain vectors of length greater than one.

See Also

Other foreign key functions: [dm_add_fk\(\)](#), [dm_enum_fk_candidates\(\)](#), [dm_get_fk\(\)](#), [dm_has_fk\(\)](#)

Examples

```
dm_get_all_fks(dm_nycflights13())
```

dm_get_all_pks	<i>Get all primary keys of a dm object</i>
----------------	--

Description

dm_get_all_pks() checks the dm object for set primary keys and returns the tables, the respective primary key columns and their classes.

Usage

```
dm_get_all_pks(dm)
```

Arguments

dm A dm object.

Value

A tibble with the following columns:

table table name,
 pk_cols column name(s) of primary key.

Compound keys

Currently, keys consisting of more than one column are not supported. **This feature** is planned for dm 0.2.0. Therefore the pk_cols column may contain vectors of length greater than one.

See Also

Other primary key functions: [dm_add_pk\(\)](#), [dm_get_pk\(\)](#), [dm_has_pk\(\)](#), [enum_pk_candidates\(\)](#)

Examples

```
dm_nycflights13() %>%  
  dm_get_all_pks()
```

dm_get_filters	<i>Get filter expressions</i>
----------------	-------------------------------

Description

dm_get_filters() returns the filter expressions that have been applied to a dm object. These filter expressions are not intended for evaluation, only for information.

Usage

```
dm_get_filters(x)
```

Arguments

x An object.

Value

A tibble with the following columns:

table table that was filtered,

filter the filter expression,

zoomed logical, does the filter condition relate to the zoomed table.

dm_get_fk	<i>Foreign key column names</i>
-----------	---------------------------------

Description

`dm_get_fk()` returns the names of the columns marked as foreign key of table `table` with respect to table `ref_table` within a `dm` object. If no foreign key is set between the tables, an empty character vector is returned.

Usage

```
dm_get_fk(dm, table, ref_table)
```

Arguments

<code>dm</code>	A <code>dm</code> object.
<code>table</code>	A table in the <code>dm</code> .
<code>ref_table</code>	The table that is referenced from <code>table</code> .

Value

A list of character vectors with the column name(s) of `table`, pointing to the primary key of `ref_table`.

Compound keys

Currently, keys consisting of more than one column are not supported. **This feature** is planned for `dm` 0.2.0. Therefore the function may return vectors of length greater than one in the future.

See Also

Other foreign key functions: `dm_add_fk()`, `dm_enum_fk_candidates()`, `dm_get_all_fks()`, `dm_has_fk()`

Examples

```
dm_nycflights13() %>%  
  dm_get_fk(flights, airports)  
dm_nycflights13(cycle = TRUE) %>%  
  dm_get_fk(flights, airports)
```

dm_get_pk	<i>Primary key column names</i>
-----------	---------------------------------

Description

dm_get_pk() returns the names of the columns marked as primary key of a table of a [dm](#) object. If no primary key is set for the table, an empty character vector is returned.

Usage

```
dm_get_pk(dm, table)
```

Arguments

dm	A dm object.
table	A table in the dm.

Value

A list with character vectors with the column name(s) of the primary keys of table.

Compound keys and multiple primary keys

Currently, keys consisting of more than one column are not supported. **This feature** is planned for dm 0.2.0. Therefore the function may return vectors of length greater than one in the future.

Similarly, each table currently can have only one primary key. This restriction may be lifted in the future. For this reason, and for symmetry with dm_get_fk(), this function returns a list of character vectors.

See Also

Other primary key functions: [dm_add_pk\(\)](#), [dm_get_all_pks\(\)](#), [dm_has_pk\(\)](#), [enum_pk_candidates\(\)](#)

Examples

```
dm_nycflights13() %>%  
  dm_get_pk(flights)  
dm_nycflights13() %>%  
  dm_get_pk(planes)
```

`dm_get_referencing_tables`*Get the names of referencing tables*

Description

This function returns the names of all tables that point to the primary key of a table.

Usage

```
dm_get_referencing_tables(dm, table)
```

Arguments

<code>dm</code>	A dm object.
<code>table</code>	A table in the dm.

Value

A character vector of the names of the tables that point to the primary key of table.

See Also

Other functions utilizing foreign key relations: [dm_is_referenced\(\)](#)

Examples

```
dm_get_referencing_tables(dm_nycflights13(), airports)
dm_get_referencing_tables(dm_nycflights13(), flights)
```

`dm_has_fk`*Check if foreign keys exists*

Description

`dm_has_fk()` checks if a foreign key reference exists between two tables in a dm.

Usage

```
dm_has_fk(dm, table, ref_table)
```

Arguments

<code>dm</code>	A dm object.
<code>table</code>	A table in the dm.
<code>ref_table</code>	The table to be checked if it is referred to.

Value

A boolean value: TRUE if a reference from table to ref_table exists, FALSE otherwise.

See Also

Other foreign key functions: [dm_add_fk\(\)](#), [dm_enum_fk_candidates\(\)](#), [dm_get_all_fks\(\)](#), [dm_get_fk\(\)](#)

Examples

```
dm_nycflights13() %>%
  dm_has_fk(flights, airports)
dm_nycflights13() %>%
  dm_has_fk(airports, flights)
```

dm_has_pk	<i>Check for primary key</i>
-----------	------------------------------

Description

dm_has_pk() checks if a given table has columns marked as its primary key.

Usage

```
dm_has_pk(dm, table)
```

Arguments

- dm A dm object.
- table A table in the dm.

Value

A logical value: TRUE if the given table has a primary key, FALSE otherwise.

See Also

Other primary key functions: [dm_add_pk\(\)](#), [dm_get_all_pks\(\)](#), [dm_get_pk\(\)](#), [enum_pk_candidates\(\)](#)

Examples

```
dm_nycflights13() %>%
  dm_has_pk(flights)
dm_nycflights13() %>%
  dm_has_pk(planes)
```

dm_is_referenced	<i>Check foreign key reference</i>
------------------	------------------------------------

Description

Is a table of a [dm](#) referenced by another table?

Usage

```
dm_is_referenced(dm, table)
```

Arguments

dm	A dm object.
table	A table in the dm.

Value

TRUE if at least one foreign key exists that points to the primary key of the table argument, FALSE otherwise.

See Also

Other functions utilizing foreign key relations: [dm_get_referencing_tables\(\)](#)

Examples

```
dm_nycflights13() %>%
  dm_is_referenced(airports)
dm_nycflights13() %>%
  dm_is_referenced(flights)
```

dm_join_to_tbl	<i>Join two tables</i>
----------------	------------------------

Description

A join of a desired type is performed between table_1 and table_2. The two tables need to be directly connected by a foreign key relation. Since this function is a wrapper around [dm_flatten_to_tbl\(\)](#), the LHS of the join will always be a "child table", i.e. a table referencing the other table.

Usage

```
dm_join_to_tbl(dm, table_1, table_2, join = left_join)
```


Arguments

dm	A dm object.
table_1	One of the tables involved in the join.
table_2	The second table of the join.
join	The type of join to be performed, see dplyr::join() .

Value

The resulting table of the join.

See Also

Other flattening functions: [dm_flatten_to_tbl\(\)](#)

Examples

```
dm_join_to_tbl(dm_nycflights13(), airports, flights)

# same result is achieved with:
dm_join_to_tbl(dm_nycflights13(), flights, airports)

# this gives an error, because the tables are not directly linked to each other:
try(dm_join_to_tbl(dm_nycflights13(), airlines, airports))
```

dm_nrow	<i>Number of rows</i>
---------	-----------------------

Description

Returns a named vector with the number of rows for each table.

Usage

```
dm_nrow(dm)
```

Arguments

dm	A dm object.
----	------------------------------

Value

A named vector with the number of rows for each table.

Examples

```
dm_nycflights13() %>%
  dm_filter(airports, faa %in% c("EWR", "LGA")) %>%
  dm_apply_filters() %>%
  dm_nrow()
```

dm_nycflights13	<i>Creates a dm object for the nycflights13 data</i>
-----------------	---

Description

Creates an example **dm** object from the tables in **nycflights13**, along with the references. See [nycflights13::flights](#) for a description of the data. As described in [nycflights13::planes](#), the relationship between the `flights` table and the `planes` tables is "weak", it does not satisfy data integrity constraints.

Usage

```
dm_nycflights13(cycle = FALSE, color = TRUE, subset = TRUE)
```

Arguments

<code>cycle</code>	Boolean. If <code>FALSE</code> (default), only one foreign key relation (from <code>flights\$origin</code> to <code>airports\$faa</code>) between the <code>flights</code> table and the <code>airports</code> table is established. If <code>TRUE</code> , a <code>dm</code> object with a double reference between those tables will be produced.
<code>color</code>	Boolean, if <code>TRUE</code> (default), the resulting <code>dm</code> object will have colors assigned to different tables for visualization with <code>dm_draw()</code> .
<code>subset</code>	Boolean, if <code>TRUE</code> (default), the <code>flights</code> table is reduced to flights with column <code>day</code> equal to 10.

Value

A `dm` object consisting of `nycflights13` tables, complete with primary and foreign keys and optionally colored.

Examples

```
if (rlang::is_installed("nycflights13")) {
  dm_nycflights13() %>%
    dm_draw()
}
```

dm_paste	<i>Create R code for a dm object</i>
----------	--------------------------------------

Description

`dm_paste()` takes an existing `dm` and emits the code necessary for its creation.

Usage

```
dm_paste(dm, select = NULL, ..., tab_width = 2, options = NULL, path = NULL)
```

Arguments

dm	A dm object.
select	Deprecated, see "select" in the options argument.
...	Must be empty.
tab_width	Indentation width for code from the second line onwards
options	Formatting options. A character vector containing some of: <ul style="list-style-type: none"> • "tables": <code>tibble()</code> calls for empty table definitions derived from <code>dm_ptype()</code>, overrides "select". • "select": <code>dm_select()</code> statements for columns that are part of the dm. • "keys": <code>dm_add_pk()</code> and <code>dm_add_fk()</code> statements for adding keys. • "color": <code>dm_set_colors()</code> statements to set color. • "all": All options above except "select" Default NULL is equivalent to <code>c("keys", "color")</code>
path	Output file, if NULL the code is printed to the console.

Details

The code emitted by the function reproduces the structure of the dm object. The options argument controls the level of detail: keys, colors, table definitions. Data in the tables is never included, see `dm_ptype()` for the underlying logic.

Value

Code for producing the prototype of the given dm.

Examples

```
dm() %>%
  dm_paste()

dm_nycflights13() %>%
  dm_paste()

dm_nycflights13() %>%
  dm_paste(options = "select")
```

dm_ptype	<i>Prototype for a dm object</i>
----------	----------------------------------

Description

Experimental

The prototype contains all tables, all primary and foreign keys, but no data. All tables are truncated and converted to zero-row tibbles. Column names retain their type. This is useful for performing creation and population of a database in separate steps.

Usage

```
dm_ptype(dm)
```

Arguments

dm	A dm object.
----	--------------

Examples

```
## Not run:
dm_financial() %>%
  dm_ptype()

dm_financial() %>%
  dm_ptype() %>%
  dm_nrow()

## End(Not run)
```

dm_rename	<i>Rename columns</i>
-----------	-----------------------

Description

Rename the columns of your `dm` using syntax that is similar to `dplyr::rename()`.

Usage

```
dm_rename(dm, table, ...)
```

Arguments

dm	A dm object.
table	A table in the dm.
...	<p>One or more unquoted expressions separated by commas. You can treat variable names as if they were positions, and use expressions like x:y to select the ranges of variables.</p> <p>Use named arguments, e.g. new_name = old_name, to rename the selected variables.</p> <p>The arguments in ... are automatically quoted and evaluated in a context where column names represent column positions. They also support unquoting and splicing. See <code>vignette("programming", package = "dplyr")</code> for an introduction to those concepts.</p> <p>See <code>select</code> helpers for more details, and the examples about <code>tidyselect</code> helpers, such as <code>starts_with()</code>, <code>everything()</code>, ...</p>

Details

If key columns are renamed, then the meta-information of the dm is updated accordingly.

Value

An updated dm with the columns of table renamed.

Examples

```
dm_nycflights13() %>%
  dm_rename(airports, code = faa, altitude = alt)
```

dm_rm_tbl	<i>Remove tables</i>
-----------	----------------------

Description

Removes one or more tables from a [dm](#).

Usage

```
dm_rm_tbl(dm, ...)
```

Arguments

dm	A dm object.
...	One or more unquoted table names to remove from the dm. <code>tidyselect</code> is supported, see <code>dplyr::select()</code> for details on the semantics.

Value

The dm without the removed table(s) that were present in the initial dm.

See Also

`dm_add_tbl()`, `dm_select_tbl()`

Examples

```
dm_nycflights13() %>%
  dm_rm_tbl(airports)
```

dm_select	Select columns
-----------	----------------

Description

Select columns of your `dm` using syntax that is similar to `dplyr::select()`.

Usage

```
dm_select(dm, table, ...)
```

Arguments

dm	A dm object.
table	A table in the dm.
...	<p>One or more unquoted expressions separated by commas. You can treat variable names as if they were positions, and use expressions like <code>x:y</code> to select the ranges of variables.</p> <p>Use named arguments, e.g. <code>new_name = old_name</code>, to rename the selected variables.</p> <p>The arguments in <code>...</code> are automatically quoted and evaluated in a context where column names represent column positions. They also support unquoting and splicing. See <code>vignette("programming", package = "dplyr")</code> for an introduction to those concepts.</p> <p>See <code>select</code> helpers for more details, and the examples about <code>tidyselect</code> helpers, such as <code>starts_with()</code>, <code>everything()</code>, ...</p>

Details

If key columns are renamed, then the meta-information of the dm is updated accordingly. If key columns are removed, then all related relations are dropped as well.

Value

An updated dm with the columns of `table` reduced and/or renamed.

Examples

```
dm_nycflights13() %>%  
  dm_select(airports, code = faa, altitude = alt)
```

dm_select_tbl	<i>Select and rename tables</i>
---------------	---------------------------------

Description

dm_select_tbl() keeps the selected tables and their relationships, optionally renaming them.

dm_rename_tbl() renames tables.

Usage

```
dm_select_tbl(dm, ...)
```

```
dm_rename_tbl(dm, ...)
```

Arguments

dm	A dm object.
...	One or more table names of the tables of the dm object. tidyselect is supported, see dplyr::select() for details on the semantics.

Value

The input dm with tables renamed or removed.

See Also

[dm_rm_tbl\(\)](#)

Examples

```
dm_nycflights13() %>%  
  dm_select_tbl(airports, fl = flights)  
dm_nycflights13() %>%  
  dm_rename_tbl(ap = airports, fl = flights)
```

dm_zoom_to

*Mark table for manipulation***Description**

Zooming to a table of a `dm` allows for the use of many `dplyr`-verbs directly on this table, while retaining the context of the `dm` object.

`dm_zoom_to()` zooms to the given table.

`dm_update_zoomed()` overwrites the originally zoomed table with the manipulated table. The filter conditions for the zoomed table are added to the original filter conditions.

`dm_insert_zoomed()` adds a new table to the `dm`.

`dm_discard_zoomed()` discards the zoomed table and returns the `dm` as it was before zooming.

Please refer to `vignette("dm-zoom-to-table", package = "dm")` for a more detailed introduction.

Usage

```
dm_zoom_to(dm, table)
```

```
dm_insert_zoomed(dm, new_tbl_name = NULL, repair = "unique", quiet = FALSE)
```

```
dm_update_zoomed(dm)
```

```
dm_discard_zoomed(dm)
```

Arguments

<code>dm</code>	A <code>dm</code> object.
<code>table</code>	A table in the <code>dm</code> .
<code>new_tbl_name</code>	Name of the new table.
<code>repair</code>	<p>Either a string or a function. If a string, it must be one of "check_unique", "minimal", "unique", or "universal". If a function, it is invoked with a vector of minimal names and must return minimal names, otherwise an error is thrown.</p> <ul style="list-style-type: none"> Minimal names are never <code>NULL</code> or <code>NA</code>. When an element doesn't have a name, its minimal name is an empty string. Unique names are unique. A suffix is appended to duplicate names to make them unique. Universal names are unique and syntactic, meaning that you can safely use the names as variables without causing a syntax error. <p>The "check_unique" option doesn't perform any name repair. Instead, an error is raised if the names don't suit the "unique" criteria.</p>
<code>quiet</code>	By default, the user is informed of any renaming caused by repairing the names. This only concerns unique and universal repairing. Set <code>quiet</code> to <code>TRUE</code> to silence the messages.

Details

Whenever possible, the key relations of the original table are transferred to the resulting table when using `dm_insert_zoomed()` or `dm_update_zoomed()`.

Functions from `dplyr` that are supported for a `zoomed_dm`: `group_by()`, `summarise()`, `mutate()`, `transmute()`, `filter()`, `select()`, `rename()` and `ungroup()`. You can use these functions just like you would with a normal table.

In addition to filtering the zoomed table, the filter condition from `filter()` is also stored in the `dm`. Depending on which function you use to return to a normal `dm`, one of the following happens:

1. `dm_discard_zoomed()`: all filter conditions for the zoomed table are discarded
2. `dm_update_zoomed()`: the filter conditions of the original table and those of the zoomed table are combined
3. `dm_insert_zoomed()`: the filter conditions of the original table stay there and those of the zoomed table are transferred to the new table of the `dm`

Furthermore, the different `join()`-variants from `dplyr` are also supported (apart from `nest_join()`). The join-methods for `zoomed_dm` have an extra argument `select` that allows choosing the columns of the RHS table.

And – last but not least – also the `tidyr`-functions `unite()` and `separate()` are supported for `zoomed_dm`.

Value

For `dm_zoom_to()`: A `zoomed_dm` object.

For `dm_insert_zoomed()`, `dm_update_zoomed()` and `dm_discard_zoomed()`: A `dm` object.

Examples

```
flights_zoomed <- dm_zoom_to(dm_nycflights13(), flights)

flights_zoomed

flights_zoomed_transformed <-
  flights_zoomed %>%
    mutate(am_pm_dep = ifelse(dep_time < 1200, "am", "pm")) %>%
    # `by`-argument of `left_join()` can be explicitly given
    # otherwise the key-relation is used
    left_join(airports) %>%
    select(year:dep_time, am_pm_dep, everything())

flights_zoomed_transformed

# replace table `flights` with the zoomed table
flights_zoomed_transformed %>%
  dm_update_zoomed()

# insert the zoomed table as a new table
flights_zoomed_transformed %>%
  dm_insert_zoomed("extended_flights") %>%
```

```

dm_draw()

# discard the zoomed table
flights_zoomed_transformed %>%
  dm_discard_zoomed()

```

dplyr_join

dplyr join methods for zoomed dm objects

Description

Use these methods without the '.zoomed_dm' suffix (see examples).

Usage

```

## S3 method for class 'zoomed_dm'
left_join(x, y, by = NULL, copy = NULL, suffix = NULL, select = NULL, ...)

## S3 method for class 'zoomed_dm'
inner_join(x, y, by = NULL, copy = NULL, suffix = NULL, select = NULL, ...)

## S3 method for class 'zoomed_dm'
full_join(x, y, by = NULL, copy = NULL, suffix = NULL, select = NULL, ...)

## S3 method for class 'zoomed_dm'
right_join(x, y, by = NULL, copy = NULL, suffix = NULL, select = NULL, ...)

## S3 method for class 'zoomed_dm'
semi_join(x, y, by = NULL, copy = NULL, suffix = NULL, select = NULL, ...)

## S3 method for class 'zoomed_dm'
anti_join(x, y, by = NULL, copy = NULL, suffix = NULL, select = NULL, ...)

```

Arguments

x, y	tbls to join. x is the zoomed_dm and y is another table in the dm.
by	If left NULL (default), the join will be performed by via the foreign key relation that exists between the originally zoomed table (now x) and the other table (y). If you provide a value (for the syntax see dplyr::join), you can also join tables that are not connected in the dm.
copy	Disabled, since all tables in a dm are by definition on the same src.
suffix	Disabled, since columns are disambiguated automatically if necessary, changing the column names to table_name.column_name.
select	Select a subset of the RHS-table 's columns, the syntax being select = c(col_1,col_2,col_3) (unquoted or quoted). This argument is specific for the join-methods for zoomed_dm. The table's by column(s) are automatically added if missing in the selection.
...	see dplyr::join

Examples

```

flights_dm <- dm_nycflights13()
dm_zoom_to(flights_dm, flights) %>%
  left_join(airports, select = c(faa, name))

# this should illustrate that tables don't necessarily need to be connected
dm_zoom_to(flights_dm, airports) %>%
  semi_join(airlines, by = "name")

```

dplyr_table_manipulation

dplyr table manipulation methods for zoomed dm objects

Description

Use these methods without the '.zoomed_dm' suffix (see examples).

Usage

```

## S3 method for class 'zoomed_dm'
filter(.data, ...)

## S3 method for class 'zoomed_dm'
mutate(.data, ...)

## S3 method for class 'zoomed_dm'
transmute(.data, ...)

## S3 method for class 'zoomed_dm'
select(.data, ...)

## S3 method for class 'zoomed_dm'
rename(.data, ...)

## S3 method for class 'zoomed_dm'
distinct(.data, ..., .keep_all = FALSE)

## S3 method for class 'zoomed_dm'
arrange(.data, ...)

## S3 method for class 'zoomed_dm'
slice(.data, ..., .keep_pk = NULL)

## S3 method for class 'zoomed_dm'
group_by(.data, ...)

## S3 method for class 'zoomed_dm'

```

```

ungroup(x, ...)

## S3 method for class 'zoomed_dm'
summarise(.data, ...)

## S3 method for class 'zoomed_dm'
pull(.data, var = -1, ...)

```

Arguments

.data	object of class zoomed_dm
...	see corresponding function in package dplyr or tidyr
.keep_all	For distinct.zoomed_dm(): see dplyr::distinct
.keep_pk	For slice.zoomed_dm: Logical, if TRUE, the primary key will be retained during this transformation. If FALSE, it will be dropped. By default, the value is NULL, which causes the function to issue a message in case a primary key is available for the zoomed table. This argument is specific for the slice.zoomed_dm() method.
x	For ungroup.zoomed_dm: object of class zoomed_dm
var	<p>A variable specified as:</p> <ul style="list-style-type: none"> • a literal variable name • a positive integer, giving the position counting from the left • a negative integer, giving the position counting from the right. <p>The default returns the last column (on the assumption that's the column you've created most recently).</p> <p>This argument is taken by expression and supports quasiquotation (you can unquote column names and column locations).</p>

Examples

```

zoomed <- dm_nycflights13() %>%
  dm_zoom_to(flights) %>%
  group_by(month) %>%
  arrange(desc(day)) %>%
  summarize(avg_air_time = mean(air_time, na.rm = TRUE))
zoomed
dm_insert_zoomed(zoomed, new_tbl_name = "avg_air_time_per_month")

```

enum_pk_candidates	<i>Primary key candidate</i>
--------------------	------------------------------

Description

Questioning

enum_pk_candidates() checks for each column of a table if the column contains only unique values, and is thus a suitable candidate for a primary key of the table.

dm_enum_pk_candidates() performs these checks for a table in a [dm](#) object.

Usage

```
enum_pk_candidates(table)

dm_enum_pk_candidates(dm, table)
```

Arguments

table	A table in the dm.
dm	A dm object.

Value

A tibble with the following columns:

columns	columns of table,
candidate	boolean: are these columns a candidate for a primary key,
why	if not a candidate for a primary key column, explanation for this.

Life cycle

These functions are marked "questioning" because we are not yet sure about the interface, in particular if we need both `dm_enum...()` and `enum...()` variants. Changing the interface later seems harmless because these functions are most likely used interactively.

See Also

Other primary key functions: [dm_add_pk\(\)](#), [dm_get_all_pks\(\)](#), [dm_get_pk\(\)](#), [dm_has_pk\(\)](#)

Examples

```
nycflights13::flights %>%
  enum_pk_candidates()

dm_nycflights13() %>%
  dm_enum_pk_candidates(airports)
```

examine_cardinality	<i>Check table relations</i>
---------------------	------------------------------

Description

All `check_cardinality_?_?()` functions test the following conditions:

1. Is `pk_column` is a unique key for `parent_table`?
2. Is the set of values in `fk_column` of `child_table` a subset of the set of values of `pk_column`?
3. Does the relation between the two tables of the data model meet the cardinality requirements?

`examine_cardinality()` also checks the first two points and subsequently determines the type of cardinality.

Usage

```

check_cardinality_0_n(parent_table, pk_column, child_table, fk_column)

check_cardinality_1_n(parent_table, pk_column, child_table, fk_column)

check_cardinality_1_1(parent_table, pk_column, child_table, fk_column)

check_cardinality_0_1(parent_table, pk_column, child_table, fk_column)

examine_cardinality(parent_table, pk_column, child_table, fk_column)

```

Arguments

parent_table	Data frame.
pk_column	Column of parent_table that has to be one of its unique keys.
child_table	Data frame.
fk_column	Column of child_table that has to be a foreign key to pk_column in parent_table.

Details

All cardinality-functions accept a parent table (data frame), a column name of this table, a child table, and a column name of the child table. The given column of the parent table has to be one of its unique keys (no duplicates are allowed). Furthermore, in all cases, the set of values of the child table's column has to be a subset of the set of values of the parent table's column.

The cardinality specifications 0_n, 1_n, 0_1, 1_1 refer to the expected relation that the child table has with the parent table. The numbers 0, 1 and n refer to the number of values in the column of the child table that correspond to each value of the column of the parent table. n means "more than one" in this context, with no upper limit.

0_n means, that each value of the pk_column has at least 0 and at most n corresponding values in the column of the child table (which translates to no further restrictions).

1_n means, that each value of the pk_column has at least 1 and at most n corresponding values in the column of the child table. This means that there is a "surjective" mapping from the child table to the parent table w.r.t. the specified columns, i.e. for each parent table column value there exists at least one equal child table column value.

0_1 means, that each value of the pk_column has at least 0 and at most 1 corresponding values in the column of the child table. This means that there is a "injective" mapping from the child table to the parent table w.r.t. the specified columns, i.e. no parent table column value is addressed multiple times. But not all of the parent table column values have to be referred to.

1_1 means, that each value of the pk_column has exactly 1 corresponding value in the column of the child table. This means that there is a "bijective" ("injective" AND "surjective") mapping between the child table and the parent table w.r.t. the specified columns, i.e. the sets of values of the two columns are equal and there are no duplicates in either of them.

Finally, examine_cardinality() tests for and returns the nature of the relationship (injective, surjective, bijective, or none of these) between the two given columns. If either pk_column is not a unique key of parent_table or the values of fk_column are not a subset of the values in pk_column, the requirements for a cardinality test is not fulfilled. No error will be thrown, but the result will contain the information which prerequisite was violated.

Value

For `check_cardinality_?()`: Functions return `parent_table`, invisibly, if the check is passed, to support pipes. Otherwise an error is thrown and the reason for it is explained.

For `examine_cardinality()`: Returns a character variable specifying the type of relationship between the two columns.

Examples

```
d1 <- tibble::tibble(a = 1:5)
d2 <- tibble::tibble(c = c(1:5, 5))
d3 <- tibble::tibble(c = 1:4)
# This does not pass, `c` is not unique key of d2:
try(check_cardinality_0_n(d2, c, d1, a))

# This passes, multiple values in d2$c are allowed:
check_cardinality_0_n(d1, a, d2, c)

# This does not pass, injectivity is violated:
try(check_cardinality_1_1(d1, a, d2, c))

# This passes:
check_cardinality_0_1(d1, a, d3, c)

# Returns the kind of cardinality
examine_cardinality(d1, a, d2, c)
```

n an integer vector of length up to `dim(x)` (or 1, for non-dimensioned objects). Values specify the indices to be selected in the corresponding dimension (or along the length) of the object. A positive value of `n[i]` includes the first/last `n[i]` indices in that dimension, while a negative value excludes the last/first `abs(n[i])`, including all remaining indices. NA or non-specified values (when `length(n) < length(dim(x))`) select all indices in that dimension. Must contain at least one non-missing value.

... arguments to be passed to or from other methods.

Details

see manual for the corresponding functions in **utils**.

Value

A `zoomed_dm` object.

Examples

```
zoomed <- dm_nycflights13() %>%
  dm_zoom_to(flights) %>%
  head(4)
zoomed
dm_insert_zoomed(zoomed, new_tbl_name = "head_flights")
```

`pull_tbl`

Retrieve a table

Description

This function has methods for both `dm` classes:

1. With `pull_tbl.dm()` you can chose which table of the `dm` you want to retrieve.
2. With `pull_tbl.zoomed_dm()` you will retrieve the zoomed table in the current state.

Usage

```
pull_tbl(dm, table)
```

Arguments

dm A `dm` object.

table One unquoted table name for `pull_tbl.dm()`, ignored for `pull_tbl.zoomed_dm()`.

Value

The requested table

Examples

```
# For an unzoomed dm you need to specify the table to pull:
dm_nycflights13() %>%
  pull_tbl(airports)

# If zoomed, pulling detaches the zoomed table from the dm:
dm_nycflights13() %>%
  dm_zoom_to(airports) %>%
  pull_tbl()
```

reunite_parent_child *Merge two tables that are linked by a foreign key relation*

Description

Questioning

Perform table fusion by combining two tables by a common (key) column, and then removing this column.

reunite_parent_child(): After joining the two tables by the column id_column, this column will be removed. The transformation is roughly the inverse of what decompose_table() does.

reunite_parent_child_from_list(): After joining the two tables by the column id_column, id_column is removed.

This function is almost exactly the inverse of decompose_table() (the order of the columns is not retained, and the original row names are lost).

Usage

```
reunite_parent_child(child_table, parent_table, id_column)
```

```
reunite_parent_child_from_list(list_of_parent_child_tables, id_column)
```

Arguments

child_table	Table (possibly created by decompose_table()) that references parent_table
parent_table	Table (possibly created by decompose_table()).
id_column	Identical name of referencing / referenced column in child_table/parent_table.
list_of_parent_child_tables	Cf arguments child_table and parent_table from reunite_parent_child(), but both in a named list (as created by decompose_table()).

Value

A wide table produced by joining the two given tables.

Life cycle

These functions are marked "questioning" because they feel more useful when applied to a table in a dm object.

See Also

Other table surgery functions: [decompose_table\(\)](#)

Examples

```
decomposed_table <- decompose_table(mtcars, new_id, am, gear, carb)
ct <- decomposed_table$child_table
pt <- decomposed_table$parent_table

reunite_parent_child(ct, pt, new_id)
reunite_parent_child_from_list(decomposed_table, new_id)
```

tbl.dm

dplyr table retrieval, table info and DB interaction methods

Description

Use these methods without the '.dm' or '.zoomed_dm' suffix (see examples).

Usage

```
## S3 method for class 'dm'
tbl(src, from, ...)

## S3 method for class 'dm'
compute(x, ...)

## S3 method for class 'zoomed_dm'
compute(x, ...)

## S3 method for class 'dm'
src_tbls(x, ...)

## S3 method for class 'dm'
copy_to(
  dest,
  df,
  name = deparse(substitute(df)),
  overwrite = FALSE,
  temporary = TRUE,
  repair = "unique",
  quiet = FALSE,
```

```

    ...
  )

## S3 method for class 'dm'
collect(x, ...)
```

Arguments

src	A dm object.
from	A length one character variable containing the name of the requested table
...	See original function documentation
x	Either a dm or a zoomed_dm; the latter leads to an error for src_tbls.dm()
dest	For copy_to.dm(): The dm object to which a table should be copied.
df	For copy_to.dm(): A table (can be on a different src)
name	For copy_to.dm(): See dplyr::copy_to
overwrite	For copy_to.dm(): See dplyr::copy_to ; TRUE leads to an error
temporary	For copy_to.dm(): If the dm is on a DB, the copied version of df will only be written temporarily to the DB. After the connection is reset it will no longer be available.
repair, quiet	Name repair options; cf. vctrs::vec_as_names

tidyr_table_manipulation

tidyr *table manipulation methods for zoomed dm objects*

Description

Use these methods without the '.zoomed_dm' suffix (see examples).

Usage

```
## S3 method for class 'zoomed_dm'
unite(data, col, ..., sep = "_", remove = TRUE, na.rm = FALSE)

## S3 method for class 'zoomed_dm'
separate(data, col, into, sep = "[^[:alnum:]]+", remove = TRUE, ...)
```

Arguments

data	object of class zoomed_dm
col	For unite.zoomed_dm: see tidyr::unite For separate.zoomed_dm: see tidyr::separate
...	For unite.zoomed_dm: see tidyr::unite For separate.zoomed_dm: see tidyr::separate

sep	For unite.zoomed_dm: see tidyr::unite For separate.zoomed_dm: see tidyr::separate
remove	For unite.zoomed_dm: see tidyr::unite For separate.zoomed_dm: see tidyr::separate
na.rm	see tidyr::unite
into	see tidyr::separate

Examples

```
zoom_united <- dm_nycflights13() %>%  
  dm_zoom_to(flights) %>%  
  select(year, month, day) %>%  
  unite("month_day", month, day)  
zoom_united  
zoom_united %>%  
  separate(month_day, c("month", "day"))
```

Index

- * **DB interaction functions**
 - copy_dm_to, 6
- * **flattening functions**
 - dm_flatten_to_tbl, 23
 - dm_join_to_tbl, 32
- * **foreign key functions**
 - dm_add_fk, 10
 - dm_enum_fk_candidates, 18
 - dm_get_all_fks, 25
 - dm_get_fk, 28
 - dm_has_fk, 30
- * **functions utilizing foreign key relations**
 - dm_get_referencing_tables, 30
 - dm_is_referenced, 32
- * **primary key functions**
 - dm_add_pk, 12
 - dm_get_all_pks, 26
 - dm_get_pk, 29
 - dm_has_pk, 31
 - enum_pk_candidates, 44
- * **table surgery functions**
 - decompose_table, 7
 - reunite_parent_child, 49
- anti_join.zoomed_dm(dplyr_join), 42
- arrange.zoomed_dm
 - (dplyr_table_manipulation), 43
- as_dm(dm), 8
- as_tibble(), 19
- check_cardinality_0_1
 - (examine_cardinality), 45
- check_cardinality_0_n
 - (examine_cardinality), 45
- check_cardinality_1_1
 - (examine_cardinality), 45
- check_cardinality_1_n
 - (examine_cardinality), 45
- check_key, 3
- check_key(), 10
- check_set_equality, 4
- check_subset, 5
- check_subset(), 10
- collect_dm(tbl_dm), 50
- compute_dm(tbl_dm), 50
- compute.zoomed_dm(tbl_dm), 50
- copy_dm_to, 6
- copy_dm_to(), 10
- copy_to_dm(tbl_dm), 50
- DBI::DBIConnection, 6, 9, 25
- decompose_table, 7, 50
- decompose_table(), 10
- DiagrammeR::grViz(), 17
- distinct.zoomed_dm
 - (dplyr_table_manipulation), 43
- dm, 6, 8, 12, 14, 16, 18, 20, 22–26, 28, 29, 32–34, 36–40, 44
- dm_add_fk, 10, 19, 26, 28, 31
- dm_add_fk(), 10, 35
- dm_add_pk, 12, 27, 29, 31, 45
- dm_add_pk(), 10, 35
- dm_add_tbl, 14
- dm_add_tbl(), 38
- dm_apply_filters(dm_filter), 20
- dm_apply_filters_to_tbl(dm_filter), 20
- dm_disambiguate_cols, 15
- dm_discard_zoomed(dm_zoom_to), 40
- dm_draw, 16
- dm_draw(), 10
- dm_enum_fk_candidates, 11, 18, 26, 28, 31
- dm_enum_pk_candidates
 - (enum_pk_candidates), 44
- dm_examine_constraints, 19
- dm_filter, 20
- dm_filter(), 10
- dm_financial, 22
- dm_financial_sqlite(dm_financial), 22
- dm_flatten_to_tbl, 23, 33
- dm_flatten_to_tbl(), 32

dm_from_src, 24
 dm_from_src(), 10
 dm_get_all_fks, 11, 19, 25, 28, 31
 dm_get_all_pks, 13, 26, 29, 31, 45
 dm_get_available_colors(dm_draw), 16
 dm_get_colors(dm_draw), 16
 dm_get_con(dm), 8
 dm_get_filters, 27
 dm_get_fk, 11, 19, 26, 28, 31
 dm_get_pk, 13, 27, 29, 31, 45
 dm_get_referencing_tables, 30, 32
 dm_get_src(dm), 8
 dm_get_tables(dm), 8
 dm_has_fk, 11, 19, 26, 28, 30
 dm_has_pk, 13, 27, 29, 31, 45
 dm_insert_zoomed(dm_zoom_to), 40
 dm_is_referenced, 30, 32
 dm_join_to_tbl, 24, 32
 dm_join_to_tbl(), 10
 dm_nrow, 33
 dm_nycflights13, 34
 dm_nycflights13(), 10
 dm_paste, 34
 dm_ptype, 36
 dm_ptype(), 35
 dm_rename, 36
 dm_rename_tbl(dm_select_tbl), 39
 dm_rm_fk(dm_add_fk), 10
 dm_rm_pk(dm_add_pk), 12
 dm_rm_tbl, 37
 dm_rm_tbl(), 14, 39
 dm_select, 38
 dm_select(), 35
 dm_select_tbl, 39
 dm_select_tbl(), 10, 38
 dm_set_colors(dm_draw), 16
 dm_set_colors(), 35
 dm_squash_to_tbl(dm_flatten_to_tbl), 23
 dm_update_zoomed(dm_zoom_to), 40
 dm_zoom_to, 40
 dm_zoom_to(), 21
 dplyr::copy_to, 51
 dplyr::copy_to(), 6
 dplyr::distinct, 44
 dplyr::filter(), 20, 21
 dplyr::join, 42
 dplyr::join(), 23, 33
 dplyr::select(), 17, 23, 37, 39
 dplyr::semi_join(), 21
 dplyr::src_dbi, 6
 dplyr_join, 42
 dplyr_table_manipulation, 43
 enum_fk_candidates
 (dm_enum_fk_candidates), 18
 enum_pk_candidates, 13, 27, 29, 31, 44
 examine_cardinality, 45
 examine_cardinality(), 10
 filter.zoomed_dm
 (dplyr_table_manipulation), 43
 full_join.zoomed_dm(dplyr_join), 42
 group_by.zoomed_dm
 (dplyr_table_manipulation), 43
 head.zoomed_dm, 47
 inner_join.zoomed_dm(dplyr_join), 42
 is_dm(dm), 8
 left_join.zoomed_dm(dplyr_join), 42
 mutate(), 14
 mutate.zoomed_dm
 (dplyr_table_manipulation), 43
 new_dm(dm), 8
 nycflights13::flights, 34
 nycflights13::planes, 34
 pull.zoomed_dm
 (dplyr_table_manipulation), 43
 pull_tbl, 48
 quasiquotation, 44
 rename.zoomed_dm
 (dplyr_table_manipulation), 43
 reunite_parent_child, 8, 49
 reunite_parent_child_from_list
 (reunite_parent_child), 49
 right_join.zoomed_dm(dplyr_join), 42
 select.zoomed_dm
 (dplyr_table_manipulation), 43
 semi_join.zoomed_dm(dplyr_join), 42
 separate.zoomed_dm
 (tidyr_table_manipulation), 51

`slice.zoomed_dm`
 (`dplyr_table_manipulation`), 43
`src`, 24
`src_tbls.dm(tbl.dm)`, 50
`summarise.zoomed_dm`
 (`dplyr_table_manipulation`), 43

`tail.zoomed_dm(head.zoomed_dm)`, 47
`tbl`, 8, 9
`tbl.dm`, 50
`tibble()`, 35
`tidyr::separate`, 51, 52
`tidyr::unite`, 51, 52
`tidyr_table_manipulation`, 51
`transmute.zoomed_dm`
 (`dplyr_table_manipulation`), 43

`ungroup.zoomed_dm`
 (`dplyr_table_manipulation`), 43
`unite.zoomed_dm`
 (`tidyr_table_manipulation`), 51

`validate_dm(dm)`, 8
`vctrs::vec_as_names`, 51
`vctrs::vec_as_names()`, 9